

4-071167

TO:  
STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING  
130 SOUTH MARKET, SUITE 2078  
WICHITA, KANSAS 67202

API Number: 15-195-22,170-00-00

1-26

SW SE NW \_\_\_\_\_ /4 SEC. 32, 13 S, 21 W  
2310 feet from NS section line  
1650 feet from W section line

Operator license# 9860

Lease: Bongarts Well # 2

Operator: Castle Ressources, Inc.

County: Trego

Address: 1200 East 27th - #C  
Hays, Kansas 67601-2120  
Jerry Green

Well total depth 4125 <sup>134.06</sup> feet  
Conductor Pipe: 0 inch @ 0 feet  
Surface pipe 8 5/8 Inch @ 226 feet

Aband. oil well \_\_\_\_\_, Gas well \_\_\_\_\_, Input well \_\_\_\_\_, SWD \_\_\_\_\_, D & A X

Plugging contractor: Discovery Drilling - Halliburton License# -

Address: Hays, Kansas 67601 - Hays, Kansas 67601

Company to plug at: Hour: A.M. Day: 26 Month: January Year: 1996

Plugging proposal received from: Tom Alm

Company: Discovery Drilling, Inc. Phone: 913-625-5155

Were: 8 5/8" - 226' S.P. cwc. w/135 sxs 60/40 pozmix - 2% gel - 3% c.c. By Halliburton.  
Elv. 2300' - Anhy. 1697' - No circulation problems. Arbuckle 4125'. Mud condition 53 vis. -  
9.3 wt. - 9.0 water loss - 3000 ppm cl at 4125'. Proposal 225 sxs 60/40 pozmix - 6% gel and  
1/4# flocele per sack - spot and displace all cement through drill pipe - heavy mud between  
all plugs. 25 sxs at 4080' - 25 sxs at 1710' - 100 sxs at 900' - 40 sxs at 276' - 10 sxs 40'  
- 15 sxs in rathole (circulate) - 10 sxs in mousehole (circulate)

Plugging Proposal Received by: Marion J. Schmidt

Plugging operations attended by agent? All[ ], Part[ ], None[ X ]

Completed: Hour: 7:00 A.M., Day: 26, Month: January, Year: 1996

Actual plugging report: Castle Resources ordered 225 sxs 60/40 pozmix - 6% gel and 1/4#  
flocele per sack. Spotted and displaced all cement through drill pipe with heavy mud between  
all plugs.

- 1st. Plug at 4080' w/25 sxs. cement.
- 2nd. Plug at 1710' w/25 sxs. cement.
- 3rd. Plug at 900' w/100 sxs. cement.
- 4th. Plug at 276' w/40 sxs. cement. 15 sxs in rathole (circulated)
- 5th. Plug at 40' w/10 sxs. cement. 10 sxs in mousehole (circulated)

Remarks: Cemented by Halliburton.

Condition of casing(in hole): GOOD \_\_\_\_\_ BAD \_\_\_\_\_ Anhy.plug: YES X NO \_\_\_\_\_  
Bottom plug(in place): YES \_\_\_\_\_, CALC \_\_\_\_\_, NO \_\_\_\_\_ Dakota plug: YES X, NO \_\_\_\_\_  
Plugged through TUBING \_\_\_\_\_, CASING \_\_\_\_\_ Elevation: \_\_\_\_\_ GL

I did[ ] / did not[ X ] observe the plugging.

INVOICED

HA

Marion J. Schmidt  
(agent)  
Form CP-2/3

DWS 2-6-96  
44826  
RWAB  
1-26

RECEIVED  
KANSAS CORP COMM  
FEB - 2 A 11:14

02.02.96