222

R

4-070974

12-11

TO:
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API number: 15-195-22,098-00-00

C /W2 SW /4 SEC. 33, 13 S, 21 W
1320 feet from S section line
660 feet from E section line

Operator license# 6127

Lease M. Schuster well # 1-18

Operator: Taurus Oil Company

County Trego

Address: P.O. Box 981
Hays, Kansas 67601
J.L. Koron

Well total depth 4150 feet 134.87
Conductor Pipe: 0 inch @ 0 feet
Surface pipe 8 5/8 Inch @ 207 feet

Aband. oil well ___, Gas well ___, Input well ___, SWD ___, D & A X

Plugging contractor: _____ License# _____

Address: _____

Company to plug at: Hour: A.M. Day: 11 Month: December Year: 91

Plugging proposal received from: Larry Langhofer

Company: Emphasis Drilling Inc. Phone: _____

Were: 8 5/8" - 207' S.P. cwc. w/140 sx. cement by Allied Cement. No arbuckle. Elv. 2265'. Anhy. 1664'. No circulation problems. Mud condition 48 vis - 8.9 weight - 9.0 water loss. Proposal 215 sx. 60/40 pozmix - 6% gel. - 3% c.c. and 1 sx F.C. Spot with drill stem. Heavy mud between all plugs. 25 sx. @ 4080' - 25 sx. @ 1675' - 100 sx. with 1 sx. F.C. @ 865' - 40 sx. @ 250' - 10 sx. @ 40'. 15 sx. rathole circulate

Plugging Proposal Received by: Marion J. Schmidt MJS

Plugging operations attended by agent? All[ ], Part[ ], None[X]

Completed: Hour: 7:30P.M, Day: 11, Month: December, Year: 91

Actual plugging report: Emphasis ordered 215 sx. 60/40 pozmix - 6% gel. 3% c.c. and 5 sx. hulls. Spot with drill stem, circulate hole, heavy mud between all plugs.
1st. plug @ 4080' w/ 25 sx. cement.
2nd. plug @ 1675' w/ 25 sx. cement.
3rd. plug @ 865' w/100 sx. cement w/1 sx. flocele.
4th. plug @ 250' w/ 40 sx. cement.
5th. plug @ 40' w/ 10 sx. cement. 15 sx. in Rathole (Cir)

DEC 26 1991
12-26-91

Remarks: Cement by: Allied Cement. Elev. 2265'.

I did did not[X] observe the plugging. Marion J. Schmidt

INVOICED

DATE 1-10-92

INV. NO. 34314

12-11

J.L.S.

(agent)

Form CP-2/3