

Notice: Fill out COMPLETELY and return to Conservation Division at the address below within 60 days from plugging date.

KANSAS CORPORATION COMMISSION
OIL & GAS CONSERVATION DIVISION
WELL PLUGGING RECORD
K.A.R. 82-3-117

Form CP-4
March 2009
Type or Print on this Form
Form must be Signed
All blanks must be Filled

OPERATOR: License #: 31191
Name: R&B Oil & Gas, Inc
Address 1: P.O. Box 195
Address 2: _____
City: Attica State: KS Zip: 67009 + _____
Contact Person: Randy Newberry
Phone: (620) 254-7251
Type of Well: (Check one) Oil Well Gas Well OG D&A Cathodic
 Water Supply Well Other: _____ SWD Permit #: _____
 ENHR Permit #: _____ Gas Storage Permit #: _____
Is ACO-1 filed? Yes No If not, is well log attached? Yes No
Producing Formation(s): List All (if needed attach another sheet)
Miss Depth to Top: 4430 Bottom: 4460 T.D. 4597

Depth to Top: _____ Bottom: _____ T.D. _____

API No. 15 - 007-20840-00-02
Spot Description: NE SE
NE SE Sec. 11 Twp. 32 S. R. 10 East West
1,980 Feet from North / South Line of Section
660 Feet from East / West Line of Section
Footages Calculated from Nearest Outside Section Corner:
 NE NW SE SW
County: Barber
Lease Name: Schreiner Well #: C1 OWWO
Date Well Completed: 8-13-2008
The plugging proposal was approved on: 4/19/10 (Date)
by: Steve Durrant (KCC District Agent's Name)
Plugging Commenced: 7/27/10
Plugging Completed: 7/28/10

Show depth and thickness of all water, oil and gas formations.

Oil, Gas or Water Records		Casing Record (Surface, Conductor & Production)			
Formation	Content	Casing	Size	Setting Depth	Pulled Out
		Surface	8 5/8"	244'	250 Sacks Cement
Miss	Oil	Production	5 1/2"	4597'	175 Sacks Cement

Describe in detail the manner in which the well is plugged, indicating where the mud fluid was placed and the method or methods used in introducing it into the hole. If cement or other plugs were used, state the character of same depth placed from (bottom), to (top) for each plug set.

Cut surface off 4' below ground. Sand at 4380', bailed 5 sacks cement on sand. Ripped casing at 3410' & 3275'; pipe came free. Pulled casing up to 600' & pumped 50 sacks cement with 100# hulls. Pulled to 270' & pumped 50 sacks cement with 100# hull. Pulled to 40' & pumped 25 sacks cement.

RECEIVED

OCT 08 2010

DR

Plugging Contractor License #: 31925 Name: Quality Well Service Inc
Address 1: 190 US Highway 56 Address 2: _____
City: Ellinwood State: KS Zip: 67526 + _____
Phone: (620) 727-3410

KCC WICHITA

Name of Party Responsible for Plugging Fees: R&B Oil & Gas, Inc.
State of Kansas County, Harper, ss.
Randy Newberry (Print Name) Employee of Operator or Operator on above-described well,

being first duly sworn on oath, says: That I have knowledge of the facts statements, and matters herein contained, and the log of the above-described well is as filed, and the same are true and correct, so help me God.

Signature: Randy Newberry

QUALITY WELL SERVICE, INC.

5027

Home Office 190th US 56 HWY, Ellinwood, KS 67526

Todd's Cell 620-388-5422
Darin's Cell 785-445-2686

Rich's Cell 620-727-3409
Brady's Cell 620-727-6964

Date	7-23-10	Sec.	11	Twp.	32	Range	10	County	BARBEC	State	KS	On Location		Finish	1:30 PM
Lease	SCHREINER		Well No.		C-1 QWVO		Location								
Contractor	QWS							Owner							
Type Job	PTA							To Quality Well Service, Inc. You are hereby requested to rent cementing equipment and furnish cementer and helper to assist owner or contractor to do work as listed.							
Hole Size	7 7/8		T.D.												
Csg.	5 1/2		Depth		Charge To										
Tbg. Size			Depth		R & B OIL & GAS										
Tool			Depth		Street										
Cement Left in Csg.			Shoe Joint		City										
Meas Line			Displace		State										
EQUIPMENT												125sx 60/40 4% GEL			
Pumptrk	6	No.	KEVIN		Common										
Bulktrk	2	No.	TODD		Poz. Mix										
Bulktrk		No.			Gel.										
Pickup		No.			Calcium										
JOB SERVICES & REMARKS												Hulls.			
Rat Hole												Salt			
Mouse Hole												Flowseal			
Centralizers												Kol-Seal			
Baskets												Mud CLR 48			
D/V or Port Collar												CFL-117 or CD110 CAF 38			
1st Plug 600'												Sand			
10sx GEL 50sx 60/40 4% w/100" h/ls												Handling			
												Mileage			
2nd Plug 270'												/ FLOAT EQUIPMENT			
50sx 60/40 4% w/100" h/ls												Guide Shoe			
												Centralizer			
3rd Plug 40'												Baskets			
25sx 60/40 4% GEL												AFU Inserts			
CIRC CMT TO PIT												Float Shoe			
												Latch Down			
												5 1/2 WIRE Plug			
												Pumptrk Charge			
thanks												PTA			
Toas: Quality Well												Mileage			
												20			
PLEASE CALL AGAIN												Tax			
												Discount			
X Signature												Total Charge			

RECEIVED
OCT 08 2010
KCC WICHITA