STATE OF KANSAS STATE CORPORATION COMMISSION 200 Iplorado Derby Building Wichita, Kansas. 67202

WELL PLUGGING RECORD K.A.R.-82-3-117

API NUMBER 15-051-05914-0000

Wichita, Kansas, 67202	LEASE NAME Baumer						
	TYPE OR PRINT NOTICE: Fill out completely and raturn to Cons. Div.			WELL NUMBER 7 SUSTICION S Section Line			
•	office with	hin 30	days.	4990 Ft. Trom E Section Line			
LEASE OPERATOR Phillips	SEC. 27 TWP.115 RGE.17WX Exor(W)						
ADDRESS RT #3 Box 20-A	COUNTY Ellis						
PHONE 816 793-8421 OF				Date Wel	l Complete	d <u>7-9-37</u>	
Character of Well Oil				Plugging	Commenced	1-7-91	
(OII, Gas, D&A, SWD, Input,	Plugging	Completed	1-24-91				
The plugging proposal was a						(etab)	
			-	(KCC	District	Agent's Name).	
Is ACO-1 filed?							
Producing formation		+0 To	nn	Botto	m T	.D. 3542'	
						-	
Show depth and thickness of	1	no gas		ASING RECOR	0		
OIL, GAS OR WATER RECORDS							
Formation Content	From	To	Size	Put In	Pulled out		
			10"	1250' 3531'	none 1538'		
Describe in detail the manuplaced and the method or were used, state the change of the state of the change of the	racter of same a ttom to 3480' a 38'. Mixed 350	nd de	pth plac	ed, from_ sacks cem	_feet to	feet each set pine @2017	
(if additional	description is nec	essar	y, uso BA	CK of this	form.)		
Name of Plugging Contracto	rKELSO_CASIN	IG PU	LLING. I			6050	
Address P.O. Box 347				s Petrole	um COmpa	nv "-	
NAME OF PARTY RESPONSIBLE STATE OF Kansas	COUNTY OF			5 1001010	,55. F	D2-06-91	
D Daws	ell Kelso			Employee of	Operator)) or (Operator)	
above-described well, bein statements, and matters the same are true and corr	POLOTU COULSIUAG C	od.	ath, says e log of Signature		lescribed	rell as filed t	
		(Address)	P.O. Bo	x 347 Cha	ase,KS. 67524	
SUBSCRIBE	ED AND SWORN TO be			4 day	Feb.	,19 <u>91</u>	
Mu Comple	selon Expires:	HOTAL PARE	IZENE MEZ	Not	ary Public	/ .	

My Appt. Exp. Aug. 24, 1993

Well No.	1		7-	الله المركزة الركاف المركزة المركزة الم	e no a de de la competicación de la competicac	anderson and all the	E	_	- 2029•		
	•	Benney	• • •			Farm	Sec.	•	118	Range 178	
Drilling C	ntractor	Helmer,	Loh & I	eyne, In	Carrier .	,	FILLS		nty Kanagan	State 640 A	
		June	·		. 1	19 57		114.00	2	+-	
Drilling Co		<u>jarl</u>				19 37	,5	5AIU. OC	NORTH	Elev' R1 2031 R1	
		ng Joly	9			19 37	" CON		:	7.031	
Natural Pr		Fir	st 24 hours	Pot. 232	3	·bbls.			:		
Natural Pro			ond 24 hou	rs		bbls.	ļ.			 ₹	
T.	D. 35						1				
	1	RECORD	OF PA	Y SAND	•••			·		· .	
81mps	on Ser	.	3505	5526	Ţ _			<u> </u>	BOUTH		
Silicions Lime		3532	3542	Pay		Center	Feet from N.	3*			
						·	2510	Feet from S. I		Teet from E. ine	
							Fresh water			Feet from W. lin	
					Salt water from			to			
							Sait water fr		to		
						Salt water fr		to			
									, tọ		
							Wooden Conductor-Size Fe DRIVE PIPING, CASING, TUBING AND RODS				
							Size	Wt. per Ft.	Put In		
<u>.</u>							15}*	TOLW S.R.		Pulled Out	
							10*	35Ly 8. E.			
								24 9mls			
								SE CHIS	5581.		
						3	Si Ly s	E. com	ted with B	33	
-						1	LO" LE S.	R. com	ed with 85	anaka.	
						1	" New Ja	L Sale	Promised and Al	175 sacks.	
									TARK ATM	170 sacks.	
									-23	 	
e of Shot			DO REC				Packer set at	<u> </u>	Size and Kin	1	
or Stot	Qts.	Top Shot	Box Shot	Re	marks		Packer set at	<u> </u>	Size and Kine		
		·	· 			1	Packer set at		Size and King		
			 	<u>_</u>			Water well		Feet as &		
			 			I	rice of Contra	ct \$ 4.00	TALESCOL T	vnishes gas, & drilling	
			-,				pproved	210 - (17 4	front.	
								- Green	4-4-4-W	Superintendent	
				NOV 19	(विदेश)		1 measur	ements for	on top of		
					<u> </u>	br	whing.		+ob or	- Cotary	
				** - ***				t to all	Mensuremen		
						100	atrifinate	in order	to agree 1	dth this	
						re	cord.				
1			- 1					_			

```
48 State
48 1850 Shale, shells & Aydrite
1850 1860 Anhydrite
1280 1655 Shale, red beds & shalls
1655 1730 Shale
1780 1900 Brown lime
1900 2020 Shale and sandy lime
2020 2030 Shale
2030 2080 Lime
2080 2285 Lime and shale
2285 2375 Line"
2375 2425 Red bed & lime shells
2425 2500 Lime
2500 2515 Shale
2515 2780 Shale and shells
2720 2835 Shale
2835 2995 Broken lime
2995 5002 Shale
3002 5465 Lime
3465 3515 Lime and shale
5515 5542 Lime
3542
          Total Depth
```

Summary by W. J. Allen

Klev. 2029' D.F.

All measurements to Elev. 2031' Rot. Bush.

```
1245
               Anhydrite (Cimmeron)
2425
               Hove Le.
2780
               Tarkin La.
3000
                Topeka Le.
3130-50
                Show oil saturation in samples
                7 7 7 7 H
3250-75
3300-10
5380
                Lensing-Kenses City
3320~50
                Show oil saturation in samples
3410-90
3505
                Simpson
                Simpson Sand - Show oil saturation in samples (Core)
3526 ~ 32
5532
              Silicious Lime - Oil (Cored 6' of Total Depth (Drlid 6' of Sil.Le.)
                Silicious Lime - Oil (Cored 5' of Sil. kimle)
3548- T
```

See drilling "folder" for additional detail