TO: 5-20	API Number: 15-109-20,627-00-00
STATE CORPORATION COMMISSION	
CONSERVATION DIVISION - PLUGGING	<u>NW NW SE</u> /4 SEC. <u>04</u> , <u>13</u> S, <u>33</u> W
130 SOUTH MARKET, SUITE 2078	2310 feet from S section line
WICHITA, KANSAS 67202	2200 feet from E section line
Operator license#31120	Lease: <u><b>Hess</b></u> Well # 1
Operator: Pelican Hill Oil & Gas, Inc.	County: Logan
	Well total depth 4700 152.75 feet Conductor Pipe: 0 inch @ 0 feet
Address: 1401 N. El Camino Real - #203	Well total depth 4700 \5 4. feet
San Clemente, CA 92672	Conductor Pipe: 0 inch @ 0 feet
	Surface pipe 8 5/8 Inch @ 263 feet
Aband. oil well, Gas well, Input well	, SWD, D & A_X
Plugging contractor: Abercrombie RTD, Inc.	T + man ma # 20504
Plugging contractor: Abercrombie RTD, Inc.	License#30684
Address:	
Company to plug at: Hour: P.M. Day: _20 Mo	nth: May Year 1996
Plugging proposal received from: Tony Martin	
Company: Abercrombie RTD, Inc.	O
W O. J 100 CO/40	(n = 52)
Were: Order 190 sxs 60/40 pozmix with 6% gel -	
Spot plug through drill pipe with heavy	mud between all plugs.
	2 5
Plugging Proposal Received by: Dennis L. Hamel	₹ 2 <del>₹</del>
Plugging operations attended by agent? All[	
	4
Completed: Hour: 12:00 P.M., Day: 20, Month	:
Actual plugging report:	
1st. plug at 2507' w/25 sxs.	<u> </u>
2nd. plug at 1440' w/100 sxs.	
3rd. plug at 300' w/40 sxs.	
4th. plug at 40' w/10 sxs.	
15 sxs in rathole.	
	Secretary of the secret
The second secon	and the second s
	•
Remarks: Allied Cementing.	
Condition of casing(in hole): GOODBAD	Anhy.plug: YES X NO
Bottom plug(in place): YES, CALC, NO	Dakota plug: YES X , NO
Bottom plug(in place): YES, CALC, NO Plugged through TUBING, CASING	Dakota plug: YES X , NO
Plugged through TUBING, CASING	Dakota plug: YES X , NO GL  GL
	Dakota plug: YES X, NO GL  Elevation: 3039 GL  Jennes J Hamel
Plugged through TUBING, CASING	Dakota plug: YES X , NO GL  GL

INV. NO. 45724 5-20