## 4-060375

| TO:' STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING 200 COLORADO DERBY BUILDING WICHITA, KANSAS 67202   | API number: 15-109-20,546-00-00  NW SE SE /4 SEC. 09 , 13 S, 33 W 990 feet from S section line 990 feet from E section line |
|--|---|
| Operator license#30269   | Lease_Trust well #_1  |
| Operator: Argent Energy, Inc.  | County Logan  |
| Address: 110 South Main Wichita, Kansas 67202  | Well total depth <u>4645</u> feet<br>Conductor Pipe: <u>0</u> inch @ <u>0</u> feet  |
| Aband. oil well, Gas well, Inpu  | ut well, SWD, D & A _X_   |
| Plugging contractor: Murfin Drilling Co  | Dmpany License#_30606   |
| Address: Wichita, Kansas 67201   |   |
| Company to plug at: Hour: 10:30P.M Day:  | 5 Month: January Year: 93   |
| Plugging proposal received from: Ed Mc   | Kenna   |
| Company: Murfin Drilling Company   | Phone:  |
| Were: Order 200 sxs. 60/40 posmix - Space all plugs with heavy dr.   | illing mud through drill pipe.  |
| Plugging Proposal Received by: Herb   Plugging operations attended by agent?  Completed: Hour: 10:30P.M, Day: 5 , Mon Actual plugging report: 8 5/8" to 279 1st. plug @ 2450' w/25 sxs Anhydrite 2nd. plug @ 1380' w/100 sxs Dakota 3rd. plug @ 330' w/40 sxs Surface 14th. plug @ 40' w/10 sxs.  Rathole with 15 sxs.  Mousehole with 10 sxs. | 1079' - 1379'.  Dipe to 279'.  MILA 15 100 100 100 100 100 100 100 100 100  |
| Remarks: Allied Cementing. Condition of casing(in hole):GOODBB Bottom plug(in place):YES,CALC Plugged through TUBING, CASING I did[ N]   | ,NOX_Dakota plug:YES_X_,NO<br>Elevation:2979GL  |
| DATE 3-3-93 UNY NO 37293   | (agent) Form CP-2/3   |