<i>Q</i>	<u>, , , , , , , , , , , , , , , , , , , </u>
TO:	API number: 15-109-20,613-00-00
STATE CORPORATION COMMISSION 3-4	20,013
CONSERVATION DIVISION - PLUGGING	<u>C SW NW/4 SEC. 05 , 13 S, 33 W</u>
130 SOUTH MARKET, SUITE 2078	3160 feet from S section line
WICHITA, KANSAS 67202	4640 feet from E section line
Wichilli, Idahbib 0/202	I took I become I in
Operator license# 3966	Lease: Jack D. Lee Well # B-1
Operator: Wanker Oil	County: Logan
-	121.48
Address: R.R.2 - Box 14	Well total depth 4661 feet
- Wakeeney, Kansas 67672	• • • • • • • • • • • • • • • • • • •
	Surface pipe 8% Inch @ 216 feet
Aband. oil well, Gas well, Input wel	11, SWD, D & A <u>X</u>
Plugging contractor: <u>Discovery Drilling</u>	License#31548
Address:	
Company to plug at: Hour: P.M. Day: 01	Month March Vear 1996
Company to plug at: hour: F.M. Day: UI	March Tear. 1990
Plugging proposal received from: Tom Alm	
Company: Discovery Drilling	Phone:
	RECEIVED
Were: Order 195 sxs 60/40 posmix - 6% gel.	KANSAS CORPORATION COMMUNISSIUM
Spot all plugs through drill pipe with heavy m	mud between all plugs.
	MAR 0 8 1996
	03 08 1001
	05-08-1196
	CONSERVATION DIVISION WICHITA, KS
Plugging Proposal Received by: Ed Schumacher	
Plugging operations attended by agent? All[], Part[], None[X]
Completed: Hour: 7:30 A.M., Day: 4 , N	Month: March , Year: 1996_
	•
Actual plugging report:	
1st. Plug at 2520' w/20 sxs cement.	
2nd. Plug at 1455' w/100 sxs cement.	
3rd. Plug at 265' w/40 sxs cement.	
4th. Plug at 40' w/10 sxs cement.	
15 sxs rathole. 10 sxs mousehole.	
Arbuckle - no - Anhydrite 2509'	
Remarks: Allied Cementing	
Condition of casing(in hole): GOODBAI	D Anhy.plug: YES 2509 NO
Bottom plug(in place): YES, CALC,	NO Dakota plug: YES X . NO
Plugged through TUBING, CASING	
India [] [all mot [x] observe the plugging	g. Ed Achumalha
MAR 1 9 4000	(agent) Form CP-2/3
1/7// T O 4644	W. 1. 27.3