

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15-167-2224500-00

SW, Sec. 11, T 14-S, R 12 W/E

\_\_\_\_\_ feet from N/S section line

\_\_\_\_\_ feet from W/E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5184

Lease Name Mahoney Well # 1

Operator: Shields Oil Prod  
Name & Shields Bldg.  
Address Russell Ks.

County Russell

Well Total Depth 3325 feet 108.07

Conductor Pipe: Size \_\_\_\_\_ feet

Surface Casing: Size 8 5/8 feet 691

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well (D&A)

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Shields Dring Co. License Number 5655

Address Russell Ks.

Company to plug at: Hour: 4 PM Day: 9 Month: 11 Year: 19 83

VERBAL PLUGGING ORDERS GIVEN TO Burton Berry

(company name) Shields Dring Co. (phone) \_\_\_\_\_

were: order 180 sx cem. 50/50 portmix 6% Gel. 3% c.c.

1 sx nulls, 1. 8 5/8 plug, 1 sx Flow Seal

Heavy mud between all plugs.

pump cem. down drill pipe.

Elev. 1814 Anhydrite 683-720 Arbuckle 3312

Dakota 1650

Signed Dale F. Balthazor  
(TECHNICIAN)

164 z 470

Plugging Operations attended by Agent?: All \_\_\_\_\_ Part \_\_\_\_\_ None (circled)

Operations Completed: Hour: 12:15 AM Day: 10 Month: 11 Year: 19 83

ACTUAL PLUGGING REPORT circ @ 3315 turn hole over

25 sx @ 3315

25 sx @ 700

100 sx @ 480 mixed with 1sx Flow Seal

1sx nulls push plug to 40'

10 sx @ 40'

10 sx Rat Hole

Remarks: 10 sx mouse hole

Cementing to Allied

I hereby certify that the above plugging instructions were given as herein stated and that I (did (circled) did not) observe this plugging.

INVOICED

DATE 12-27-83

INV. NO. 7218-6

RECEIVED  
STATE CORPORATION COMMISSION  
NOV 21 1983  
11-21-1983  
CONSERVATION DIVISION  
Wichita, Kansas

Signed Dale F. Balthazor  
(TECHNICIAN)