

6 050238

API NUMBER 15-051 21 456 00101

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

Sec 22, T 14S, R 18W

TECHNICIAN'S PLUGGING REPORT

Operator License # 7031

\_\_\_\_\_ feet from S section line

\_\_\_\_\_ feet from E section line

Operator: R & R Exploration Inc.

Lease Name Nrees Well # 1

Name & Address: Box 1198

County Ellis 118.79

Hayo Rans 67601

Well Total Depth 3655-PB 3609 feet

Conductor Pipe: Size \_\_\_\_\_ feet

Surface Casing: Size 8 5/8 feet 1222

Abandoned Oil Well  Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SHD Well \_\_\_\_\_ D&A \_\_\_\_\_

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor B & Titan Cementing Co. License Number \_\_\_\_\_

Address \_\_\_\_\_

Company to plug at: Hour: \_\_\_\_\_ Day: \_\_\_\_\_ Month: \_\_\_\_\_ Year: 19 \_\_\_\_\_

Plugging proposal received from Ray & Breit

(company name) Box 1198 - Hayo Rans (phone 913-625-7238)

were: Order 250 ex 60/40 Pozmix 6 1/2 Gal 370.00 18 5/8 cementing Plug.

Plugging Proposal Received by \_\_\_\_\_ (TECHNICIAN)

Plugging Operations attended by Agent?: All  Part \_\_\_\_\_ None \_\_\_\_\_

Operations Completed: Hour: 50M Day: 22 Month: Dec Year: 1985

ACTUAL PLUGGING REPORT T.D 3655 PB to 3609 - 8 5/8 1222 - 4 1/2 3655 ~ 1500

Perfs 3400 to 45 - 3484 to 94 - sand to 3400' with 5 sac cement.  
Shot 4 1/2" at 2450' and pulled cone. Pumped 5 sac bulls  
thru 8 5/8 Plug container and 170 sac cement. Released plug  
and squeezed with 80 sac cement - 100 lbs working pressure  
and 50 lbs standing pressure - By B & Titan cementing Co.

Remarks: \_\_\_\_\_

(If additional description is necessary, use BACK of this form.)

I (holder) observe this \_\_\_\_\_ STATE CORPORATION COMMISSION

DATE NOV 12 1985 Signed Gilbert P. Luke (TECHNICIAN)

INV. NO. 10977