

TO: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API number: 15-051-20,731-00-00

SE NW SE /4 SEC. 34, 13 S, 20 W
1650 feet from S section line
1650 feet from E section line

Operator license# 30606

Lease Kingsley well # 4

Operator: Murfin Drilling Co., Inc.

County Ellis

Address: 250 North Water - Suite #300
Wichita, Kansas 67202
Stan Froetschner

Well total depth 3895 feet ^{126.59}
Conductor Pipe: 0 inch @ 0 feet
Surface pipe 8 5/8 Inch @ 211 feet

Aband. oil well X, Gas well , Input well , SWD , D & A

Plugging contractor: Co Tools - Allied Cementing License#

Address: Russell, Kansas 67665 - Russell, Kansas 67665

Company to plug at: Hour: P.M. Day: 1 Month: March Year: 95

Plugging proposal received from: Stan Froetschner

Company: Murfin Drilling Co., Inc. Phone: 316-267-3241

Were: 8 5/8" - 211' S.P. cwc. w/159 sxs. cement. 5 1/2" casing set at 3878' w/175 sxs. cement. 5 1/2" casing squeezed @ 1004' w/200 sxs. Perfs. 3878' - 3888'. Elv. 2270'. Proposal 400 sxs. 60/40 pozmix - 6% gel and 500# cotton seed hulls. Pump in with pump truck-spotted and displaced all cement through tubing. Starting at 3800' - load 5 1/2" casing from bottom to top - squeeze and shut in under pressure. Squeeze 5 1/2" x 8 5/8" annulus with cement. Shut in under pressure.

Plugging Proposal Received by: Marion J. Schmidt

Plugging operations attended by agent? All[X], Part[], None[]

Completed: Hour: 6:00P.M., Day: 1, Month: March, Year: 95

Actual plugging report: Actual plugging report: Murfin Drilling, Inc. ordered 400 sxs. 60/40 pozmix - 6% gel and 5 sxs. hulls. Pumped in with pump truck, spotted and displaced all cement through tubing.
1) 5 1/2" casing was squeezed at 1004' w/200 sxs. cement.
2) Perforated 5 1/2" casing at 2258' - 1550' - 850'.
3) 2 3/8" tubing at 3800' spotted and displaced w/150 sxs. cement w/4 1/2 sxs. hulls added.
4) 2 3/8" tubing at 1854' spotted and displaced w/200 sxs. cement w/1/2 sxs. hulls added.
5) Returned with additional cement then, 2 3/8" tubing at 1000' spotted w/100 sxs. cement on vac.
6) 2 3/8" tubing at 860' spotted w/160 sxs. cement w/3 sxs. hulls. Cement circulated to surface out of 5 1/2" casing.
7) Squeezed 5 1/2" casing w/15 sxs. cement. Max. P.S.I. 700#.
8) Squeezed 5 1/2" x 8 5/8" annulus w/105 sxs. cement w/1 sx. hulls. Max. P.S.I. 200#. S.I.P. 100#.

Remarks: Cemented by Allied Cementing.

Condition of casing(in hole): GOOD X BAD Anhy. plug: YES X NO

Bottom plug(in place): YES , CALC X, NO Dakota plug: YES X, NO

Plugged through TUBING X, CASING . Elevation: GL

I did X / did not [] observe the plugging.

DATE 3-20-95

INV. NO. 42418

3-1

STATE CORPORATION COMMISSION RECEIVED
MAR 13 1995
CONSERVATION DIVISION
WICHITA, KANSAS

(agent)