
KANSAS STATE CORPORATION COMMISSION

CONSERVATION DIVISION AGENT'S REPORT

TO: Jewel M. Ogden, Director 500 Insurance Building 212 North Market Wichita 2, Kansas

Remarks:



PLUGGING

FILE SEC 27 T /3 R 20 L BOOK PAGE 3/ LINE /4

File No.						
	31-14	County:	Ell is			
Location:	SE SE SW	Sec	<u>27</u> Twp.	<u>13</u> Rge.	<u>20 (E)</u>	(W) <u> </u>
Name of Fiel	1d:		Tota	al Depth:	3830	
		supervision of plu				
Lease Name:	Giebler	·		Well No.	<u>B-1</u>	
		mperial Oil of				
Complete Ad	dress:	780 4th Natl Bk	Wichita	, Kans		
		same & Hallibur				
Address:		<u></u>		License	No.	
		Input Wel				
Other well	as hereafter ind	licated:				·
		perations caused b				
		R				
	completed: Hour_	4PM Day				
	ell was plugged					
8 5/8" a	at 220' circul	ated with cemen	t - 5분" 38:	17' with 10	00	
squeezed		ed with cement :				
		ed with cement :				
PB to 37	and circulat	ed with cement :	from 1500'	to 0' - no	pipe recove	ry.
PB to 37	and circulat 760', perf 348	ed with cement:	from 1500'	to 0' - no	pipe recove	ry.
PB to 37 Filled h	and circulate 760', perf 348 nole with heavex cement - ce	ed with cement: 8'. y rotary mud, p	from 1500'	to 0' - no	pipe recove	ry.
PB to 37 Filled h	and circulate 760', perf 348 nole with heavex cement - ce	ed with cement: 8'. y rotary mud, poment 570' to 0'	from 1500'	to 0' - no	pipe recove	ry.
PB to 37 Filled h	and circulate 760', perf 348 nole with heavex cement - ce	ed with cement: 8'. y rotary mud, poment 570' to 0'	from 1500'	to 0' - no	pipe recove	ry.
PB to 37 Filled h	and circulate 760', perf 348 nole with heavex cement - ce	ed with cement: 8'. y rotary mud, poment 570' to 0'	from 1500'	to 0' - no	pipe recove	ry.
PB to 37 Filled h	and circulate 760', perf 348 nole with heavex cement - ce	ed with cement: 8'. y rotary mud, proment 570' to 0' by Halliburton	from 1500'	to 0' - no	pipe recove	ry.