

Notice: Fill out COMPLETELY and return to Conservation Division at the address below within 60 days from plugging date.

KANSAS CORPORATION COMMISSION
OIL & GAS CONSERVATION DIVISION
WELL PLUGGING RECORD
K.A.R. 82-3-117

Form CP-4
March 2009
Type or Print on this Form
Form must be Signed
All blanks must be Filled

OPERATOR: License #: 6407
Name: Flowers Production Co., Inc.
Address 1: P.O. Box 249
Address 2: _____
City: El Dorado State: KS Zip: 67042 + _____
Contact Person: Dallas Flowers
Phone: (316) 321-0550
Type of Well: (Check one) Oil Well Gas Well OG D&A Cathodic
 Water Supply Well Other: _____ SWD Permit #: _____
 ENHR Permit #: _____ Gas Storage Permit #: _____
Is ACO-1 filed? Yes No If not, is well log attached? Yes No
Producing Formation(s): List All (if needed attach another sheet)
Viola Depth to Top: 3144 Bottom: 3146 T.D. 3146
_____ Depth to Top: _____ Bottom: _____ T.D. _____
_____ Depth to Top: _____ Bottom: _____ T.D. _____

API No. 15 - 015-19208-00-00
Spot Description: NE NW NW NE
_____-_____-_____- Sec. 9 Twp. 27 S. R. 6 East West
5,026 Feet from North / South Line of Section
2,222 Feet from East / West Line of Section
Footages Calculated from Nearest Outside Section Corner:
 NE NW SE SW
County: Butler
Lease Name: McGinnis Well #: 11
Date Well Completed: 10-5-46
The plugging proposal was approved on: 10-25-10 (Date)
by: Steve Bond (KCC District Agent's Name)
Plugging Commenced: 3-20-11
Plugging Completed: 4-8-11

Show depth and thickness of all water, oil and gas formations.

| Oil, Gas or Water Records | | Casing Record (Surface, Conductor & Production) | | | |
|---------------------------|-------------|---|--------|---------------|------------|
| Formation | Content | Casing | Size | Setting Depth | Pulled Out |
| Viola | Oil & Water | Production | 7" | 2765' | 0 |
| | | Production | 5 1/2" | 3129' | 0 |
| | | | | | |
| | | | | | |

RECEIVED
MAY 27 2011
KCC WICHITA

Describe in detail the manner in which the well is plugged, indicating where the mud fluid was placed and the method or methods used in introducing it into the hole. If cement or other plugs were used, state the character of same depth placed from (bottom), to (top) for each plug set.

3-30-2011, TAG BOTTOM @ 3138', FLUID LEVEL @ 1125'. DUMP 10 GAL GRAVEL & 60 GAL SAND. 4-2-2011, DUMP BAILED 5 SXS CEMENT ON TOP @3075', LOADED HOLE TO SURFACE & SHOT SQUEEZE HOLES FROM 250'-251'. 4-8-2011, SWEDGED INTO 5-1/2" CASING & ESTABLISHED CIRCULATION, CONSOLIDATED OIL WELL SERVICES MIXED & PUMPED 387 SXS 60/40 POZMIX 4% GEL, 1% CC TO SURFACE. CEMENT CIRCULATED. PLUG DOWN 4-8-2011, 5:00PM. CONSOLIDATED CEMENT TICKET #30859.

Plugging Contractor License #: 33961 Name: Consolidated Oil Well Services, LLC
Address 1: P.O. Box 884 Address 2: _____
City: Chanute State: KS Zip: 66720 + _____
Phone: (620) 431-9210
Name of Party Responsible for Plugging Fees: Dallas Flowers

State of Kansas County, Butler, ss.
Flowers Production Co., Inc. Dallas Flowers Employee of Operator or Operator on above-described well,
(Print Name)

being first duly sworn on oath, says: That I have knowledge of the facts statements, and matters herein contained, and the log of the above-described well is as filed, and the same are true and correct, so help me God.

Signature: Dallas Flowers President

**SACO OIL COMPANY
WELL LOG**

300' from Cen. road of
North Line
440' E of W Line

Operator The Hugo Oil Company
Comm. 10-5-46 Comp. 11-27-46
Shot _____ Qts. From _____ ft. To _____ ft.
Acidized _____ Gal.
Prod. Formation Viola Lime
Initial Prod. 12 Ebl.
Elevation 1417 Est.
Acidized w/ 500 Gal.

Lease Adams-McGinnis Well No. 11
Loc. NE/4 Sec. 9 Twp. 27 Rge. 6E
County Butler State Kansas
Contractor The Saco Oil Company

| Casing Record | | | |
|---------------|------|----------|---------|
| Size | Ft. | Pulled | Remarks |
| 12 1/8" | 766' | R&P | |
| 10 | 1629 | R&P | |
| 8 1/4 | 2250 | R&P | |
| 7 | 2765 | Cem. In. | |
| 5 1/2 | 3129 | " | |

**RECEIVED
MAY 27 2011**

FIGURES INDICATE BOTTOM OF FORMATION

| | | | | | |
|-----------------------|-----|------------------|--------------------|-----------------|----------------|
| soil & shale | 30 | shale | 950 | lime ✓ | 2425 |
| lime | 110 | lime | 960 | shale light ✓ | 2440 |
| shale | 115 | shale | 965 | sand ✓ | 2450 |
| lime broken | 125 | shale dark | 1010 | shale light ✓ | 2475 |
| shale dark | 135 | lime | 1020 | lime ✓ | 2500 |
| lime | 145 | shale | 1024 | shale dark ✓ | 2520 |
| shale | 150 | lime hard (5BW) | 1030 | lime ✓ | 2535 |
| lime | 190 | lime&wtr. sand | 1037 | shale light ✓ | 2560 |
| red rock | 210 | lime | 1075 | shale gray ✓ | 2600 |
| lime | 225 | shale | 1080 | lime ✓ | 2620 |
| lime broken | 245 | lime | 1085 | shale&shells ✓ | 2645 |
| shale dark | 260 | shale | 1115 | shale sandy ✓ | 2660 |
| shale & shells | 290 | shale light | 1137 | shale dark ✓ | 2665 |
| lime | 300 | lime | 1142 | red rock ✓ | 2670 |
| slate 3 BWP | 310 | shale light | 1150 | MEAS. CORR. | 2679 |
| lime | 335 | lime white | 1175 | shale sandy ✓ | 2720 |
| lime sandy | 340 | shale | 1180 | shale -cvg. ✓ | 2745 (1BW) |
| lime | 350 | lime | 1185 | lime ✓ | 2748 |
| red rock | 353 | shale | 1190 | shale ✓ | 2765 |
| lime | 370 | lime | 1218 | lime-brown-sft | 2771 |
| shale | 385 | shale | 1235 | lime light | 2775 |
| lime | 395 | lime | 1250 | lime | 2781 |
| shale dark | 405 | shale | 1270 | lime brown | 2785-stained |
| lime | 410 | lime | 1290 | lime | 2803 |
| shale & shells | 460 | shale | 1300 | shale blue | 2805 (1BW280) |
| shale | 482 | lime | 1315 | lime | 2820 8 |
| lime & shale | 495 | shale | 1345 | lime black | 2836 |
| lime | 500 | lime | 1375 | lime light | 2845 |
| shale | 505 | shale | 1390 | lime black | 2860 |
| lime | 520 | lime | 1410 | lime light | 2872 |
| shale | 535 | sandy shale | 1425 | lime gray hard | 2910 |
| shale light | 545 | lime | 1430 | lime gray sharp | 2914 (3BW291) |
| lime | 550 | lime | 1445 | lime white | 2919 |
| shale dark | 602 | shale | 1460 | lime hard | 2927 (20BW29) |
| lime | 607 | lime | 1470 | lime | 2940 2 |
| shale light | 625 | shale | 1475 | lime gray | 2957 |
| shale | 630 | lime | 1505 | lime | 2987 |
| lime | 635 | shale | 1520 | lime&shale | 3045 |
| slate | 650 | lime | 1550 | lime | 3065 |
| lime | 655 | shale (10BW) | 1590 | lime ✓ | 3082 |
| slate (3 BWP 735-747) | 665 | water sand | 1620 | shale | 3090 |
| shale | 735 | sandy shale | 1670 | shale dark | 3129 |
| water sand | 747 | sand | 1675 | shale ✓ | 3144-Top Viola |
| shale dark | 755 | sandy shale | 1705 | lime cap-lite | 3145 |
| lime & shale | 757 | lime | 1715 | lime br. porous | 3146-T.D. |
| shale & shells | 760 | shale | 1730 | | |
| shale | 765 | lime | 1745 | | |
| lime | 772 | shale light | 1806-Top Lansing | | |
| shale light | 810 | lime (4 BW 1935) | 1965 | | |
| shale | 815 | shale light ✓ | 2126-Top K.C. Lime | | |
| lime | 840 | lime (5BW 2235) | 2297 | | |
| shale | 850 | shale | 2310 | | |
| lime | 895 | lime ✓ | 2325 | | |
| shale light | 900 | shale dark ✓ | 2365 | | |
| lime | 910 | lime ✓ | 2370 | | |
| shale light | 915 | shale ✓ | 2397 | | |
| | | shale light | 2405 | | |

OIL SHOWINGS

Show Oil - 2235-2240
" " - 2440-50
Free Oil - 3146- T.D.
12 Bbls-no water

KCC WICHITA