FEB 0 1 2010

Notice: Fill out COMPLETELY and return to Conservation Division at the address below within 60 days from plugging date.

KANSAS CORPORATION COMMISSION OIL & GAS CONSERVATION DIVISION

Form CP-4 CONSERVATION DIVISION March 2009
WICHITA, KS Type or Print on this Form

WELL PLUGGING RECORD K.A.R. 82-3-117

Form must be Signed All blanks must be Filled

OPERATOR: License #: 30717				API No. 15 - 051-25,880-00-00		
Name:Downing-Nelson Oil Co. Inc.				Spot Description: 180' N and 50' E of NE NW		
Address 1:113 W, 13th				NE_NW_Sec.31_Twp.13_S. R. 20East West		
Address 2:				150 Feet from 📝 North / 🔲 South Line of Section		
City: Hays State: Kan. zip: 67601 + 0372				_2,030 Feet from East / West Line of Section		
Contact Person:Terry_WPiesker				Footages Calculated from Nearest Outside Section Corner:		
Phone: (785_) 735-4363				☐ NE ✓ NW ☐ SE ☐ SW		
Type of Well: (Check one) Oil Well Gas Well OG D&A Cathodic				County: Ellis		
Water Supply Well Other: SWD Permit #:				Lease Name: Kroeger-Luea Unit Well #: 1-31		
ENHR Permit #: Gas Storage Permit #:				Date Well Completed: 8-07-09		
Is ACO-1 filed? Yes No If not, is well log attached? Yes No				The plugging proposal was approved on: 12-16-09 (Date)		
Producing Formation(s): List All (If needed attach another sheet) by: Case Morris (KCC District Age						
Arbuckle Depth to Top: 3911' Bottom: 3925' T.D. 3992' Plugging Commenced: 1-26-10						
Sand Depth to Top: 3870' Bottom: 3890' T.D. 3904'				Plugging Completed: 1-26-10		
Lan-KC Depth to Top: 3596' Bottom: 3636' T.D. 3904'						
Show depth and thickness of all water, oil and gas formations.						
				ord (Surface, Conductor & Production)		
Formation	Content	Casing	Size	Setting Depth	Pulled Out	
Arbuckle	oil and water	Surface	8 5/8*	220'	none	
Sand	Oil and water	Production	5_1/2"	4025'	none	
L-KC	oil and water				ļ	
cement or other plugs were used, state the character of same depth placed from (bottom), to (top) for each plug set. Tied to 8 5/8" Casing and pressured to 500#. Tied to 5 1/2" Casing and mixed 75 sxs. 60/40 Poz, 4% Gel and 1/4# Flo-Seal per sxs. with 200# Hulls. Followed with 15 sxs. Gel. Followed with 170 sxs. 60/40 Poz., 4% Gel and 1/4# Flo-Seal per sxs. Pressure at end of job- 500#. SIP- 500#						
Plugging Contractor License #:				Oilwell Cemer	nting Com.	
City: Russell			State: Ka	nsas	zip: <u>67665</u> + <u>0032</u>	
Phone: (785) 483-2025						
Name of Party Responsible for	or Plugging Fees: _Dowl	ning-Nelson_Oil_CoI	nc.			
State of Kansas County, Ellis						
Teiny W. Piesker				ployee of Operator or	Operator on above-described well,	
the same are true and correct	, says: That I have knowled	dge of the facts statements, ar	nd matters herein cor		f the above-described well is as filed, and	
Mail to: KCC - Conservation Division, 130 S. Market - Room 2078, Wichita, Kansas 67202						