TO:

API NUMBER 15-071-20,655 -0000

STATE CORPORATION COMMISSION	<u>C-SE SEC 32</u> , T <u>18</u> S, R <u>40</u> W
CONSERVATION DIVISION - PLUGGING SECTION	1325' FEET FROM SOUTH SECTION LINE
WICHITA STATE OFFICE BLDG., 130 S. MARKET	1327' FEET FROM EAST SECTION LINE
WICHITA, KANSAS 67202	LEASE NAME <u>SMITH</u> WELL# 1
TECHNICIAN'S PLUGGING REPORT	COUNTY GREELEY
OPERATOR LICENSE # 4894	WELL TOTAL DEPTH 2977' FEET
OPERATOR: HORSESHOE OPERATING, INC.	PRODUCTION CSG: SIZE 4 1/2 FEET 2965'
NAME AND 500 W.TEXAS, SUITE 1190	SURFACE CASING: SIZE <u>8 5/8</u> FEET <u>267'</u>
ADDRESS MIDLAND TX. 79701	
ABANDONED OIL WELL GAS WELL X INPUT W	ELLD/A
OTHER WELL AS HEREINAFTER INDICATED	
PLUGGING CONTRACTOR ALLIED CEMENTING	LICENSE NUMBER
ADDRESS P.O. BOX 31-24, RUSSELL, KS 67665-	0031
COMPANY TO PLUG AT: HOUR: 9:00amDAY: 27 MONTH: 5 YEAR: 98	
PLUGGING PROPOSAL RECEIVED FROM	
(COMPANY NAME) S.L. BURNS	(PHONE) (915)-683-1448
WERE: PUMP 200# HULLS DOWN 4 1/2" CASING AND 150sx CEMENT.CHECK 8 5/8 X 4 1/2 ANNULAS PUMP 50sx IF NEEDED	
PLUGGING PROPOSAL RECEIVED BY Kevin Strub	e
PLUGGING OPERATIONS ATTENDED BY AGENT?:	
	: <u>27</u> MONTH: <u>5</u> YEAR: <u>98</u>
MIXED IN FIRST PART OF CEMENT PUMPER	DOWN 4 1/2 W/100# COTTONSEED HULLS AHEAD W/100# D 150sx CEMENT MAX PSI 300#, S#ROW CENVED 300# OTAL 10 SX CEMENT, SHUT IN 12008#S CORPORATION COMMISSIO
	IIIN 07 1000
REMARKS: Used 60/40 Pozmix 6% gel by ALLIE	JUN 03 1998  No casing recovery 6-3-98
I (DID/xxxxxxx) OBSERVE THIS PLUGGING.	CONSERVATION DIVISION WICHITA, KS
	(TECHNICIAN)
	FORM CRH 2X3

INVOICED

DATE 6-8-98

INV. NO. 50687