ı 020047	API NUMBER 15-071-20,433-0000
STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING SECT 200 COLORADO DERBY BUILDING WICHITA, KANSAS 67202	, , , , , , , , , , , , , , , , , , , ,
TECHNICIAN'S PLUGGING REPORT	4620 feet from E section line
Operator License # 5476	Lease Name Larson Well # 1
Operator: DNB Drilling, Inc.	County Greeley 185.25
Address 535 North Oliver	Well Total Depth 5700 feet
Wichita, KS 67208	Conductor Pipe: Sizefeet
	Surface Casing: Size 8 5/8 feet 335
Abandoned OII Well Gas Well_	Input Well SWD Well D&A_X
Other well as hereinafter indicated	·
Plugging Contractor Cheyenne Drillin	g, Inc. License Number 5382
Address Box 916, Garden City, KS 678	46
Company to plug at: Hour: 9:45 a.m.	Pay: 8 Month: 1 Year:19
Plugging proposal received from Cla	
(company name) Cheyenne Drilling, Inc	(phone) 316-277-2062
	d spot cement through drill pipe Anhydrite 2510'
1st plug at 2510' with 50 sx cement, 2	nd plug at 1550' with 80 sx cement,
3rd plug at 360' with 50 sx cement, 4t	h plug at 40' with 10 sx cement,
5th plug to circulate rathole with 15	sx cement,
6th plug to circulate mousehole with 1	0 sx cement.
	Proposal Received by Richard Lacey
	(TECHNICIAN)
Plugging Operations attended by Agent	?: AllPartNone_X
Operations Completed: Hour: 1:30 p.m	Day: 8 Month: 1 Year: 19 87
ACTUAL PLUGGING REPORT 1st plug at 2	510' with 50 sx cement,
2nd plug at 1550 with 80 sx cement,	
3rd plug at 360' with 50 sx cement,	STATE CORPORATION COMMISSION
4th plug at 40-0' with 10 sx cement,	1AN 12 1989
5th plug to circulate rathole with 15	sx cement, CONSERVATION DIVISION
6th plug to circulate mousehole with 1	0 sx cement.
Remarks: Used 60/40 Pozmix 6% gel by	Halliburton.
	on is necessary, use BACK of this form.)
N FRA de Eof observe this pluggi	
re 1-12-87	Signed Signed (TECHNICYAN)

FORM CP-2/3 Rev.01-84