JOHN CARLIN R. C. LOUX JANE T. ROY PHILLIP R. DICK CAROL J. LARSON Governor Chairman Commissioner Commissioner Executive Secretary

## State Corporation Commission

## CONSERVATION DIVISION

(Oil, Gas and Water)

200 Colorado Derby Building WICHITA, KANSAS 67202

VERBAL PERMIT FORM (To be filed by Plugging Agent)

Dear Sir:
Mr. New Jang of Vanger Wilg Inc. has this
date requested permission to plug the following described well:
Operator's Full Name: Ernst & Steinle
Complete Address: Boy 859, Russell, Hans 67665
Lease Name: Gabel Well No. ##/
Location: SF-NW-NE Sec. 19 Twp. 14 Rge. 17 (E) (W)
County: Stis Total Depth: 3565 Et
Abandoned Oil Well Gas Well Input Well SWD Well D&AX
Other well as hereafter indicated:
Mr. was instructed to plug the well as follows:
Was instructed to plug the well as follows:  8 3/8" 245 = SP. cu 4/160 st Common-2% 60.3% Ca-Cl.
was instructed to plug the well as follows:
8 3/8" 245 E SP. cu 4/160 St Common-2 % Gel. 3 % Ca-Cl.
8 3/8" 245 E SP. cu 4/60 St Common-2% Gel. 3% la-ch.  Beder-10 St 5/50 Pozming 4% Gel. 3% la-ch. +8 5/8 Plug  Sport With Dell Stem-With Heavy mud Between all Plugs.  1 ST Plug. @ 660 Et 4/65 St Int.
8 3/8" 245 E SP. cu 4/60 St Common-2% Gel. 3% la-ch.  Chele-10 St 5/50 Pozming 4% Gel. 3% la-ch. +8 3/6 Plug  Spot With Dell Stem-With Heavy much Between all Plugo.  1 ST Plug. @ 660 Et 4/65 St Int.  2 Nº Plug. @ 270 E 4/30 St Int.
8 3/8" 245 E SP. cu 4/60 St Common-2% Gel. 3% la-ch.  Beder-10 St 5/50 Pozming 4% Gel. 3% la-ch. +8 5/8 Plug  Sport With Dell Stem-With Heavy mud Between all Plugs.  1 ST Plug. @ 660 Et 4/65 St Int.
8 3/8" 245 E SP. cu 4/60 St Common-2% Gel. 3% la-ch.  Chele-10 St 5/50 Pozming 4% Gel. 3% la-ch. +8 3/6 Plug  Spot With Dell Stem-With Heavy much Between all Plugo.  1 ST Plug. @ 660 Et 4/65 St Int.  2 Nº Plug. @ 270 E 4/30 St Int.
8 38" 245 E SP. Cu 1/160 t Common-2% Gel. 3% la-cl.  Order-110 t 5% Pozming 4% Gel. 3% la-cl. 78 36 Dlug  Spot With Doll Stem-With Heavy mud Between all Muyo.  1 5 Plug. 6 660 Et 165 t mt.  2 NP Plug. 6 270 to 1/30 th.  3 2 Plug. 6 270 to 1/30 th.
8 78" 245 E SP. Cur 1/60 St Common-2% Gel. 3/6 la-ll.  Order-110 St 5% Bermy 4% Gel. 3% la-ll. 78 36 Dlug  Spot With Drill Stem-With Heavy Mid Between all Plugs.  1 St Plug. C 660 Et ur/65 St Int.  2 No Plug. C 270 E m/30 St Int.  3 Ro Plug- Sulfo-Owig 440 E to 1/10 Text.  5 Short Class Story Covery truly yours. By Sun Ont)