| | 1090158 | \mathcal{O} |
|--------|--|--|
| | To: STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING SECTION 200 COLORADO DERBY BUILDING WICHITA, KANSAS 67202 | NQ NQ NQ , SEC. 33 , 7 20 S, R 34 WXX 330 feet from NXX section line |
| r. | TECHNICIAN'S PLUGGING REPORT | 330 feet from W/EX section line |
| | Operator License # 5506 | Lease Name Farm Lease "C" Well # 1 |
| | Operator: Woolsey Petroleum Corporation Name& Address 300 West Douglas, Suite 400 | CountyScott Well Total Depth5100 /65.75 feet |
| ٠ | Wichita, KS 67202 | Surface Casing: Size 8 5/8 feet 518 |
| | Abandoned Oll Well Gas Well | Input WellD&AX |
| | Other well as hereinafter indicated | |
| | Address IMA Plaza, Wichita, KS 67202 | License Number 6033 |
| | Company to plug at: Hour: 7:00 pm Day: | 16 Month: April Year:1984 |
| • | Plugging proposal received from Marvin | Julian |
| | (company name) Murfin | (phone) 316-267-3241 |
| | were: to fill hole with heavy mud and lst plug at 2220' with 50 sx cement | spot cement through drill pipe |
| | 2nd plug at 1620' with 50 sx cement | |
| | 3rd plug at 780' with 70 sx cement solid bridge 4th plug hulls - plug at 40' cement to 6th plug to circulate rathole with 15 sx Plugging Pro | surface with 10 sx cement cement posal Received by ASTALLUHAN (TECHNICIAN) |
| | Plugging Operations attended by Agent?: | |
| | ACTUAL PLUGGING REPORT 1st plug at 2220 | Month: April Year:1984 with 50 sx cement, 2nd plug at 1620' with 50 ment, 4th & 5th plugs - solid bridge - hulls - |
| • . | plug at 40' cement to surface with 10 | sx cement, 6th plug to circulate rathole with |
| | 15 sx cement. | STATE CORPORATION COMMISSION |
| | | MAY COMMISSION |
| | Remarks: Use 60/40 Pozmix 2% gel 3% cc by | Sun CONSECUTOR 1984 |
| I N | Value (If additional description is value of the plugging. | Sun CONSERVATION DIVISION Signed Signed CONSERVATION DIVISION Signed CONSERVATION DIVISION TECHNICIAN |
| INV. N | 0. 1457 4-16 MAY 1 8 1984 | FORM CP-2/3 Rev.01-84 |