TO: STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING SECTION 200 COLORADO DERBY BUILDING WICHITA, KANSAS 67202		API NUMBER 15- 171-20,342		
		SW_NE_SW_, SEC35	т 16	S, R 31 W
TECHNICIAN	'S PLUGGING REPORT	3630	feet from	E section line
Operator L	Icense # 5886	Lease Name		
Operator:	Chief Drilling Co., Inc.	County Scot	:t	151.13
	151 N. Main #700	Well Total Depth_		
	Wichita, KS 67202	Conductor Pipe: S		•
		Surface Casing: \$		
Abandoned	Oll WellGas Well			
	as hereinafter indicated	 		
	ontractor Warrior Drilling Co.,	Rig #2	icense Numbe	5883
,	05 Century Plaza, Wichita, KS 67		, compo ivembe	··
	plug at: Hour: 1:30 p.m. Day:		10	86
	roposal received from Marion Bur			101 : 19
- -	ame) Warrior Drilling Co.			216 652 7716
			E1e	316-653-7716 evation 2906
	fill hole with heavy mud and sp	of cement through dril	_1 pipe Anh	ovdrite 2314-34'
1st plug	at 2350 with 50 sx cement			
	at 1170' with 50 sx cement			
3rd plug	at 660' with 50 sx cement			
4th plug	at 360' with 40 sx cement, 5th p	lug at 40' with 10 sx	cement, 6th	plug to circulat
rathole w	rith 10 sx cement, 7th plug to ci Plugging Prop	osal Received by	Glenn Bar	
			(TECHNI	CIAN)
	perations attended by Agent?: A			
Operations	Completed: Hour: 3 p.m. Day:	22 Month: 10)Ye	86 ear:19
ACTUAL PLU	GGING REPORT 1st plug at 2340	with 50 sx cement		
2nd plug	at 1500' with 70 sx cement		,	
3rd plug	at 660' with 40 sx cement, 4th p	lug at 360' with 50 sx	cement	
5th plug	at 40' with 10 sx cement, 6th pl	ug to circulate ratho	le with 15 s	ex cement
7th plug	to circulate mousehole with 10 s	ex cement.		
		10.24-86		
Remarks: U	Jsed 60/40 Pozmix 6% gel by Allie	36.		
	(if additional description is		of this form	1.)
Nak O &		\circ	11	
TO 10-	-24-86	Signed Nan	Jood of	