To: STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING SECTION 200 COLORADO DERBY BUILDING WICHITA, KANSAS 67202		API NUMBER 15-171-20,271-700 SW/4 SE/4 Se/4, SEC. 16 , T 16 s, F 330 feet from XW/S sec	R 34 W 200
TECHNICIA	N'S PLUGGING REPORT	990feet from XW/E sec	stion line
Operator	License # 6029	Lease Name Koehn Well #	1-16
•	Ladd Petroleum Corporation	County Scott	·
Name& Address	P. O. Box 2848	Well Total Depth5095 /6	5. 59,00
	Tulsa, OK 74101	Conductor Pipe: Sizefeet	t
		Surface Casing: \$1ze 8 5/8 feet_	1628
Abandoned	Oll Well Gas Well	Input WellSWD Well	
	•	Co., Inc. License Number	
	435 Page Court, 220 West Dougla		
Company to	o piug at: Hour: 12:30 am Day:	12 Month: April Year:19	84
	proposal received from		<u></u>
		(phone)918-5	87-6531
•	to fill hole with heavy mud and		0, 0001
	g at 2500° with 50 sx cement	spot cement through drift pipe.	
	g at 1670' with 50 sx cement		
· · · · · · · · · · · · · · · · · · ·			
	g at 680' with 25 sx cement solid bridge		
6th plu	g hulls - plug at 40' cement g to circulate rathole with 15 sx Plugging Prop	cement cement (TECHNICIAN)	this
Plugging (Operations attended by Agent?: A	1 Part None	X
Operations	s Completed: Hour: 2:30 am Day:	12 Month: April Year:19	84
ACTUAL PL	UGGING REPORT 1st plug at 2500'	with 50 sx cement, 2nd plug at 1670'	with 50
sx ceme	nt, 3rd plug at 680° with 25 sx c	ement, 4th & 5th plugs - solid bridge	- hulls
plug at	40' cement to surface with 10	sx cement, and 6th plug to circulate	
rathole	with 15 sx cement	STATE . F	35000
			RECEIVED ORATION COMA
		APR	16.40
Remarks:	Use 60/40 Pozmix 2% gel 3% cc by	Halliburton Wichitan necessary, use BACK of this form.)	ION DIVISION
\$ 970/1° = _4-1	did not) observe this plugging.	Signed Gulf Gethologian)	-as
•a_//6			RM CP-2/3 Rev.01-84