Ϋ́,	ADT Number 15 100 00 040 - A.
TO: STATE CORPORATION COMMISSION 10-2	API Number: 15-199-20,240-00-00
CONSERVATION DIVISION - PLUGGING	<u>NE NE SW</u> /4 SEC. <u>22</u> , <u>15</u> S, <u>41</u> W
130 SOUTH MARKET, SUITE 2078	2000 feet from S section line
WICHITA, KANSAS 67202	2050 feet from E section line
•	
Operator license# 8541	Lease: O' Trimble Well # 1
Operator: Petex, Inc.	County: Wallace
operator: Feter, Inc.	
Address: 1610 E. Sunshine	Well total depth 5307 172, 47 feet
Springfield, Missouri 65804	Conductor Pipe: 0 inch @ 0 feet
417-887-1225	Surface pipe 8 5/8 Inch @ 364 feet
	·
Aband. oil well, Gas well, Input well	, SWD, D & A_ X
Dissolve and the Markle Duillian German	T :
Plugging contractor: Murfin Drilling Company	License#
Address:	:
Address.	
Company to plug at: Hour: P.M. Day: 2 Mont	h: Year: 1996
Plugging proposal received from:	
	_,
Company:	Phone:
Were: Order 200 sxs 60/40 pozmix - 6% gel -	1/4# Flo-gapl par gagk
were: Older 200 SRS 00/40 pozmik - 0% ger -	1/4# FIO-Seal pel Sack.
Plugging Proposal Received by: <u>Marvin Miller</u> Plugging operations attended by agent? All[
riugging operations attended by agent: Air	j, Parci j, Nonei x j
Completed: Hour_8:00 P.M. , Day:, M	onth: October , Year: 1996
Actual plugging report:	7 7
1st. Plug at 2740' with 25 sxs cement.	27.7.3
2nd. Plug at 1995' with 100 sxs cement.	the state of the s
3rd. Plug at 415' with 40 sxs cement.	
4th. Plug at 40' with 10 sxs cement - 8 5/8" wi 15 sxs cement in rathole.	
10 sxs cement in mousehole.	
Anhydrite 2726' - 2755'.	\$ 00°
	2 3
Remarks:	80 23
Condition of casing(in hole): GOOD BAD_	Anhy.plug: YES X NO
Bottom plug(in place): YES, CALC, NO	
Plugged through TUBING, CASING	
T did[1 / did not [obcorro the plugging	Marin Miller
I did[] \ did not [x] observe the plugging.	(acent)
	Form CP-2/3
DATE 10-20-90	r v
DATE 10-28-96 INV. NO. 46829	
INV. NO. July	