

4-032149

TO: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING  
130 SOUTH MARKET, SUITE 2078  
WICHITA, KANSAS 67202

4-5

API Number: 15-199-20,235-00-00  
53'E.&98'S.of  
C S2 SW SW /4 SEC. 32 , 15 , 41 W  
232 feet from S section line  
4577 feet from E section line

Operator license# 5152

Lease: Kuder Well # 2-32

Operator: Lee Banks d/b/a Banks Oil Co.

County: Wallace

Address: 200 West Douglas - Suite #550  
Wichita, Kansas 67202

Well total depth 5180 <sup>1108.35</sup> feet  
Conductor Pipe: 0 inch @ 0 feet  
Surface pipe 8.5/8 Inch @ 357 feet

Aband. oil well\_\_\_, Gas well\_\_\_, Input well\_\_\_, SWD\_\_\_, D & A

Plugging contractor: Murfin Drilling Company, Inc. License# 30606

Address: Wichita, Kansas 67202

Company to plug at: Hour: P.M. Day: 5 Month: April Year: 1996

Plugging proposal received from: Jim

Company: Murfin Drilling Company, Inc. Phone: \_\_\_\_\_

Were: Order 200 sxs 60/40 pozmix - 6% gel. - 3% c.c. - W.P.  
Allied Cement Company.  
Condition hole with no less than 36 vis. mud.

Plugging Proposal Received by: Carl Goodrow

Plugging operations attended by agent? All[ ], Part[ ], None[ X ]

Completed: Hour: 6:30 P.M., Day: 5, Month: April, Year: 1996

Actual plugging report: Spot plugs with drill pipe.

- 1st. Plug at 2725' w/25 sxs.
- 2nd. Plug at 1660' w/100 sxs.
- 3rd. Plug at 400' w/40 sxs.
- 4th. Plug at 40' w/10 sxs.
- Circulated 15 sxs in rathole.
- Circulated 10 sxs in mousehole.

Remarks: Anhy. 2708' - 2740'.

Condition of casing(in hole): GOOD \_\_\_ BAD \_\_\_ Anhy.plug: YES  NO \_\_\_  
Bottom plug(in place): YES \_\_\_ , CALC \_\_\_ , NO \_\_\_ Dakota plug: YES \_\_\_ , NO \_\_\_  
Plugged through TUBING \_\_\_ , CASING \_\_\_ . Elevation: 3767 GL

I did[ ] / did not[ X ] observe the plugging.

*Carl Goodrow*  
(agent)

INVOICED  
5-29-96  
45655