

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15-011-20,275-00-00  
SE1/4, Sec. 2, T 16 S, R 39 W1/4  
990 feet from N1/8 section line  
2310 feet from W1/8 section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5005

Lease Name HERL "E" Well # 1

Operator: SUNBURST EXPLORATION Co., Inc County GREELEY  
Name & Address 708 ONE MAIN PLACE  
Wichita, KS 67202

Well Total Depth 5300 feet  
Conductor Pipe: Size \_\_\_\_\_ feet  
Surface Casing: Size 10 3/4 feet 315'

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Abercrombie Drilling Inc License Number 5422

Address 801 UNION CENTER, WICHITA, KS 67202

Company to plug at: Hour: 6:00 PM, Day: 20 Month: NOV Year: 1982

VERBAL PLUGGING ORDERS GIVEN TO W. W. TOWNS Rig # 9

(company name) ABERCROMBIE (phone) 316-262-7841

were: Use 50/50 Pozmix, 4% gel, 3% CC, and place the  
1st plug @ 1500' w/ 10 1/2" cement; 2nd plug @ 780' w/ 35 1/2" cement;  
3rd plug @ 330' w/ 10 1/2" cement; 4th plug of solid  
bridge of bulls & 10 3/4" plug; 5th plug 70'-0" w/ 20 1/2" cement.  
Rathole w/ 10 1/2" circ & mouse hole w/ 10 1/2" circ.

Signed R. Barluttan (TECHNICIAN)

Plugging Operations attended by Agent?: All \_\_\_\_\_ Part \_\_\_\_\_ None

Operations Completed: Hour: 6:00 PM Day: 20 Month: NOV Year: 1982

ACTUAL PLUGGING REPORT plugged as ordered.  
Cementing by Sun.

RECEIVED  
STATE CORPORATION COMMISSION  
11-24-82  
NOV 24 1982  
CONSERVATION DIVISION  
Wichita Kansas

Remarks: Anhydrite top @ 2583'  
10 3/4" set w/ 225 cement.

I hereby certify that the above plugging instructions were given as herein stated  
and that I ~~did~~ / did not) observe this plugging.

INVOICED  
DATE 12-27-82  
INV. NO. 1998-W

Signed R. Barluttan (TECHNICIAN)