

API NUMBER 15-199-20-0940000

To: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

C-NW-5E, SEC. 8, T 14 S, R 40 E

2250 feet from S section line

2100 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5533

Lease Name Robben Well # 1-8

Operator: Shinolead Petroleum, Inc

County Wallace 58.11

Name & Address: P.O. Box 8287 Munga St

Well Total Depth 1788 feet

Wichita, Kans. 67208

Conductor Pipe: Size 0 feet

Todd Seymour

Surface Casing: Size 8 5/8 feet 370

Abandoned Oil Well Gas Well Input Well SWD Well D&A

Other well as hereinafter indicated Had trouble maintaining Circulation - Plugged

Plugging Contractor Halliburton Cmt Company License Number _____

Address East Hwy 40 Hays, Kansas. 67601

Company to plug at: Hour: 1:00 AM Day: 1st Month: Nov Year: 19 86

Plugging proposal received from Walley Torone

(company name) Abercrombie Drilling Inc (phone) 316-681-3921

were: 8 5/8" - 370' 50' cement / 360' cement followed with 125' cement spotted "1/2" tubing, cement by holes.

Total of 485' cement was used on surface pipe since they had to run 3" tubing to circulate

Proposal - Ordered 235' 60/40 Formax 3% CaCl₂ - 1' shale. Elev. 3608 - Why?

Just Circulation @ 430 ft. Spotted 50' cement @ 350 ft, @ 1200 ft again later partial Circulation

Regain Circulation Just, @ 1340 ft Spent 100' cement 1/2 cell shale, @ 440' Spent 100' cement 1/4 cell shale.

3RD Plug @ 40' 60/10' cement, 15' In Rat Hole (circulate) 10' In Mouse Hole (circulate)

Plugging Proposal Received by MJ Seymour (TECHNICIAN)

Fluid Condition - Vis to 42. Bkls plugging.

Plugging Operations attended by Agent?: All Part None

Operations Completed: Hour: 2:30 AM Day: 1st Month: Nov Year: 19 86

ACTUAL PLUGGING REPORT Ordered 235' 60/40 Formax 3% CaCl₂ 1/2 shale.

Spot with Drill Stem, Reconditioned Hole, Heavy Mud between all plugs.

Displace first two plugs w/ mud.

1st plug @ 1340 ft w/ 100' cement 1/2 cell shale, 2nd Plug @ 440' 100' cement 1/2 shale

3RD Plug @ 40' 60/10' cement, 15' In Rat Hole (circulate)

10' In Mouse Hole (circulate) Cemented by Halliburton Cmt.

Remarks: _____

INVOICED

If additional description is necessary, use BACK of this form.)

DATE 11-12-86 observe this plugging. 11-10-86

1 Signed Marion Schmidt (TECHNICIAN)

INV. NO. 15325