

API NUMBER 15-071-20,449-00-00

To: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

NW SW NW, SEC. 18, T 16 S, R 42 W EX

3630 feet from S section line

4950 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 3504

Lease Name Westfield Well # 1

Operator: Spurlock & Spines Expl., Inc.
Name & Address: 525 Fourth Financial Center
Wichita, KS 67202

County Greeley 177-25

Well Total Depth 5300 feet

Conductor Pipe: Size _____ feet

Surface Casing: Size 8 5/8 feet 523

Abandoned Oil Well _____ Gas Well _____ Input Well _____ SHD Well _____ D&A X

Other well as hereinafter indicated _____

Plugging Contractor H-30 Drilling Inc. License Number 5107

Address 251 North Water, Suite 10, Wichita, KS 67202

Company to plug at: Hour: 1 a.m. Day: 30 Month: 3 Year: 19 88

Plugging proposal received from Dennis Wilson

(company name) H-30 Drilling Inc. (phone) 316-263-2043

were: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 2600-95'

1st plug at 2695' with 50 sx cement, 2nd plug at 1650' with 50 sx cement,

3rd plug at 550' with 40 sx cement, 4th plug at 40' with 10 sx cement,

5th plug to circulate rathole with 15 sx cement,

6th plug to circulate mousehole with 10 sx cement.

Plugging Proposal Received by Dan Goodrow (TECHNICIAN)

Plugging Operations attended by Agent?: All _____ Part _____ None X

Operations Completed: Hour: 4:30 a.m. Day: 30 Month: 3 Year: 19 88

ACTUAL PLUGGING REPORT 1st plug at 2695' with 50 sx cement.

2nd plug at 1650' with 50 sx cement,

3rd plug at 550' with 40 sx cement.

4th plug at 40' with 10 sx cement,

5th plug to circulate rathole with 10 sx cement.

6th plug to circulate mousehole with 10 sx cement.

RECEIVED STATE CORPORATION COMMISSION

APR - 6 1988 04-0688

CONSERVATION DIVISION WICHITA, KANSAS

Remarks: Used 60/40 Pozmix 3% gel by Halliburton. (If additional description is necessary, use BACK of this form.)

INVOICED (copy to be observed this plugging.)

DATE 4-6-88

INV. NO. 20313 3-30

Signed Dan Goodrow (TECHNICIAN)

NOTICE OF INTENTION TO DRILL

Expected Spud Date 3-4-88
 month day year

API Number 15-071-20,449-00-00 2

OPERATOR: License # 3504
 Name Spurlock & Spines Expl., Inc.
 Address 525 Fourth Financial Center
 City/State/Zip Wichita, KS 67202
 Contact Person Robert C. Spurlock
 Phone 316/264-2808

NW SW NW Sec. 18 Twp. 16 S, Rg. 42W
3630 Ft. from South Line of Section
4950 Ft. from East Line of Section

CONTRACTOR: License # 5107
 Name H-30 Drilling Inc.
 City/State Wichita, KS 67202

(Note: Locate well on Section Plat on reverse side)
 Nearest lease or unit boundary line 330 feet
 County Greeley
 Lease Name WESTFIELD Well # 1

Well Drilled For: Well Class: Type Equipment:
 Oil Storage Infield Mud Rotary
 Gas Inj Pool Ext. Air Rotary
 OWWO Expl Wildcat Cable

Ground surface elevation 3880 feet MSL
 Domestic well within 330 feet: yes no
 Municipal well within one mile: yes no

If OWWO: old well info as follows:
 Operator _____
 Well Name _____
 Comp Date _____ Old Total Depth _____

Depth to bottom of fresh water 300'
 Depth to bottom of usable water 1700'
 Surface pipe by Alternate: _____
 Surface pipe planned to be set 470'

I certify that well will comply with K.S.A. 55-101, et seq., plus eventually plugging hole to KCC specifications.
 Date 2/25/88 Signature of Operator or Agent [Signature] Title President

For KCC Use:
 Conductor Pipe Required _____ feet; Minimum Surface Pipe Required _____ feet per Alt. X(2)
 This Authorization Expires 8-26-88 Approved By [Signature]

EFFECTIVE DATE: 3-2-88
 set 523' of 85/8 on 3-22-88

NW SW NW Sec. 18 Twp. 16 S, Rg. 42W

PLUGGING PROPOSAL IF ABOVE IS D & A

This plugging proposal will be reviewed and approved or revised at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).

1st plug @ ft. deep.....	3730.....	or formation with.....	50.....	feet of.....
2nd plug @ ft. deep.....	1680.....	or formation with.....	80.....	feet of.....
3rd plug @ ft. deep.....	480.....	or formation with.....	50.....	feet of.....
4th plug @ ft. deep.....	40.....	or formation with.....	10.....	feet of.....
5th plug @ ft. deep.....	or formation with.....	feet of.....
(2) Rathole to surface minus 5 feet	15	(b) Mousehole to surface minus 5 feet	10	

2600
2695

PUSHER Dinn's Wilson
 TD 5300 FORMATION MISS.
 SURFACE PIPE 8 5/8" @ 523'
 ANHYDRITE 2600 ELEVATION 3880'
 STARTING TIME & DATE 3-30-88
 COMPLETION TIME & DATE 4:30 AM
 1st PLUG @ 2695 FT. WI 50 SX
 2nd PLUG @ 1650 FT. WI 50 SX
 3rd PLUG @ 550 FT. WI 40 SX
 4th PLUG @ 40 FT. WI 10 SX
 RAT HOLE CIRCULATED WI 10 SX
 MOUSE HOLE CIRCULATED WI 10 SX
 WATER WELL PLUGGED WI _____ SX
 CEMENT COMPANY [Signature]
 TECHNICIAN D.G.

RECEIVED
 STATE CORPORATION COMMISSION
 APR - 6 1988
 CONSERVATION DIVISION
 Wichita, Kansas
 6/00 670
 6/0/88 w 3% gel