

15-15-10420-0003
KANSAS CORPORATION COMMISSION
ONE POINT STABILIZED OPEN FLOW OR DELIVERABILITY TEST

(See Instructions on Reverse Side)

Type Test:

- Open Flow
 Deliverability

Test Date:

API No. 15

Company Mull Drilling Company, Inc.		Lease Tatlock A		Well Number 1	
County Pratt	Location SW NW NW	Section 31	TWP 26S	RNG (E/W) 15W	Acres Attributed
Field Tatlock SW		Reservoir Mississippian & Cherokee		Gas Gathering Connection Oneok Midstream Gas Supply	
Completion Date 5-14-58		Plug Back Total Depth 4488		Packer Set at	
Casing Size 5 1/2"	Weight 14#	Internal Diameter 5.012	Set at 4539	Perforations 4456-60, 4464-66, 4438-41&4430-34	To
Tubing Size 2 3/8"	Weight 4.7#	Internal Diameter 1.995	Set at 4440	Perforations	To
Type Completion (Describe) Commingled		Type Fluid Production Oil & Water		Pump Unit or Traveling Plunger? Yes / NO	
Producing Thru (Annulus / Tubing) Annulus		% Carbon Dioxide		% Nitrogen	
Vertical Depth(H)		Pressure Taps		(Meter Run) (Prover) Size	
Pressure Buildup: Shut in 9-19-2011 19 at 1:00 (AM) (PM) Taken		19 at		(AM) (PM)	
Well on Line: Started 9-20-2011 19 at 1:00 (AM) (PM) Taken		19 at		(AM) (PM)	

OBSERVED SURFACE DATA

Duration of Shut-in **24** Hours

Static / Dynamic Property	Orifice Size inches	Circle one: Meter or Prover Pressure psig	Pressure Differential in (h) Inches H ₂ O	Flowing Temperature t	Well Head Temperature t	Casing Wellhead Pressure (P _w) or (P _i) or (P _e)		Tubing Wellhead Pressure (P _w) or (P _i) or (P _e)		Duration (Hours)	Liquid Produced (Barrels)
						psig	psia	psig	psia		
Shut-in	.375					80				24	
Flow	.375					37					

FLOW STREAM ATTRIBUTES

Plate Coefficient (F _p) (F _v) Mcfd	Circle one: Meter or Prover Pressure psia	Press Extension $\sqrt{P_m \times H_w}$	Gravity Factor F _g	Flowing Temperature Factor F _t	Deviation Factor F _{pv}	Metered Flow R (Mcfd)	GOR (Cubic Feet/ Barrel)	Flowing Fluid Gravity G _m

(OPEN FLOW) (DELIVERABILITY) CALCULATIONS

(P_e)² = _____ : (P_w)² = _____ : P_d = _____ % (P_e - 14.4) + 14.4 = _____ : (P_d)² = 0.207
(P_d)² = _____

(P _e) ² - (P _w) ² or (P _e) ² - (P _d) ²	(P _w) ² - (P _d) ²	Choose formula 1 or 2: 1. P _e ² - P _w ² 2. P _w ² - P _d ² divided by: P _e ² - P _w ²	LOG of formula 1. or 2. and divide by: $\frac{P_e^2 - P_w^2}{P_e^2 - P_d^2}$	Backpressure Curve Slope = "n" ----- Assigned Standard Slope	n x LOG []	Antilog	Open Flow Deliverability Equals R x Antilog Mcfd

Open Flow **Mcfd @ 14.65 psia** Deliverability **Mcfd @ 14.65 psia**

The undersigned authority, on behalf of the Company, states that he is duly authorized to make the above report and that he has knowledge of the facts stated therein, and that said report is true and correct. Executed this the _____ day of **9-20**, 20**11**

Witness (if any) _____ For Company **Mull Drilling RECEIVED**

For Commission _____ Checked by **OCT 05 2011**

KCC WICHITA

I declare under penalty or perjury under the laws of the state of Kansas that I am authorized to request exempt status under Rule K.A.R. 82-3-304 on behalf of the operator Mull Drilling Company, Inc. and that the foregoing information and statements contained on this application form are true and correct to the best of my knowledge and belief based upon gas production records and records of equipment installation and/or of type completion or upon use of the gas well herein named.

I hereby request a permanent exemption from open flow testing for the Tatlock A #1 gas well on the grounds that said well:

(Check one)

- is a coalbed methane producer
- is cycled on plunger lift due to water
- is a source of natural gas for injection into an oil reservoir undergoing ER
- is on vacuum at the present time; KCC approval Docket No. _____
- is incapable of producing at a daily rate in excess of 150 mcf/D

Date: _____

Signature: Jim Hoso

Title: Prod Foreman

Instructions: All active gas wells must have at least an original G-2 form on file with the conservation division. If a gas well meets the eligibility criteria set out in KCC regulation K.A.R. 82-3-304, the operator may complete the statement provided above in order to obtain a testing exemption.

At some point during the succeeding calendar year, wellhead shut-in pressure shall be measured after a minimum of 24 hours shut-in/buildup time and shall be reported on the front side of this form under "observed surface data." Shut-in pressure shall thereafter be reported yearly in the same manner.

The G-2 form conveying the newest shut-in pressure reading shall be filed with the Wichita office no later than thirty (30) days after the taking of the pressure reading. The form must be signed and dated on the front side as though it was a verified report of test results.