AND NUMBER 15. OF PAIR COMMISSION AND NUMBER 15. OF PAIR COMPOSITION OF COMMISSION OF	```	1 060634		071 20 27/ -00 40	
TECHNICIAN'S PLUGSING REPORT 990 feet from S section III TECHNICIAN'S PLUGSING REPORT 990 feet from E section III Operator: TXO Production Corp. County Greeley 771, 2 Denver, CO 80264 County Greeley 771, 2 Denver, CO 80264 County Feet feet Surface Casing: Size 8 5/8" feet 474 Abandoned Oil Neil Gas Neil Input Neil SND Neil OAA X Other well as hereineffer indicated Plugsing Contractor Muffin Drilling Co. License Number 6033 Address 250 North Water, Suite 300, Wichita, KS67202 Company to plug at: Hour: 12:30 pm Day: 3 Month: August Year: 19 85 Plugsing proposal received from Frank Tsuru (compeny acce) TXO (phone) 303-861-4246 Elevation 3907 vere: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 2750' 1st plug at 480' with 40 sx cement 2nd plug at 480' with 40 sx cement 4th plug at 480' with 40 sx cement 4th plug at 480' with 40 sx cement 1nd plug builts - plug at 480' with 40 sx cement 1nd plug builts - plug at 480' with 40 sx cement 1nd plug builts - plug at 480' with 40 sx cement 1nd plug builts - plug at 480' with 40 sx cement 1nd plug builts - plug at 480' with 40 sx cement 2nd plug at 480' with 40 sx cement 2nd plug at 480' with 40 sx cement 3nd plug for circulate road by with 15 sx 6 8th plug to circulate mouse hole with 10 sx cement, 3rd plug at 720' with 40 sx cement, 3rd plug at 1350' with 50 sx cement, 3rd plug at 720' with 40 sx cement, 4th plug at 530' with 40 sx cement, 5th plug to circulate mouseahole with 10 sx cement, 3rd plug at 720' with 40 sx cement, 4th plug to circulate mouseahole with 10 sx cement. Remerks: Used 60/40 Pozmix 6% gel by Halliburton. (11 seditional description is necessary, use BACK of this fore.) 20 CONSERNATION BUSINGS FORM CP-22' ELECTIVED 10 FORM CP-22' ELECTIVED 10 FORM CP-22' ELECTIVED 10 FORM CP-22' ELECTIVED 10 FORM CP-22' ELECTIVED 11 FORM CP-22' ELECTIVED 12 FORM CP-22' ELECTIVED 13 FORM CP-22' ELECTIVED 14 FORM CP-22' ELECTIVED 15 FORM CP-22' ELECTIVED 16 FORM CP-22' ELECTIVED 17 FORM CP-22'	TO: STATE CORP	•		API NUMBER 15- 071-20,374 -00-00	
TECHNICIAM'S PLUGGING REPORT Operator: Internation State		•	SECTION	NW <u>SE SE</u> , SEC. 1, 'T 16 S, R 43	_W /2
Operator: License / 5171				990feet from S section	lin
Operator: TXO Production Corp. Name 1800 Lincoln Center Building Denver, CO 80264 Conductor Pipe: Size Surface Cosing: Size 8 5/8" feet 474 Abandoned Oil Well Gas Well Imput Well SWD Well D&A X Other well as hereinafter Indicated Plugging Contractor Muffin Drilling Co. License Number 6033 Address 250 North Water, Suite 300, Wichita, KS67202 Company to plug ef: Hour: 12:30 pm Dey: 3 Month: August Year: 19 85 Plugging proposal received from Frank Tsuru (company anne) TXO (phone) 303-861-4246 Elevation 3907' were: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 2750' 1st plug at 2750' with 50 sx cement 2nd plug at 1350' with 50 sx cement 3rd plug at 720' with 40 sx cement 4th plug at 480' with 40 sx cement 5th plug hulls - plug at 480' with 10 sx cement 7th plug for Sirculate rat hole with 10 sx cement, 2nd plug at 1350' with 10 sx cement 3rd plug at 720' with 50 sx cement Operations Completed: Hour: 2:30 pm Dey: 3 Month: August Year: 19 85 ACTUAL PLUGGING REPORT 1st plug at 2750' with 50 sx cement, 2nd plug at 1350' with 50 sx cement, 3rd plug at 720' with 40 sx cement, 4th plug at 530' with 40 sx cement, 5th plug to circulate mouse hole with 10 sx cement, 3rd plug at 720' with 40 sx cement, 4th plug at 530' with 40 sx cement, 7th plug to circulate rat hole with 15 sx cement, 8th plug to circulate mouse hole with 10 sx cement, 3rd plug at 720' with 40 sx cement, 4th plug at 530' with 40 sx cement, 7th plug to circulate rat hole with 15 sx cement, 8th plug to circulate mousechole with 10 sx cement. Remerks: Used 60/40 Pozmix 6% gel by Hählibutton. (If additional description is necessary, use BACK of this form.) AUG 13 1895 CONSENUATION MUSICAN FORM CP-22' AUG 13 1995 FORM CP-22' AUG 13 1995 FORM CP-22' AUG 13 1995 FORM CP-22' FO	TECHNICIAN	'S PLUGGING REPORT		990 feet from E section	lin
Denver, CO 80264 Denver, CO 80264 Denver, CO 80264 Conductor Pipe: Size Surface Casing: Size 8 5/8" feet Surface Casing: Size 8 5/8" feet Abandoned Oil Well Gas Well Input Well SMD Well Other well as hereinefter indicated Plugging Contractor Muffin Drilling Co. License Number 6033 Address 250 North Water, Suite 300, Wichita, K867202 Company to plug et: Hour: 12:30 pm Day: 3 Month: August Year:19 85 Plugging proposal received from TXO (phone) 303-861-4246 Elevation 3907' vere: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 2750' 1st plug at 2750' with 50 sx cement 2nd plug at 1350' with 50 sx cement 3rd plug at 1350' with 40 sx cement 4th plug at 480' with 40 sx cement Solid bridge Sth plug hulls - plug at 481ugging Proposal Received by Paul A. Luthi cement to surface with 10 sx cement 7th plug to circulate rat hole with 18 sx 6 8th plug to circulate mouse hole with 10 or None X Operations Completed: Hour: 2:30 pm Day: 3 Month: August Year:19 85 ACTUAL PLUSGING REPORT 1st plug at 2750' with 50 sx cement, 2nd plug at 1350' with 50 sx cement, 3nd plug at 720' with 40 sx cement, 4th plug at 530' with 40 sx cement, 5th plug to circulate rat hole with 15 sx cement, 8th plug to circulate mouseehole with 10 sx cement. RECENSION RECENSION AUG 13 1805 CREENION AUG 13 1805 CREENI	Operator L	icense / 5171	<u> </u>	Lease Name Edsall "F" Well # 5	
Denver, CO 80264 Denver, CO 80264 Denver, CO 80264 Conductor Pipe: Size Surface Casing: Size 8 5/8" feet Surface Casing: Size 8 5/8" feet Abandoned Oil Well Gas Well Input Well SMD Well Other well as hereinefter indicated Plugging Contractor Muffin Drilling Co. License Number 6033 Address 250 North Water, Suite 300, Wichita, K867202 Company to plug et: Hour: 12:30 pm Day: 3 Month: August Year:19 85 Plugging proposal received from TXO (phone) 303-861-4246 Elevation 3907' vere: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 2750' 1st plug at 2750' with 50 sx cement 2nd plug at 1350' with 50 sx cement 3rd plug at 1350' with 40 sx cement 4th plug at 480' with 40 sx cement Solid bridge Sth plug hulls - plug at 481ugging Proposal Received by Paul A. Luthi cement to surface with 10 sx cement 7th plug to circulate rat hole with 18 sx 6 8th plug to circulate mouse hole with 10 or None X Operations Completed: Hour: 2:30 pm Day: 3 Month: August Year:19 85 ACTUAL PLUSGING REPORT 1st plug at 2750' with 50 sx cement, 2nd plug at 1350' with 50 sx cement, 3nd plug at 720' with 40 sx cement, 4th plug at 530' with 40 sx cement, 5th plug to circulate rat hole with 15 sx cement, 8th plug to circulate mouseehole with 10 sx cement. RECENSION RECENSION AUG 13 1805 CREENION AUG 13 1805 CREENI		TXO Production Corp.		County Greeley /7/	.2
Surface Casing: Size 8 5/8" feet 474 Abandoned Oil Weil Gas Weil Input Weil SND Weil DAA X Other weil as hereinafter indicated Plugging Contractor Müffin Drilling Co. License Number 6033 Address 250 North Water, Suite 300, Wichita, KS67202 Company to plug at: Hour: 12:30 pm Day: 3 Month: August Year:19 85 Plugging proposal received from Frank Tsuru (company name) TXO (phone) 303-861-4246 Elevation 3907 were: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 2750' 1st plug at 2750' with 50 sx cement 3rd plug at 1350' with 50 sx cement 3rd plug at 720' with 40 sx cement 4th plug at 480' with 40 sx cement 5th plug hulls - plug at 48' ugging Proposal Received by Parl A. Luthi cement to surface with 10 sx cement (TECHNICIAN) The plug to circulate rat hole with 15 sx & 8th plug to circulate mouse hole with 10 sy generic in strended by Agenti: 18 None X Operations Completed: Hour: 2:30 pm Day: 3 Month: August Year:19 85 ACTUAL PLUGGING REPORT 1st plug at 2750' with 50 sx cement, 2nd plug at 1350' with 50 sx cement, 3rd plug at 720' with 40 sx cement, 4th plug at 530' with 40 sx cement, 5th plug to circulate rat hole with 15 sx cement, 8th plug to circulate mouseshole with 10 sx cement. Remarks: Used 60/40 Pozmix 6% gel by Halliburton. (If additional description is necessary, use BACK of this form.) REFERENCES IN 1885 AUG 1 3 1895 CR-13-14300 CR-1		1800 Lincoln Center I	Building	(Mississi Well Total Depth5270	
Surface Casing: Size 8 5/8" feet 474 Abandoned Oli Meii Gas Meii Input Weii SWD Weii DAA X Other well as hereinstfer indicated Plugging Contractor Muffin Drilling Co. License Number 6033 Address 250 North Water, Suite 300, Wichita, KS67202 Company to plug at: Hour: 12:30 pm Day: 3 Month: August Year:19 85 Plugging proposel received from Frank Tsuru (company name) TXO (phone) 303-861-4246 Elevation 3907' Were: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 2750' lst plug at 2750' with 50 sx cement 2nd plug at 1350' with 50 sx cement 3rd plug at 480' with 40 sx cement 4th plug at 480' with 40 sx cement 7th plug to circulate rat hole with 15 sx & 8th plug to circulate mouse hole with 10 sx cement, 2nd plug at 90 pratfors elevated by Agentic. Mone X Operations Completed: Hour: 2:30 pm Day: 3 Month: August Year:19 85 ACTUAL PLUGGING REPORT 1st plug at 2750' with 50 sx cement, 2nd plug at 1350' with 50 sx cement, 3rd plug at 720' with 40 sx cement, 4th plug at 530' with 40 sx cement, 5th plug to circulate mousehole with 10 sx cement. Remarks: Used 60/40 Pozmix 6% gel by Halliburton. (If additional description is necessary, use BACK of this form.) Remarks: Used 60/40 Pozmix 6% gel by Halliburton. (If additional description is necessary, use BACK of this form.) Remarks: Used 60/40 Pozmix 6% gel by Halliburton. (If additional description is necessary, use BACK of this form.) Remarks: Used 60/40 Pozmix 6% gel by Halliburton. (If additional description is necessary, use BACK of this form.) Remarks: Used 60/40 Pozmix 6% gel by Halliburton. (If additional description is necessary, use BACK of this form.) Remarks: Used 60/40 Pozmix 6% gel by Halliburton. (If additional description is necessary, use BACK of this form.) Remarks: Used 60/40 Pozmix 6% gel by Halliburton. (If additional description is necessary) (OCTUBENTIAL MUSICO CONSENTATION MUSICO CONS		Denver, CO 80264		Conductor Pipe: Sizefeet	
Other well as hereinefter indicated Plugging Confrector Muffin Drilling Co. License Number 6033 Address 250 North Water, Suite 300, Wichita, KS67202 Company to plug at: Hour: 12:30 pm Day: 3 Month: August Year:19 85 Plugging proposal received from Frank Tsuru (company name) TXO (phone) 303-861-4246 Elevation 3907* were: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 2750* 1st plug at 2750* with 50 sx cement 2nd plug at 1350* with 50 sx cement 3rd plug at -720* with 40 sx cement 4th plug at 480* with 40 sx cement solid bridge 5th plug hulls - plug at 481 ugging Proposal Received by Paul A. Luthi cement to surface with 10 sx cement 7th plug to circulate rat hole with 15 sx & 8th plug to circulate mouse hole with 10 sr Operations Completed: Hour: 2:30 pm Day: 3 Month: August Year:19 85 ACTUAL PLUGGING REPORT 1st plug at 2750* with 50 sx cement, 2nd plug at 1350* with 50 sx cement, 3rd plug at 720* with 40 sx cement, 4th plug at 530* with 40 sx cement, 5th plug & 6th plug - solid bridge - hulls - plug at 40* cement to surface with 10 sx cement 7th plug to circulate rat hole with 15 sx cement, 8th plug to circulate mouseshole with 10 sx cement. Remarks: Used 60/40 Pozmix 6% gel by Hälliburton. (If additional description is necessary, use BACK of this form.) RECEIVED AUG 13 1905 AUG 13 1905 AUG 13 1905 FORM CP-27 AUG 13 1905 FORM CP-27 FORM CP-27 AUG 13 1905 FORM CP-27 FORM CP-27 FORM CP-27 FORM CP-27 AUG 13 1905 FORM CP-27				,	
Other well as hereinefter indicated Plugging Confrector Muffin Drilling Co. License Number 6033 Address 250 North Water, Suite 300, Wichita, KS67202 Company to plug at: Hour: 12:30 pm Day: 3 Month: August Year:19 85 Plugging proposal received from Frank Tsuru (company name) TXO (phone) 303-861-4246 Elevation 3907* were: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 2750* 1st plug at 2750* with 50 sx cement 2nd plug at 1350* with 50 sx cement 3rd plug at -720* with 40 sx cement 4th plug at 480* with 40 sx cement solid bridge 5th plug hulls - plug at 481 ugging Proposal Received by Paul A. Luthi cement to surface with 10 sx cement 7th plug to circulate rat hole with 15 sx & 8th plug to circulate mouse hole with 10 sr Operations Completed: Hour: 2:30 pm Day: 3 Month: August Year:19 85 ACTUAL PLUGGING REPORT 1st plug at 2750* with 50 sx cement, 2nd plug at 1350* with 50 sx cement, 3rd plug at 720* with 40 sx cement, 4th plug at 530* with 40 sx cement, 5th plug & 6th plug - solid bridge - hulls - plug at 40* cement to surface with 10 sx cement 7th plug to circulate rat hole with 15 sx cement, 8th plug to circulate mouseshole with 10 sx cement. Remarks: Used 60/40 Pozmix 6% gel by Hälliburton. (If additional description is necessary, use BACK of this form.) RECEIVED AUG 13 1905 AUG 13 1905 AUG 13 1905 FORM CP-27 AUG 13 1905 FORM CP-27 FORM CP-27 AUG 13 1905 FORM CP-27 FORM CP-27 FORM CP-27 FORM CP-27 AUG 13 1905 FORM CP-27	Abandoned	Oll WellGas W	/e/	Input WellSWD Well D&A	X
Plugging Contrector Muffin Drilling Co. License Number 6033 Address 250 North Water, Suite 300, Wichita, KS67202 Company to plug at: Hour: 12:30 pm Day: 3 Month: August Year:19 85 Plugging proposal received from Frank Tsuru (company name) TXO (phone) 303-861-4246 Elevation 3907 vere: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 2750' 1st plug at 2750' with 50 sx cement 2nd plug at 1350' with 50 sx cement 3rd plug at -720' with 40 sx cement 4th plug at 480' with 40 sx cement solid bridge 5th plug hulls - plug at 48'ugging Proposal Received by Paul A. Luthi cement to surface with 10 sx cement 7th plug to circulate rath bole with 15 sx & 8th plug to circulate mouse hole with 10 sr Operations Completed: Hour: 2:30 pm Day: 3 Month: August Year: 19 85 ACTUAL PLUGGING REPORT 1st plug at 2750' with 50 sx cement, 2nd plug at 1350' with 50 sx cement, 3rd plug at 720' with 40 sx cement, 4th plug at 530' with 40 sx cement, 7th plug to circulate rath hole with 15 sx cement, 8th plug to circulate mouse hole with 10 sx cement. Remarks: Used 60/40 Pozmix 6% gel by Hālīlburton. (If additional description is necessary, use BACK of this form.) Remarks: Used 60/40 Pozmix 6% gel by Hālīlburton. (If additional description is necessary, use BACK of this form.) RECCIVICO AUG 13 1965 FORM CP-27:		•		····	
Address 250 North Water, Suite 300, Wichita, KS67202 Company to plug at: Hour: 12:30 pm Day: 3 Month: August Year:19 85 Plugging proposal received from Frank Tsuru (company name) TXO (phone) 303-861-4246 Elevation 3907' Anhydrite 2750' 1st plug at 2750' with 50 sx cement 2nd plug at 1350' with 50 sx cement 3rd plug at 720' with 40 sx cement 4th plug at 480' with 40 sx cement 5th plug hulls - plug at 48lugging Proposal Received by Paul A. Luthi cement to surface with 10 sx cement 7th plug chirculate rat hole with 15 sx & 8th plug to circulate mouse hole with 10 sy gentless at the deal by Agentless All States Actual Plugging Report less attended by Agentless Actual Plugging Report less attended by Agentless Actual Plugging Report less the plug at 2750' with 50 sx cement, 3rd plug at 720' with 40 sx cement, 4th plug at 530' with 40 sx cement, 5th plug to circulate rat hole with 15 sx cement, 8th plug to circulate mouseshole with 10 sx cement. Remarks: Used 60/40 Pozmix 6% gel by Halliburton. (If additional description is necessary, use BACK of this form.) RECEIVILD AUG 13 1985 COMPANIANO COMMANDAL COMMANDOR COMMANDO					
Company to plug at: Hour: 12:30 pm Day: 3 Month: August Year:19 85 Plugging proposal received from Frank Tsuru (company name) TXO (phone) 303-861-4246 Elevation 3907' were: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 2750' lst plug at 2750' with 50 sx cement 2nd plug at 1350' with 50 sx cement 3rd plug at 720' with 40 sx cement 4th plug at 480' with 40 sx cement 5olid bridge 5th plug hulls - plug at 48'ugging Proposal Received by Paul A. Luthi cement to surface with 10 sx cement 7th plug to cdrculate rat hole with 15 sx & 8th plug to cdrculate mouse hole with 10 square year:19 85 ACTUAL PLUGGING REPORT 1st plug at 2750' with 50 sx cement, 2nd plug at 1350' with 50 sx cement, 3rd plug at 720' with 40 sx cement, 4th plug at 530' with 40 sx cement, 5th plug to circulate rat hole with 15 sx cement, 8th plug to circulate mouseshole with 10 sx cement. Remarks: Used 60/40 Pozmix 6% gel by Hälliburton. (If additional description is necessary, use BACK of this form.) RECEIVED AUG 13 1935 (N.NO. 9 5 99 1 1 1000 CONSENSATION DUMINSON FORM CP-27' SEN CP-17' SEN CP					
Plugging proposal received from Frank Tsuru (company name) TXO (phone) 303-861-4246 Elevation 3907 were: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 2750' 1st plug at 2750' with 50 sx cement 2nd plug at 1350' with 50 sx cement 3rd plug at 720' with 40 sx cement 4th plug at 480' with 40 sx cement solid bridge 5th plug hulls - plug at 48'ugging Proposal Received by Paul A. Luthi cement to surface with 10 sx cement (TECHNICIAN) 7th plug to circulate rat hole with 15 sx & 8th plug to circulate mouse hole with 10 springling Operations attended by Agent; 15 All Operations Completed: Hour: 2:30 pm Dey: 3 Honth: August Yeer:19 85 ACTUAL PLUGGING REPORT 1st plug at 2750' with 50 sx cement, 2nd plug at 1350' with 50 sx cement, 3rd plug at 720' with 40 sx cement, 4th plug at 530' with 40 sx cement, 5th plug to circulate rat hole with 15 sx cement, 8th plug to circulate mouseshole with 10 sx cement. Remarks: Used 60/40 Pozmix 6% gel by Haltiburton. (If additional description is necessary, use BACK of this form.) RECEIVED RECEIVED AUG 13 1985 OC 13 1985 (IECHNICIAN) FORM CP-27: Sevent: CONSERVATION DURSION FORM CP-27: Sevent: CONSERVATION DURSION					·
(company name) TXO (phone) 303-861-4246 Elevation 3907' 1st plug at 2750' with 50 sx cement 2nd plug at 1350' with 50 sx cement 3rd plug at 720' with 40 sx cement 4th plug at 480' with 40 sx cement 5th plug hulls - plug at 480'uging Proposal Received by Paul A. Luthi cement to surface with 10 sx cement 7th plug to circulate rat hole with 10 sx cement Operations Completed: Hour: 2:30 pm Day: 3 Month: August Year:19 85 ACTUAL PLUGGING REPORT 1st plug at 2750' with 50 sx cement, 2nd plug at 1350' with 50 sx cement, 3rd plug at 720' with 40 sx cement, 4th plug at 530' with 40 sx cement, 5th plug to circulate rat hole with 15 sx cement, 8th plug to circulate mousehole with 10 sx cement. Remarks: Used 60/40 Pozmix 6% gel by Halliburton. (If additional description is necessary, use BACK of this form.) RECEIVED ACTUAL PLUGGING REPORT 1st plug at 2750' with 50 sx cement, 8th plug to circulate mouseehole with 10 sx cement. Remarks: Used 60/40 Pozmix 6% gel by Halliburton. (If additional description is necessary, use BACK of this form.) RECEIVED ACTUAL PLUGGING 13 935 RECEIVED ACTUAL PLUGGING 15 Poserve this plugging Proposal Received by Again 1280 (PC-2000) RECEIVED ACTUAL PLUGGING 25 97 ACTUAL PLUGGING 26 97 ACTUAL PLUGGING 27 97 ACTUAL PLUGGING 27 97 ACTUAL PLUGGING 25 97 ACTUAL PLUGGING 27		· ·			
Were: to fill hole with heavy mud and spot cement through drill pipe Elevation 3907	Plugging p				
Separations Completed: Hour: 2:30 pm Day: 3 Month: August Year: 19 85	(company n	ame) TXO		(phone) 303-861-42	46
4th plug at 480' with 40 sx cement solid bridge 5th plug hulls - plug at 48'ugging Proposal Received by Paul A. Luthi cement to surface with 10 sx cement 7th plug to circulate rat hole with 15 sx & 8th plug to circulate mouse hole with 10 specified by Agent?: All All Part None X Operations Completed: Hour: 2:30 pm Day: 3 Month: August Year: 19 85 ACTUAL PLUGGING REPORT 1st plug at 2750' with 50 sx cement, 2nd plug at 1350' with 50 sx cement, 3rd plug at 720' with 40 sx cement, 4th plug at 530' with 40 sx cement, 5th plug to circulate mouse hole with 10 sx cement 8 6th plug - solid bridge - hulls - plug at 40' cement to surface with 10 sx cement 7th plug to circulate rat hole with 15 sx cement, 8th plug to circulate mouse shole with 10 sx cement. Remarks: Used 60/40 Pozmix 6% gel by Halliburton. (If additional description is necessary, use BACK of this form.) RECEIVED AUG 13 1985 OR 13 1985 FORM CP-27. PLANCE 13 1985 CONSERVATION DUNISION FORM CP-27. FORM CP-27.	2nd plu	g at 1350' with 50 sx c	ement		
Solid bridge 5th plug hulls - plug at 40 ugging Proposal Received by Paul A. Luthi cement to surface with 10 sx cement 7th plug to circulate rat hole with 15 sx & 8th plug to circulate mouse hole with 10 spart of the plug of the plug of the plug to circulate mouse hole with 10 spart of the plug of the plug to circulate mouse hole with 10 spart of the plug of the plug to circulate mouse hole with 10 spart of the plug of the plug to circulate mouse hole with 10 spart of the plug of the plug to circulate mouse hole with 50 sx cement, 2nd plug at 1350 with 50 sx cement, 3rd plug at 720 with 40 sx cement, 4th plug at 530 with 40 sx cement, 5th plug to circulate at hole with 15 sx cement to surface with 10 sx cement 7th plug to circulate rat hole with 15 sx cement, 8th plug to circulate mouse hole with 10 sx cement. Remarks: Used 60/40 Pozmix 6% gel by Hälliburton. (If additional description is necessary, use BACK of this form.) RECEIVED AUG 1 3 1985 OR - 13 - 14 - 8 Signed August 1 10000 CONSERVATION DIVISION FORM CP-2/FORM CP-2/FORM DIVISION FORM CP-2/FORM CP-2/FORM CP-2/FORM DIVISION DIVISION FORM CP-2/FORM CP-2/FORM DIVISION DIVISION FORM CP-2/FORM CP-2/FORM DIVISION DIVISION FORM CP-2/FORM CP-2/FORM DIVISION DIVISION	3rd plu	g at .720' with 40 sx c	ement		
Sth plug hulls - plug at 48'ugging Proposal Received by Paul A. Luthi cement to surface with 10 sx cement 7th plug to circulate rat hole with 10 sx & 8 8th plug to circulate mouse hole with 10 sy Agent?: ANI SY & 8th plug to circulate mouse hole with 10 sy Agent?: ANI SY & 8th plug to circulate mouse hole with 10 sy Agent?: ANI SY & 8 8th plug to circulate mouse hole with 10 sy Agent?: ANI SY & 8 8th plug to circulate mouse hole with 10 sy Agent?: ANI SY & 8 8th plug to circulate mouse hole with 50 sx cement, 2nd plug at 1350' with 50 sx cement, 3rd plug at 720' with 40 sx cement, 4th plug at 530' with 40 sx cement, 5th plug & 6th plug - solid bridge - hulls - plug at 40' cement to surface with 10 sx cement 7th plug to circulate rat hole with 15 sx cement, 8th plug to circulate mouse hole with 10 sx cement. Remarks: Used 60/40 Pozmix 6% gel by Halliburton. (If additional description is necessary, use BACK of this form.) RECEIVED AUG 1 3 1985 AUG 1 3 1985 CONSERVATION DIVISION FORM CP-2/ PROVINCE TO THE TOTAL AND SIGNED TO THE TOTAL A	4th plu		ement		
Operations Completed: Hour: 2:30 pm Day: 3 Month: August Year:19 85 ACTUAL PLUGGING REPORT 1st plug at 2750' with 50 sx cement, 2nd plug at 1350' with 50 sx cement, 3rd plug at 720' with 40 sx cement, 4th plug at 530' with 40 sx cement, 5th p. & 6th plug - solid bridge - hulls - plug at 40' cement to surface with 10 sx cement 7th plug to circulate rat hole with 15 sx cement, 8th plug to circulate mouseehole with 10 sx cement. Remarks: Used 60/40 Pozmix 6% gel by Halliburton. (If additional description is necessary, use BACK of this form.) RECEIVED AUG 1 3 1985 OC-1:3-1285 OC-1:3-1285 CONSERVATION DIVISION FORM CP-2/ Rev 01-28	5th plu	g hulls - plug at 40 ug			
Operations Completed: Hour: 2:30 pm Day: 3 Month: August Year:19 85 ACTUAL PLUGGING REPORT 1st plug at 2750' with 50 sx cement, 2nd plug at 1350' with 50 sx cement, 3rd plug at 720' with 40 sx cement, 4th plug at 530' with 40 sx cement, 5th plug - solid bridge - hulls - plug at 40' cement to surface with 10 sx cement 7th plug to circulate rat hole with 15 sx cement, 8th plug to circulate mouseehole with 10 sx cement. Remarks: Used 60/40 Pozmix 6% gel by Halliburton. (If additional description is necessary, use BACK of this form.) RECEIVED AUG 13 1985 AUG 13 1985 FORM CP-2/ CONSERVATION DIVISION FORM CP-2/ REV. 01-10	7th plu				0 s
ACTUAL PLUGGING REPORT 1st plug at 2750' with 50 sx cement, 2nd plug at 1350' with 50 sx cement, 3rd plug at 720' with 40 sx cement, 4th plug at 530' with 40 sx cement, 5th plug at 6th plug - solid bridge - hulls - plug at 40' cement to surface with 10 sx cement 7th plug to circulate rat hole with 15 sx cement, 8th plug to circulate mouseshole with 10 sx cement. Remarks: Used 60/40 Pozmix 6% gel by Hälliburton. (If additional description is necessary, use BACK of this form.) RECEIVED AUG 1 3 1985 OR -13-1985 FORM CP-2/ REVENUES ON SIGNED CONSERVATION DIVISION					
cement, 3rd plug at 720' with 40 sx cement, 4th plug at 530' with 40 sx cement, 5th plug - solid bridge - hulls - plug at 40' cement to surface with 10 sx cement 7th plug to circulate rat hole with 15 sx cement, 8th plug to circulate mouseshole with 10 sx cement. Remarks: Used 60/40 Pozmix 6% gel by HälTiburton. (If additional description is necessary, use BACK of this form.) RECEIVED AUG 1 3 1985 OG-13-1985 FORM CP-2/ CONSERVATION DIVISION FORM CP-2/ REV 0-1-2	•	•	· -		
& 6th plug - solid bridge - hulls - plug at 40' cement to surface with 10 sx cement 7th plug to circulate rat hole with 15 sx cement, 8th plug to circulate mouseehole with 10 sx cement. Remarks: Used 60/40 Pozmix 6% gel by Hälliburton. (If additional description is necessary, use BACK of this form.) RECEIVED AUG 13 1985 AUG 13 1985 FORM CP-2/ CONSERVATION DIVISION FORM CP-2/ Rev 01-8	ACTUAL PLU	GGING REPORT 1st plug a	t 2/50' w	7ith 50 sx cement, 2nd plug at 1350' with 50	sx
7th plug to circulate rat hole with 15 sx cement, 8th plug to circulate mouseehole with 10 sx cement. Remarks: Used 60/40 Pozmix 6% gel by Hälliburton. (If additional description is necessary, use BACK of this form.) RECEIVED AUG 13 1985 AUG 13 1985 FORM CP-2/2	cement,	3rd plug at 720° with	40 sx cem	ment, 4th plug at 530' with 40 sx cement, 5th	p1
with 10 sx cement. Remarks: Used 60/40 Pozmix 6% gel by Halliburton. (If additional description is necessary, use BACK of this form.) RECEIVED SIGNED AUG 1 3 1985 AUG 1 3 1985 FORM CP-2/ CONSERVATION DIVISION FORM CP-2/ REV 01-28	<u>& 6th p</u>	lug – solid bridge – hu	lls - plu	g at 40' cement to surface with 10 sx cem	ent
Remarks: Used 60/40 Pozmix 6% gel by Halliburton. (If additional description is necessary, use BACK of this form.) RECEIVED RECEIVED Signed Signed OR-13-1985 FORM CP-2/- CONSERVATION DIVISION FORM CP-2/- RECEIVED AUG 13 1985 FORM CP-2/- Rev. 01-88	7th plu	g to circulate rat hole	with 15	sx cement, 8th plug to circulate mouseehole	
ATE S-14-85 AUG 1 3 1985 ON-13-1985 FORM CP-2/- CONSERVATION DIVISION FORM CP-2/- CONSERVATION DIVISION FORM CP-2/- RECEIVED AUG 1 3 1985 FORM CP-2/- CONSERVATION DIVISION FORM CP-2/- Rev. 01-28	with 10	sx cement.	· · · · · · · · · · · · · · · · · · ·		
ATE S-14-85 AUG 1 3 1985 ON-13-1985 FORM CP-2/- CONSERVATION DIVISION FORM CP-2/- CONSERVATION DIVISION FORM CP-2/- RECEIVED AUG 1 3 1985 FORM CP-2/- CONSERVATION DIVISION FORM CP-2/- Rev. 01-28	•				
ATE S-14-85 AUG 1 3 1985 ON-13-1985 FORM CP-2/- CONSERVATION DIVISION FORM CP-2/- CONSERVATION DIVISION FORM CP-2/- RECEIVED AUG 1 3 1985 FORM CP-2/- CONSERVATION DIVISION FORM CP-2/- Rev. 01-28	Romanke - Ita	ed 60/40 Posmir 6% col	by Baldas	wirton	
ATE 8-14-85 AUG 1 3 1985 OR-13-1985 FORM CP-2/2 CONSERVATION DIVISION FORM CP-2/2	Nemai KS: US				
ATE 8-14-85 AUG 1 3 1985 OB-13-1985 FORM CP-2/2 CONSERVATION DIVISION FORM CP-2/2	In Warka V a	idnot) poserve this pl	REC	EIVED ATION COMMUSION / W. D	
IV. NO. 9599 OB-13-1985 FORM CP-2/2		K / C	HATE COMPUNE		20
IV. NO. 1 1 1005 CONSERVATION DIVISION	ATE				L
Wichita Kansas		19-83	AUG 1	13 1985 (TECHNICIAN)	1

PRODUCTION S	ering and Sta	NOTICE OF INTE	NTION TO DRILL CARD MUST BE SIGNED
Starting Date:		•••••	API Number 15-071-20,374-00700
Address	O Production 300 Lincoln C	Corp. enter Bldg. 30264	. NW/4 SE/4 SE Sec. 1. Twp. 16. S. Rge. 43. West
Phone	cank Tsuru 303)861-4246 Unknown Unknown	Murfu Dr G	(Note: Locate well on Section Plat on reverse side) Nearest lease or unit boundary line
City/State Well Drilled For:	Well Class:	Type Equipment:	Domestic well within 330 feet : ☐ yes xx no Municipal well within one mile : ☐ yes xx no
S Oil Swd Gas Inj OWWO Expl OWWO old well lafe.	☐ Infield ☐ Pool Ext. ☐ Wildcat is follows:	Mud Rotary ☐ Air Rotary ☐ Cable	Depth to Bottom of fresh water
Well Name Comp Date Erojected Total Depth .	Old Total5300.1		Surface pipe by Alternate: 1 2 2 2 50-475' feet Surface pipe to be set 450-475' feet Conductor pipe if any required None feet Ground surface elevation TBD 3907 feet MSL
Projected Formation at 1 superted Producing Form	nations Morrow.	*****	This Authorization Expires 1.–22–86 Approved By F4A. 7–22–85
• 7_10_85			Hole to K.C. specifications. I Auto Title Drilling & Prod, Enger Form C-1 4/84

RECEIVED
STATE CORPORATION COMMISSION

AUG 1 3 1985