

1 080476

To: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API NUMBER 15- 171-20,319-0060 *R*

NE NE SW, SEC. 23, T 17 S, R 31 *W/XX*
2310 feet from S section line
2970 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5886

Lease Name Sharp "A" Well # 1

Operator: Chief Drilling Co., Inc.

County Scott *150.64*

Name & Address: 151 N. Main, Suite 700

Well Total Depth 4635 Mississippi feet

Wichita, KS 67202

Conductor Pipe: Size _____ feet

Surface Casing: Size 8 5/8 feet 310

Abandoned Oil Well _____ Gas Well _____ Input Well _____ SWD Well _____ D&A _____

Other well as hereinafter indicated _____

Plugging Contractor Warrior Drilling Company License Number 5883

Address 905 Century Plaza, Wichita, KS 67202

Company to plug at: Hour: 2:00 am Day: 26 Month: January Year: 1986

Plugging proposal received from Marion Burris

(company name) Warrior (phone) 316-262-3791
Elevation 2800

were: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 2278-2302

1st plug at 2330' with 50 sx cement

2nd plug at 1500' with 80 sx cement

3rd plug at 530' with 50 sx cement
solid bridge

4th plug hulls - plug at 40' -- cement to surface with 10 sx cement

6th plug to circulate rat hole with 15 sx cement, 7th plug to circulate mouse hole with
10 sx cement. Plugging Proposal Received by J. H. Metz
(TECHNICIAN)

Plugging Operations attended by Agent?: All _____ Part _____ None *x*

Operations Completed: Hour: 4:00 am Day: 26 Month: January Year: 1986

ACTUAL PLUGGING REPORT 1st plug at 2330' with 50 sx cement, 2nd plug at 1500' with 80 sx
cement, 3rd plug at 330' with 50 sx cement, 4th & 5th plugs - solid bridge - hulls -

plug at 40' -- cement to surface with 10 sx cement, 6th plug to circulate rat hole with
15 sx cement, 7th plug to circulate mouse hole with 10 sx cement.

RECEIVED
STATE CORPORATION COMMISSION

JAN 30 1986

Remarks: Used 60/40 Pozmix 6% gel by Allied.
(If additional description is necessary, use BACK of this form.)

INVOICED

(XXXX) did not observe this plugging.

DATE FEB 4 1986

Signed *J. H. Metz*
(TECHNICIAN)

INV. NO. 12259

NOTICE OF INTENTION TO DRILL

(see rules on reverse side)

N

Starting Date 1 24 86 month day year

API Number 15-- 171-20,319-00-00

OPERATOR: License # 5886
Name Chief Drilling Co., Inc.
Address 151 N. Main Suite #700
City/State/Zip Wichita, Ks. 67202
Contact Person Douglas W. Thimesch
Phone 316-262-3791

NE NE SW Sec. 23 Twp. 17. S. Rg. 31. East
2310 Ft. from South Line of Section
2970 Ft. from East Line of Section

(Note: Locate well on Section Plat on reverse side)

CONTRACTOR: License # 5883
Name Warrior Drilling Co. #2
City/State Wichita, Kansas 67202

Nearest lease or unit boundary line 330 feet
County Scott
Lease Name Sharp, "A" Well # 1
Ground surface elevation Will provide feet MSL
Domestic well within 330 feet: yes X no
Municipal well within one mile: yes X no
Surface pipe by Alternate: 1 2 X
Depth to bottom of fresh water 150
Depth to bottom of usable water 1400
Surface pipe planned to be set 300
Projected Total Depth 4700 feet
Formation Miss

Well Drilled For: Well Class: Type Equipment:
X Oil SWD Infield X Mud Rotary
Gas Inj X Pool Ext. Air Rotary
OWWO Expl Wildcat Cable

If OWWO: old well info as follows:

Operator
Well Name
Comp Date Old Total Depth

I certify that well will comply with K.S.A. 55-101, et seq., plus eventually plugging hole to KCC specifications.

cementing will be done immediately upon setting production casing.

Date 1-14-86 Signature of Operator or Agent Douglas W. Thimesch Title Vice President

For KCC Use:

Conductor Pipe Required feet; Minimum Surface Pipe Required 250 feet per Alt. X 2

This Authorization Expires 7-15-86 Approved By 1-15-86

300' 8 5/8 1-17-85

PLUGGING PROPOSAL IF ABOVE IS D & A

This plugging proposal will be reviewed and approved or revised at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).

Table with 3 columns: Plug description (e.g., 1st plug @ 2330), Depth (feet), and Material/Quantity (e.g., 60-40 posmix 6% gc 13% cc).

Vertical list of well parameters: PUSHER, TD, SURFACE PIPE, ANHYDRITE, STARTING TIME & DATE, COMPLETION TIME & DATE, 1st PLUG @, 2nd PLUG @, 3rd PLUG @, 4th PLUG @, RAT HOLE CIRCULATED W/, MOUSE HOLE CIRCULATED W/, WATER WELL PLUGGED W/.

TECHNICIAN, CEMENT COMPANY, RECEIVED, STATE CORPORATION COMMISSION, JAN 30 1986, CONSERVATION DIVISION, and handwritten notes: 30 505, 00 805, 30 505, 110 105, 15' Rotherd, 10' mearns, 60/40 67 gal.