1-1080180

TO:

RECERVINEMBER 15-203-20,054 -00 -00

STATE CORPORATION DIVISION

ANSAS CONVUISEC. 25 ,T 20 S, R 38 W

CONSERVATION DIVISION - PLUGGING SECTION 13960 FEET FROM SOUTH SECTION LINE

WICHITA STATE OFFICE BUILDING 3960 FEET FROM EAST SECTION LINE

130 S. MARKET, WICHITA, KS 67202 LEASE NAME: COLLINGWOOD ESTATE WELL # 2

TECHNICIAN'S PLUGGING REPORT COUNTY: WICHITA

OPERATOR LICENSE NUMBER: 100 WELL TOTAL DEPTH: 3383 FEET

OPERATOR: KCC PRODUCTION CSG - SIZE: 5 1/2 FEET 3300

NAME AND 304 WEST MCARTOR SURFACE CASING - SIZE: 8 5/8 FEET 408

ADDRESS: **DODGE CITY, KS 67801** CONDUCTOR PIPE - SIZE: FEET

ABANDONED - OIL WELL GAS WELL X INPUT WELL SWD WELL D/A

OTHER WELL AS HEREINAFTER INDICATED:

PLUGGING CONTRACTOR: ALLIED CEMENTING LICENSE NUMBER:

ADDRESS: BOX 628, GREAT BEND, KS 67530

COMPANY TO PLUG AT - HOUR: 9:30AM DATE: 3-3-98

PLUGGING PROPOSAL RECEIVED FROM: Kevin Strube

COMPANY NAME: KCC PHONE NUMBER: 316-225-8888

WERE: pump 300 lbs of hulls, fill 5 1/2" casing with cement, pressure test 8 5/8" x 5 1/2" annulas with

cement

PLUGGING REPORT RECEIVED BY: Kevin Strube, Technician

PLUGGING OPERATION ATTENDED BY AGENT?: ALL X PART NONE

OPERATIONS COMPLETED - HOUR: 11:30am DATE: 3-3-98

ACTUAL PLUGGING REPORT: 1st plug pumped 100 lbs hulls with 200 lbs hulls mixed in cement, total of 220 sx, max pressure 800 psi and shut in at 500 psi. Tied on to 8 5/8" x 5 1/2" annulas and pumped 1 barrel cement - 500 psi.

REMARKS: Used 60/40 Pozmix 6% gel by Allied. No casing recovery.

I (DID / XXXXXXX) OBSERVE THIS PLUGGING.

recunician