

6-10

1

API NUMBER 15- 203-01,001-00-01

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

NW NW NE, SEC. 22, T 20 S, R 36 W/E  
4950 feet from S section line

TECHNICIAN'S PLUGGING REPORT

2310 feet from E section line

Operator License # 5506

Lease Name B.F. Smith Well # 1 OWWO

Operator: Woolsey Petroleum Corporation  
Name & Address 107 N. Market, Ste. 600

County Wichita

Wichita, KS 67202-1807

Well Total Depth 5126 164,60 feet

Conductor Pipe: Size feet

Surface Casing: Size 8 5/8 feet 282

Abandoned Oil Well  Gas Well  Input Well  SMD Well  D&A

Other well as hereinafter indicated

Plugging Contractor Mike's Testing & Salvage Inc. License Number 31529

Address P.O. Box 209, Chase, KS 67524

Company to plug at: Hour: 8 a.m. Day: 10 Month: 6 Year: 1995

Plugging proposal received from Richard McIntyre

(company name) Mike's Testing & Salvage Inc. (phone) 316-938-2943

were: 5 1/2" at 5116' w/240 sx cement, TOC 4110', Perfs at 4979-86, 4592-4608, 4407-12, 4414-25  
CIBP at 4950' & 4540', PBSD 5051'

1st plug pump 80 sx cement at 1150', 2nd plug pump 30 sx cement at 600',

3rd plug pump 50 sx cement at 320', 4th plug pump 10 sx cement at 40'. Gel spacers.

Plugging Proposal Received by Steve Middleton (TECHNICIAN)

Plugging Operations attended by Agent?: All  Part  None

Operations Completed: Hour: 10 a.m. Day: 10 Month: 6 Year: 1995

ACTUAL PLUGGING REPORT

1st plug pumped 10 sx gel and 80 sx cement, then 6 sx gel at 1200',

2nd plug pumped 40 sx cement at 600',

3rd plug pumped 50 sx cement at 300',

4th plug pumped 10 sx cement to surface.

Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 1253' of 5 1/2" casing.  
(If additional description is necessary, use BACK of this form.)

Observe this plugging.

DATE 6-29-95

Signed [Signature] (TECHNICIAN)

REV. NO. 43001

STATE CORPORATION COMMISSION  
JUN 25 1995  
06-15-1995