

1 110063

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15- 171-20,356 -00-00  
SE SE, SEC. 26, T 17 S, R 31 W/~~X~~  
670 feet from S section line  
710 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5181

Lease Name French "J" Well # 1

Operator: Slawson, Donald C.  
Name &  
Address 200 Douglas Building  
Wichita, KS 67202

County Scott 149.47  
Well Total Depth 4599 feet  
Conductor Pipe: Size \_\_\_\_\_ feet  
Surface Casing: Size 8 5/8 feet 320

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A X

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Slawson Drilling Company License Number 5657

Address 200 Douglas Building, 104 South Broadway, Wichita, KS 67202

Company to plug at: Hour: 11 a.m. Day: 4 Month: 7 Year: 19 87

Plugging proposal received from Bob Rowe

(company name) Slawson Drilling Company (phone) 316-793-3561

were: to fill hole with heavy mud and spot cement through drill pipe Elevation 2912'  
Anhydrite 2278-98'

1st plug at Base Anhydrite with 50 sx cement, 2nd plug at 1/2 Anhydrite plus 300' with  
75 sx cement, 3rd plug at base of surface pipe plus 30' with 40 sx cement,  
4th plug at 40' with 10 sx cement, 5th plug to circulate rathole with 15 sx cement.

Plugging Proposal Received by James R. Kapp  
(TECHNICIAN)

Plugging Operations attended by Agent?: All \_\_\_\_\_ Part \_\_\_\_\_ None X

Operations Completed: Hour: 1:15 p.m. Day: 4 Month: 7 Year: 19 87

ACTUAL PLUGGING REPORT 1st plug at 2280' with 50 sx cement,

2nd plug at 1450' with 75 sx cement,

3rd plug at 350' with 40 sx cement,

4th plug at 40' with 10 sx cement,

5th plug to circulate rathole with 15 sx cement.

RECEIVED  
STATE CORPORATION COMMISSION

JUL 7 1987  
07-07-87  
CONSERVATION DIVISION  
Wichita Kansas

Remarks: Used 60/40 Pozmix 6% gel by Allied.

(If additional description is necessary, use BACK of this form.)

**INVOICED**  
I (did / did not) observe this plugging.

DATE 7-7-87

Signed James R. Kapp  
(TECHNICIAN)

INV. NO. 17440  
7-4

NOTICE OF INTENTION TO DRILL

(see rules on reverse side)

Expected Spud Date. June 22 1987 month day year

API Number 15- 171-20,356-0000 2 SE SE Sec. 26 Twp. 17 S, Rg. 31 X West 670' Ft. from South Line of Section 710' Ft. from East Line of Section

OPERATOR: License # 5181 Name SLAWSON, DONALD C. Address 200 Douglas Building City/State/Zip Wichita, Kansas 67202 Contact Person Bill Horigan Phone (316) 263-3201

(Note: Locate well on Section Plat on reverse side) Nearest lease or unit boundary line 660' feet County Scott

CONTRACTOR: License # 5657 Name SLAWSON Drlg. Co. City/State Wichita, KANSAS

Lease Name FRENCH, J' Well # 1 Ground surface elevation 2911' GR. (Sea) feet MSL Domestic well within 330 feet: yes no

Well Drilled For: Well Class: Type Equipment: X Oil Storage Infield X Mud Rotary Gas Inj Pool Ext Air Rotary OWWO Expl X Wildcat Cable

Municipal well within one mile: yes no Depth to bottom of fresh water 200' Depth to bottom of usable water 1300' 1450'

If OWWO: old well info as follows: Operator Well Name Comp Date Old Total Depth

Surface pipe by Alternate: 1-2 X Surface pipe planned to be set 320' Conductor pipe required Projected Total Depth 4600' feet Formation Mississippian

I certify that well will comply with K.S.A. 55-101, et seq., plus eventually plugging hole to KCC specifications. Western Kansas Date 6/15/87 Signature of Operator or Agent Robert B. Jenkins Title District Geologist

For KCC Use: Conductor Pipe Required feet; Minimum Surface Pipe Required 225 feet per Alt. 98 This Authorization Expires 12-15-87 Approved By 6-15-87

dict Spud 6-25-87 4:00PM 320' 8 5/8

Signature

haul water

SE SE Sec. 26 Twp. 17 S, Rg. 31 X West

PLUGGING PROPOSAL IF ABOVE IS D & A

This plugging proposal will be reviewed and approved or revised at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).

1st plug @ ft. deep 2250' or formation with 60 feet of 60/40 Poz. w/6% Gel 2nd plug @ ft. deep 1450' or formation with 75 feet of 60/40 Poz. w/6% Gel 3rd plug @ ft. deep 360' or formation with 40 feet of 60/40 Poz. w/6% Gel 4th plug @ ft. deep 40 or formation with 10 feet of 60/40 Poz. w/6% Gel 5th plug @ ft. deep or formation with feet of

(2) Rathole to surface minus 5 feet 168x (b) Mousehole to surface minus 5 feet

Table with columns: PUSHER (Bob Rowe), TD (4599), SURFACE PIPE (8 5/8 @ 520), ANHYDRITE (2278-98 ELEVATION 5912), STARTING TIME & DATE (11 AM 7-4), COMPLETION TIME & DATE (1:15 PM 7-4), 1st PLUG @ (2280 FT. W/ 50 SX), 2nd PLUG @ (1450 FT. W/ 75 SX), 3rd PLUG @ (350 FT. W/ 40 SX), 4th PLUG @ (40 FT. W/ 10 SX), RAT HOLE CIRCULATED W/ (15 SX), MOUSE HOLE CIRCULATED W/ (SX), WATER WELL PLUGGED W/ (SX), CEMENT COMPANY Allied 60/40 Poz 6% (SX), TECHNICIAN

RECEIVED STATE CORPORATION COMMISSION JUL 7 1987 CONSERVATION DIVISION Wichita, Kansas