

1 0 0 2 6 8

4280

4293

API NUMBER 15-203-20,053 - 00-00

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

C, SEC. 28, T 20 S, R 38 W/E  
2640 feet from ~~XXXX~~ SE Corner of section line  
2640 feet from ~~XXXX~~ SE Corner of section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 6506

Lease Name Collingwood Well # 1

Operator: Intercep Resources, Inc.

County Wichita

Name:

Address ~~5680 South Sycamore Circle, 418 So. Englewood, CO 80111~~

Well Total Depth 3258 105.89 feet

1104 Camino Del Mar  
Del Mar, Calif

Conductor Pipe: Size \_\_\_\_\_ feet

Surface Casing: Size 8 5/8 feet 320

Abandoned Oil Well \_\_\_\_\_ Gas Well  Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A \_\_\_\_\_

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Halliburton Services License Number 5287

Address Box 1598, Liberal, KS 67901

Company to plug at: Hour: 8:00 am Day: 23 Month: July Year: 19 84

Plugging proposal received from Lloyd Cooper

(company name) Intercep Resources, Inc. (phone) 316-276-6914

were: 5 1/2" set at 3200' Perfs at 3026-3098'

Pump 2 sx hulls, 25 sx cement, 10 sx gel, 50 sx cement, 5 sx gel and 100 sx cement

Clyde Wiley witnessed the plugging operations

Plugging Proposal Received by Steve Dumont  
(TECHNICIAN)

Plugging Operations attended by Agent?: All  Part \_\_\_\_\_ None \_\_\_\_\_

Operations Completed: Hour: 10:00 am Day: 23 Month: July Year: 19 84

ACTUAL PLUGGING REPORT 5 1/2" set at 3200' Perfs at 3026-3098'

Pumped 2 sx hulls, 25 sx cement, 10 sx gel, 50 sx cement, 5 sx gel and 100 sx cement

RECEIVED  
STATE CORPORATION COMMISSION

SEP 17 1984

Remarks: Used 60/40 Pozmix 2% gel 3% cc by Halliburton  
(if additional description is necessary, use BACK of this report)  
CONSERVATION DIVISION  
Wichita, Kansas

Signed Steve Dumont  
(TECHNICIAN)

INVOICED

DATE 9-21-84

INV. NO. 3238

7-23 OCT 02 1984

FORM CP-2/3  
Rev. 01-84