

To: 1 110029
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API NUMBER 15- 071-20,419-00-00
W/2 SW SW, SEC. 14, T 19 S, R 43 W/EX

TECHNICIAN'S PLUGGING REPORT

Operator License # 4868
Operator: Asher Associates, Inc.
Name & Address: 5660 S. Syracuse Circle, # 216
Englewood, CO 80111

660 feet from S section line
4950 feet from E section line
Lease Name Pawax Well # 1
County Greeley 181.35
Well Total Depth 5580 Mississippi feet
Conductor Pipe: Size feet
Surface Casing: Size 8 5/8 feet 537

Abandoned Oil Well Gas Well Input Well SWD Well D&A X

Other well as hereinafter indicated

Plugging Contractor Abercrombie Drilling, Inc. License Number 5422

Address 801 Union Center, Wichita, KS 67202

Company to plug at: Hour: 11:00 pm Day: - 15 Month: March Year: 19 86

Plugging proposal received from Bill Craig

(company name) Abercrombie (phone) 316-262-1841
Elevation 3873'

were: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 2483-2511'

1st plug at the base of the Anhydrite with 50 sx cement

2nd plug at the base of the Cheyenne with 80 sx cement

3rd plug 30' below the base of the surface pipe with 50 sx cement
solid bridge

4th plug hulls - plug at 40' -- cement to surface with 10 sx cement.

6th plug to circulate rat hole with 15 sx cement, 7th plug to circulate mouse hole with 10 sx cement
Plugging Proposal Received by Paul A. Luthi (TECHNICIAN)

Plugging Operations attended by Agent?: All Part None X

Operations Completed: Hour: 4:15 am Day: 16 Month: March Year: 19 86

ACTUAL PLUGGING REPORT 1st plug at 2511' with 50 sx cement, 2nd plug at 1550' with 80 sx cement, 3rd plug at 565' with 50 sx cement, 4th & 5th plugs - solid bridge - hulls - plug at 40' -- cement to surface with 10 sx cement, 6th plug to circulate rat hole with 15 sx cement, 7th plug to circulate mouse hole with 10 sx cement.

STATE CORPORATION COMMISSION
MAR 20 1986
03-20-86
CONSERVATION DIVISION
Wichita, Kansas

Remarks: Used 60/40 Pozmix 6% gel by Allied.
(if additional description is necessary, use BACK of this form.)

INVOICED

DATE MAR 20 1986
INV. NO. 13014
3-16

Signed James P. [Signature]
(TECHNICIAN)

NOTICE OF INTENTION TO DRILL

(see rules on reverse side)

Starting Date 3-4-86 month day year 1986

API Number 15-071-20,419-00-00
660' FSL East
W/ SW/4 Sec. 14 Twp. 19 S, Rg. 43 X West
660' Ft. from South Line of Section
4950' Ft. from East Line of Section

OPERATOR: License # 4868
Name Asher Associates, Inc.
Address 5660' S. Syracuse Circle, #216
City/State/Zip Englewood, CO 80111
Contact Person Harold Patton
Phone 303-770-4100

(Note: Locate well on Section Plat on reverse side)
Nearest lease or unit boundary line 330 feet
County Greeley

CONTRACTOR: License # 5422
Name Abercrombie Drilling, Inc.
City/State Wichita, KS

Lease Name Pawax Well # 1
Ground surface elevation feet MSL

Well Drilled For: Well Class: Type Equipment:
X Oil SWD Infield X Mud Rotary
Gas Inj Pool Ext Air Rotary
OWWO Expl X Wildcat Cable

Domestic well within 330 feet: yes X no
Municipal well within one mile: yes X no
Depth to bottom of fresh water 260'
Depth to bottom of usable water 1775'

If OWWO: old well info as follows:
Operator
Well Name
Comp Date Old Total Depth

Surface pipe by Alternate: 1 2 X
Surface pipe planned to be set 500'
Conductor pipe required None
Projected Total Depth 5400' feet
Formation Mississippian

I certify that well will comply with K.S.A. 55-101, et seq., plus eventually plugging hold to KCC specifications.
Date 3-3-86 Signature of Operator or Agent Jack L. Partridge Title V.P. Abercrombie Drilling

For KCC Use:
Conductor Pipe Required feet; Minimum Surface Pipe Required feet per Alt 2
This Authorization Expires 9-3-86 Approved By [Signature]

660' FSL East
330' FWL SW/4 Sec. 14 Twp. 19 S, Rg. 43 X West

PLUGGING PROPOSAL IF ABOVE IS D & A

This plugging proposal will be reviewed and approved or revised at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).

1st plug @ Base of Anhydrite 2877' feet depth with 50 SXS of 60-40 posmix (6% gel)
2nd plug @ B/Cheyenne-Dakota 1550' feet depth with 80 SXS of 60-40 posmix (6% gel)
3rd plug @ 30' below surface casing 565' feet depth with 50 SXS of 60-40 posmix (6% gel)
4th plug @ Top 40' feet depth with 10 SXS of 60-40 posmix (6% gel)
5th plug @ feet depth with SXS of
(2) Rathole with 15 SXS (b) Mousehole with 10 SXS

PUSHER Bill Craig
TD 5580 FORMATION
SURFACE PIPE 8 3/8" @ 5371'
ANHYDRITE 2511' ELEVATION 3873
STARTING TIME & DATE 3-16-86 11:00 PM
COMPLETION TIME & DATE 3-16-86 4:15 AM
1st PLUG @ 2511 FT. W/ 50 SX
2nd PLUG @ 1550 FT. W/ 80 SX
3rd PLUG @ 565 FT. W/ 50 SX
4th PLUG @ 40-0 SB FT. W/ 10 SX
RAT HOLE CIRCULATED W/ 15 SX
MOUSE HOLE CIRCULATED W/ 10 SX
WATER WELL PLUGGED W/
CEMENT COMPANY Allied
TECHNICIAN Dick Rapp allied

STATE CONSERVATION COMMISSION
MAR 20 1986
CONSERVATION DIVISION
Wichita, Kansas