To: STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING SECTION 200 COLORADO DERBY BUILDING WICHITA, KANSAS 67202	API NUMBER 15-171 -20,242-00-00 100' SW/C- NW/4 , Sec. 2 , T 19 S, R 31 W/K feet from N/S section line
TECHNICIAN'S PLUGGING REPORT	feet from W/E section line
Operator License # 5393	Lease Name Steinberg Twin Well # 1
Operator: A. L. Abercrombie, Inc. Name & 801 Union Center	County Scott
Address Wichita, KS 67202	Well Total Depth 4500 feet
	Conductor Pipe: Sizefeet
,	Surface Casing: Size 8 5/8 feet 360
Abandoned Oil Well X Gas Well Inp	ut Well SWD Well D&A
Other well as hereinafter indicated .	
Plugging Contractor A. L. Abercrombie, Inc.	License Number 5393
Address Rt. 1, Box 56, Great Bend, KS 6	7530
Company to plug at: Hour: 7:00 am Day: 1	7 Month: February Year:19 84
VERBAL PLUGGING ORDERS GIVEN TO Kevin Wiley	
(company name) A. L. Abercrombie, Inc. (phone) 316-793-8186	
were: 5 1/2 set at 4498 Perfs at 438	
Circulate coment to surface	
Top plug pump 2 sx hulls, 30 sx cement, 20 sx gel, 50 sx cement, 5 sx gel and 1 sack hulls and pump an additional 125 sx cement. Maximum pressure 100# and shut in pressure 0	
	Signed Stew Suuront (TECHNICIAN)
Plugging Operations attended by Agent?: All	X Part None
Operations Completed: Hour: 9:35 am Day:	
ACTUAL PLUGGING REPORT 5 1/2 set at 4498' P	
and the second s	
DV Tool at 1513' Circulate cement to surf 20 sx gel, 50 sx cement, 5 sx gel, 1 sack	ace Top plug pump 2 sx hulls, 30sx cement, hulls and pump an additional 125 sx cement.
DV Tool at 1513' Circulate cement to surf 20 sx gel, 50 sx cement, 5 sx gel, 1 sack Maximum pressure 100# and shut in pressure	ace Top plug pump 2 sx hulls, 30sx cement, hulls and pump an additional 125 sx cement.
DV Tool at 1513' Circulate cement to surf 20 sx gel, 50 sx cement, 5 sx gel, 1 sack Maximum pressure 100# and shut in pressure	ace Top plug pump 2 sx hulls, 30sx cement, hulls and pump an additional 125 sx cement.
DV Tool at 1513' Circulate cement to surf 20 sx gel, 50 sx cement, 5 sx gel, 1 sack Maximum pressure 100# and shut in pressure	ace Top plug pump 2 sx hulls, 30sx cement, hulls and pump an additional 125 sx cement.

I hereby certify that the above plugging instructions were given as herein stated and that I (did / \$333,0000) observe this plugging.

STATE CORPORATION COMMISSION

MAR 2 8 1984

CONSERVATION DIVISION

Signed Stew Runnit
(TECHNICIAN)

FORM CP-2/3 Rev. 9-82