

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15- 171- 20,227-00-00

C NW , Sec. 2 , T 19 S, R 31 W 1/4

\_\_\_\_\_ feet from N/S section line

\_\_\_\_\_ feet from W/E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5393

Lease Name Steinberg Well # SWD 1

Operator: A. L. Abercrombie, Inc.  
Name & 801 Union Center  
Address Wichita, KS 67202

County Scott

Well Total Depth 4650 feet

Conductor Pipe: Size \_\_\_\_\_ feet

Surface Casing: Size 8 5/8 feet 324

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well X D&A \_\_\_\_\_

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor A. L. Abercrombie, Inc. License Number 5393

Address Rt. 1, Box 56, Great Bend, KS 67530

Company to plug at: Hour: 8:00 am Day: 17 Month: February Year: 19 84

VERBAL PLUGGING ORDERS GIVEN TO Kevin Wiley

(company name) A. L. Abercrombie, Inc. (phone) 316-793-8186

were: 4 1/2 set at 4406 PBTD 2160' Perfs 1890 to 1940

Circulate cement to surface

Top plug pump 1 sack hulls, 20 sx cement, 5 sx gel and 100 sx cement

Maximum pressure 0 shut in pressure 0

Signed Steve [Signature]  
(TECHNICIAN)

Plugging Operations attended by Agent?: All X Part \_\_\_\_\_ None \_\_\_\_\_

Operations Completed: Hour: 10:15 am Day: 17 Month: February Year: 19 84

ACTUAL PLUGGING REPORT 4 1/2 set at 4406 PBTD 2160' Perfs 1890 to 1940

Circulate cement to surface

Top plug pump 1 sack hulls, 20 sx cement, 5 sx gel and 100 sx cement

Maximum pressure 0 and shut in pressure 0

Remarks: Use 60/40 Pozmix 2% gel 3% cc by Sun Cementing

I hereby certify that the above plugging instructions were given as herein stated and that I (did / ~~did not~~) observe this plugging.

RECEIVED  
STATE CORPORATION COMMISSION  
MAR 28 1984  
CONSERVATION DIVISION  
Wichita, Kansas

Signed Steve [Signature]  
(TECHNICIAN)