

1060843

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15- 171-20,327 -00-00  
C NE SW, SEC. 5, T 19 S, R 33 W XX  
1980 feet from S section line  
3300 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5692  
Operator: Fina Oil & Chemical Company  
Name & Address: 1601 NW Expressway, Suite 900  
Oklahoma City, OK 73118

Lease Name Tindall Well # 1  
County Scott 156.88  
Well Total Depth 4827 Mississippi feet  
Conductor Pipe: Size feet  
Surface Casing: Size 8 5/8 feet 343

Abandoned Oil Well Gas Well Input Well SWD Well D&A X

Other well as hereinafter indicated

Plugging Contractor Red Tiger Drilling Company License Number 5302

Address 1720 Kansas State Bank Building, Wichita, KS 67202

Company to plug at: Hour: 12:45 am Day: 2 Month: April Year: 19 86

Plugging proposal received from Mike Waggoner

(company name) Red Tiger (phone) 316-263-1201

were: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 2283-2318' Elevation 2977'

1st plug at 2250' with 50 sx cement

2nd plug at 1600' with 80 sx cement

3rd plug at 380' with 40 sx cement solid bridge

4th plug hulls - plug at 40' -- cement to surface with 10 sx cement

6th plug to circulate rat hole with 15 sx cement

Plugging Proposal Received by Robert B. Tarbutton (TECHNICIAN)

Plugging Operations attended by Agent?: All Part None X

Operations Completed: Hour: 4:20 am Day: 2 Month: April Year: 19 86

ACTUAL PLUGGING REPORT 1st plug at 2250' with 50 sx cement, 2nd plug at 1600' with 80 sx cement, 3rd plug at 380' with 20 sx cement, 4th & 5th plugs - solid bridge - hulls - plug at 40' -- cement to surface with 10 sx cement.

APR 7 1986

Remarks: Used 60/40 Pozmix 6% gel by Allied.  
(If additional description is necessary, use BACK of this form.)

CONSERVATION DIVISION  
Wichita, Kansas

INVOICED (If you did not observe this plugging.)

Signed Paul A. Tarbutton (TECHNICIAN)

DATE APR 7 1986

INV. NO. 13300

4-2

NOTICE OF INTENTION TO DRILL

CARD MUST BE SIGNED

(see rules on reverse side)

Starting Date 3/20/86  
month day year

API Number 15- 171-20,327-00-00

OPERATOR: License # 5692  
Name FINA OIL & CHEMICAL COMPANY  
Address 1601 N.W. Expressway, Ste 900  
City/State/Zip Okla. Oklahoma City, OK 73118  
Contact Person Joe Springer  
Phone (405) 840-0671

C NE SW Sec. 5 Twp. 19 S, Rg. 33 East  
1980 Ft. from South Line of Section  
3300 Ft. from East Line of Section

(Note: Locate well on Section Plat on reverse side)

CONTRACTOR: License # Unknown Red Tiger  
Name  
City/State

Nearest lease or unit boundary line 1980 feet  
County Scott

Well Drilled For: Well Class: Type Equipment:  
 Oil  SWD  Infield  Mud Rotary  
 Gas  Inj  Pool Ext.  Air Rotary  
 OWWO  Expl  Wildcat  Cable

Lease Name TINDALL Well # 1  
Ground surface elevation 2977' KB feet MSL  
Domestic well within 330 feet:  yes  no  
Municipal well within one mile:  yes  no

If OWWO: old well info as follows:

Depth to bottom of fresh water 200'  
Depth to bottom of usable water 1150' 1350' 1450'  
Surface pipe by Alternate: 1-2   
Surface pipe planned to be set 350'  
Conductor pipe required  
Projected Total Depth 4800' feet  
Formation Mississippi

Operator  
Well Name  
Comp Date Old Total Depth

I certify that well will comply with K.S.A. 55-101, et seq., plus eventually plugging hole to KCC specifications.  
Date 3/18/86 Signature of Operator or Agent Raylene Smith Title Production Tech.

For KCC Use:

Conductor Pipe Required 220 feet; Minimum Surface Pipe Required 220 feet per Alt. 20  
This Authorization Expires 7-19-86 Approved By 3-19-86 Raylene Smith

350'-8 5/8"  
made in 3-22-86

C NE SW Sec. 5 Twp. 19 S, Rg. 33 East  
X West

PLUGGING PROPOSAL IF ABOVE IS D & A

This plugging proposal will be reviewed and approved or revised at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).

1st plug @ <u>2250</u>	feet depth with	<u>50</u>	sxs of <u>60/40 Poz. 6% gel</u>
2nd plug @ <u>1600</u>	feet depth with	<u>80</u>	sxs of <u>60/40 Poz.</u>
3rd plug @ <u>380</u>	feet depth with	<u>40</u>	sxs of <u>60/40 Poz.</u>
4th plug @ <u>40</u>	feet depth with	<u>10</u>	sxs of <u>60/40 Poz.</u>
5th plug @ <u>15</u>	feet depth with		sxs of
(2) Rathole with <u>15</u>	sxs		Mousehole with <u>10</u> sxs

PUSHER Mike Wagner  
TD 4827 FORMATION Mist  
SURFACE PIPE 8 5/8" @ 343  
2283 ELEVATION 2977  
ANHYDRITE 2318  
STARTING TIME & DATE 4-2-86 12:45  
COMPLETION TIME & DATE 4-2-86 4:20 AM  
1st PLUG @ 2250 FT. W/ 50 SX  
2nd PLUG @ 1600 FT. W/ 80 SX  
3rd PLUG @ 380 FT. W/ 20 SX  
4th PLUG @ 40 FT. W/ 10 SX  
RAT HOLE CIRCULATED W/ 15' SX  
MOUSE HOLE CIRCULATED W/ SX  
WATER WELL PLUGGED W/ SX  
CEMENT COMPANY Called 60/40 w/ 6%  
TECHNICIAN Raylene Smith

STATE OF KANSAS COMMISSION  
APR - 7 1986  
CONSERVATION DIVISION  
Wichita, Kansas