

STATE CORPORATION COMMISSION

CONSERVATION DIVISION AGENT REPORT

171

API Number 15-174-20,231-00-00

200 Colorado Derby Building  
Wichita, KS 67202

Operator's Full Name Stelbar Oil Corporation Inc

Complete Address 450 Smith Financial Center, Wichita, Kansas 67202

Lease Name Musa Well No. #1

Location C-NE-NW Sec. 36 Twp. 17 Rge. 32 (East)(West)

County Scott Total Depth 4650 <sup>ft.</sup>

Abandoned Oil Well  Gas Well  Input Well  SWD Well  D&A

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Slawson Drilling Inc. (Glen Conway)

Address 200 Douglas Broadway, Douglas, Wichita, Kansas 67202 License No. \_\_\_\_\_

Operation Completed: Hour: 3:30 PM Day: 10<sup>th</sup> Month: April Year: 19 82

Plugging Operations attended by Agent?: All  Part  None

The above well was plugged as follows:

8 5/8" - 345' <sup>ft</sup> SR. core <sup>m</sup>/200 <sup>ft</sup> 60/40 Formin - 2% Gel. - 3% Ca-Cl.  
Order 140' <sup>ft</sup> 50/50 Formin 4% Gel. - 3% Ca-Cl. + 8 5/8" plug.  
spot with Drill Stem - with heavy mud between all plugs  
1<sup>st</sup> Plug @ 1440' <sup>ft</sup> <sup>m</sup>/80' <sup>ft</sup> out.  
2<sup>nd</sup> Plug @ 330' <sup>ft</sup> <sup>m</sup>/40' <sup>ft</sup> out.  
3<sup>rd</sup> Plug → solid bridge plugs - Plug @ 40' <sup>ft</sup> to <sup>m</sup>/10' <sup>ft</sup> out.  
10' <sup>ft</sup> In Port Hole (circulate)

Completed By Allied Int.

RECEIVED  
STATE CORPORATION COMMISSION

I hereby certify APR 13 1982 the above plugging instructions were given as herein stated.

CONSERVATION DIVISION  
Wichita, Kansas  
04-13-1982

Signed: [Signature]  
Conservation Division Agent