

TO:  
STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGIN  
130 SOUTH MARKET, SUITE 2078  
WICHITA, KANSAS 67202

API Well Number: 15-003-20787-00-00  
Spot: SENESESW Sec/Twnshp/Rge: 3-22S-19E  
2039 feet from S Section Line, 2848 feet from E Section Line  
Lease Name: BUCHANAN Well #: 378  
County: ANDERSON Total Vertical Depth: 841 feet

Operator License No.: 33097  
Op Name: SOUTHERN STAR CENTRAL GAS PIPE  
Address: 4700 HWY 56  
OWENSBORO, KY 42301

| String | Size | Depth (ft) | Pulled (ft) | Comments |
|--------|------|------------|-------------|----------|
| SURF   | 7    | 8          |             |          |
| PROD   | 2.5  | 841        |             |          |

Well Type: OIL UIC Docket No: \_\_\_\_\_ Date/Time to Plug: 11/03/2011 12:00 PM  
Plug Co. License No.: 33749 Plug Co. Name: KEPLEY WELL SERVICE, LLC  
Proposal Rcvd. from: STERLING BARKER Company: SOUTHERN STAR Phone: (785) 448-4816

Proposed Plugging Method: Run work string to bottom, cement to surface, and squeeze cement until desired pressure is achieved. Cut off pipe 3' below surface, cap, and backfill.

Plugging Proposal Received By: JOHN ALMOND WitnessType: NONE  
Date/Time Plugging Completed: 11/03/2011 12:00 PM KCC Agent: JOHN ALMOND

Actual Plugging Report:

Contractor ran work string to TD, circulated portland cement to surface, pulled pipe out, topped off well, hooked up to casing and squeezed cement into well, shut in at 350 psi, used 204 sacks cement.

Perfs:

| Top | Bot | Thru | Comments |
|-----|-----|------|----------|
| 817 | 827 |      |          |

RECEIVED  
JAN 20 2012

RECEIVED

JAN 13 2012 JA

KCC Chanute Dist. #3

Remarks: I CALLED SOUTHERN STAR TO VERIFY THE AMOUNT OF CEMENT USED ON THIS WELL. STERLING BARKER INDICATED THAT 204 SACKS WAS THE CORRECT AMOUNT. KCC WICHITA

Plugged through: TBG

District: 03

Signed

  
(TECHNICIAN)

✓ 1/25/12