

KANSAS CORPORATION COMMISSION OIL & GAS CONSERVATION DIVISION

WELL COMPLETION FORM WELL HISTORY - DESCRIPTION OF WELL & LEASE



OPERATOR: License # 33365		API No. 15				
Name: Layne Energy Operating, LLC		Spot Description:				
Address 2:		1,963 Feet from V North / South Line of Section				
City: Sycamore State: KS Zip: 6	7363+	1,526 Feet from East / West Line of Section				
Contact Person: Mike Murphy		Footages Calculated from Nearest Outside Section Corner:				
Phone: (620) 627-2499		□ne ☑nw □se □sw				
CONTRACTOR: License # 33606		County: Montgomery				
Name: Thornton Air Rotary		Lease Name: Hare Well #: 6-16				
Wellsite Geologist: N/A	1	Field Name: Cherokee Basin Coal Area				
Purchaser:		Producing Formation: Cherokee Coals				
Designate Type of Completion:	,	Elevation: Ground: 767 Kelly Bushing: 0				
	Workover	Total Depth: 1186' Plug Back Total Depth: 1178'				
	_	Amount of Surface Pipe Set and Cemented at: 42 Feet				
☐ Oil ☐ WSW	☐ slow ☐ slgw					
Gas D&A ENFR	Temp. Abd.	Multiple Stage Cementing Collar Used? ☐ Yes ☑ No				
[] CM (Coal Bed Methane)	remp. Abd.	If yes, show depth set: Feet				
Cathodic Other (Core, Expl., etc.):	·	If Alternate II completion, cement circulated from: 1178				
If Workover/Re-entry: Old Well Info as follows:		feet depth to: Surface w/ 125 sx cmt.				
•	-					
Operator:		Drilling Fluid Management Plan				
Well Name:		(Data must be collected from the Reserve Pit)				
Original Comp. Date: Original Total [Chloride content: N/A ppm Fluid volume: bbls				
Deepening Re-perf. Conv. to ENF		Dewatering method used: N/A - Air Drilled				
Plug Back: Plug Ba	ck Total Depth	Location of fluid disposal if hauled offsite:				
Commingled Permit #:		Operator Name:				
Dual Completion Permit #:		Lease Name: License #:RECEIVED				
SWD Permit #:		RECEIVED				
ENHR Permit #:		Quarter Sec. Twp. S. R. East West				
GSW Permit #:		County: Permit #:				
	1/11/2010	KCC MIOLUM				
Spud Date or Date Reached TD Co Recompletion Date Re	ecompletion Date	KCC WICHITA				
Kansas 67202, within 120 days of the spud date, recof side two of this form will be held confidential for a	completion, workover or cor period of 12 months if requing ine logs and geologist well	the Kansas Corporation Commission, 130 S. Market - Room 2078, Wichita, noversion of a well. Rule 82-3-130, 82-3-106 and 82-3-107 apply. Information uested in writing and submitted with the form (see rule 82-3-107 for confiden-I report shall be attached with this form. ALL CEMENTING TICKETS MUST m with all temporarily abandoned wells.				
AFFIDAVIT		KCC Office Use ONLY				
I am the affiant and I hereby certify that all requirements lations promulgated to regulate the oil and gas industry and the statements herein are complete and correct to Signature: Title: Engineering Manager Date	have been fully complied v	with Letter of Confidentiality Received e. Date: Confidential Release Date: Wireline Log Received Geologist Report Received UIC Distribution				
Page	·	ALT [] I [] III Approved by: 98 Date: 2 [1 12				

Side Two

perator Name: <u>La</u>	Name: Layne Energy Operating, LLC Lease			ame: Hare Well #: 6-16					
ec. <u>16</u> Twp.33	S. R. <u>16</u>		County: MC	County: Montgomery					
ne tool open and cl covery, and flow ra	osed, flowing and shi	nd base of formations pout- ut-in pressures, whether est, along with final char all well site report.	shut-in pressure r	eached static level.	, hydrostatic pres	sures, bottom h	nole temperature, fluid		
Orill Stem Tests Taken Yes V No (Attach Additional Sheets)			Log Formatio	on (Top), Depth a	nd Datum	☐ Sample			
· _		☐ Yes 🔽 No	N	ame		Тор	Datum		
ores Taken lectric Log Run lectric Log Submitte (If no, Submit Cop		Yes No Yes No Yes No							
	Density Neutror - Sent previous	n - Sent previously ly	y						
			G RECORD	New Used intermediate, product	tion etc				
Purpose of String	Size Hole Drilled	Size Casing Set (In O.D.)	Weight Lbs. / Ft.	Setting Depth	Type of Cement	# Sacks Used	Type and Percent Additives		
				:					
		ADDITION	AL CEMENTING / S	SQUEEZE RECORD					
Purpose: — Perforate — Protect Casing — Plug Back TD — Plug Off Zone	Perforate Top Bottom Type of Centerit		# Sacks Used	# Sacks Used Type and Percent Additives					
Shots Per Foot		TION RECORD - Bridge Pi		acture, Shot, Cement Squeeze Record Amount and Kind of Material Used) Depth					
1	Rowe	300 GALLON	300 GALLONS 15% HCL, 2,400 LBS SAND, 177 BW 1026.5 TO 1028						
ļ	Weir	300 GALLON	300 GALLONS 15% HCL, 4,800 LBS SAND, 239 BW 856' TO 860'						
 	Mineral	300 GALLON	300 GALLONS 15% HCL, 2,400 LBS SAND, 178 BW 758 TO 759.5						
1	V-Shale/Croweb	300 GALLON	300 GALLONS 15% HCL, 3,600 LBS SAND, 202 BW 714' TO 716.5						
4 (UBING RECORD:	Excello/Mulky RD: Size: Set At: Packer At:				300 GALLONS 15% HCL, 4,800 LBS SAND, 220 BW 662' TO 665' Liner Run: RECEIVED				
Date of First, Resume	2.375 d Production, SWD or E	1055' NHR. Producing M	lethod:		Yes 📝 No	· · · · · · · · · · · · · · · · · · ·	JAN 3 0 20		
11/18/2010		Flowing	✓ Pumping	Gas Lift 0	Other (Explain)		-KCC tanara		
Estimated Production Per 24 Hours	Oil	Bbls. Gas	Mcf !	Water E	3bts.	Gas-Oil Ratio			
DISPOSITION OF GAS: METHOD			METHOD OF COM	OMPLETION: PF			RODUCTION INTERVAL:		
Vented	_	i <u> </u>			mmingled 6	62' to 1028'			
(If vented, S	ubmit ACO-18.)	Other (Specify)							