## 15-007-10113-0000

## KANSAS CORPORATION COMMISSION ONE POINT STABILIZED OPEN FLOW OR DELIVERABILITY TEST

| Type Test:   |   |  | G   | See Instructi                 | ons on Re   | verse Side)   | )                               |  |  |  |
|--|---|--|---|-------------------------------|---|---|---------------------------------|--|--|--|
| Open Flow  | v   |  | Test Date                                   | ı.                            |   |   | API                             | No. 15 - 007   | -10,11B - 0000                           |  |
| Deliverabi   | lty   |  | 12/11/1                                     |                               |   |   | ,,,,                            |  | ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,   |  |
| Company<br>BEREXCO LLI   | C   |  |   |                               | Lease<br>STUMI                                      | P-SMITH   | 1                               |  | v<br>F-1                                 | Vell Number  |
| County<br>BARBER   | Locati<br>SW N  |  | Section<br>18                               |                               | TWP<br>32S  | 1 10 11   | RNG (E/<br>14W                  | W)   | Α  | cres Attributed                                    |
| Field  |   |  | Reservoir<br>MISS                           | ,                             |   |   | Gas Gati<br>ONEO                | nering Conne   | ection                                   |  |
| Completion Date<br>10/1958   | •   |  | Plug Back<br>4741                           | k Total Depti                 | า   | ·····   | Packer S<br>NONE                |  |  |  |
| Casing Size 5.5  | Weigh<br>15.5#  |  | Internal C                                  | Diameter                      | Set 8   |   | Perfor                          | rations  | то<br>4724                               |  |
| Tubing Size 2 3/8  | Weigh   | t  | Internal E                                  | Diameter                      | Set 6<br>473  |   | Perfo                           | rations  | То                                       |  |
| Type Completion SINGLE   | (Describe)  |  | Type Flui<br>WATE                           | d Production                  |   |   | Pump Un                         | it or Traveling  | Plunger? Yes                             | No No  |
| Producing Thru<br>Annulus  | (Annulus / Tubing   | g)   | % c<br>.0835                                | arbon Dioxid                  | le  |   | % Nitrog<br>2.1892              |  | Gas Gra                                  | vity - G <sub>0</sub>                              |
| Vertical Depth(H   | )   |  |   | Press<br>FLAN                 | ure Taps  |   |                                 |  | (Meter R                                 | un) (Prover) Size                                  |
| Pressure Buildur   | o: Shut in 12/  | 10 2   | 0 11 at 8                                   |                               |   | Taken_12  | /11                             | 20   | 11 at 8:00 Al                            | <u>И</u> (AM) (PM)                                 |
| Well on Line:  |   |  | ) at  |                               | (AM) (PM)   | Taken   |                                 | 20   | at                                       | (AM) (PM)  |
|  |   |  |   | OBSERVE                       | D SURFAC  | E DATA  |                                 |  | Duration of Shut-i                       | 24 Hours   |
| Static / Orific<br>Dynamic Size<br>Property (Inches                  | Prover Pressi   | Pressure Differential in Inches H <sub>2</sub> 0   | Flowing<br>Temperature<br>t                 | Well Head<br>Temperature<br>t | Cas<br>Wellhead<br>(P_) or (P                       | Pressure<br>(,) or (P <sub>e</sub> )                | Wellhe:<br>(P <sub>w</sub> ) or | ubing<br>ad Pressure<br>(P <sub>1</sub> ) or (P <sub>a</sub> ) | Duration<br>(Hours)                      | Liquid Produced<br>(Barrels)                       |
| Shut-In  | poig (i m)  | 110103 1120  |   |                               | psig<br>295   | 98la<br>309   | psig                            | psia   | 24                                       |  |
| Flow   |   |  |   |                               |   |   |                                 |  |  |  |
|  |   | T  |   | FLOW STR                      | EAM ATTR  | IBUTES  |                                 |  |  |  |
| Plate<br>Coeffiecient<br>(F <sub>b</sub> ) (F <sub>p</sub> )<br>Mcfd | Circle one:<br>Meter or<br>Prover Pressure<br>psla              | Press<br>Extension<br>Pmxh   | Grav<br>Fact                                | tor T                         | Flowing<br>emperature<br>Factor<br>F <sub>r</sub> , | Fai   | ation<br>ctor<br>pv             | Metered Flow<br>R<br>(Mcfd)                                    | GOR<br>(Cubic Fee<br>Barrel)             | Flowing<br>Fluid<br>Gravity<br>G <sub>m</sub>      |
|  |   | <u>.                                    </u>   |   |                               |   |   |                                 |  |  |  |
| $(P_c)^2 = 157.132$  | _: (P <sub>w</sub> )² =   | 125.599  | (OPEN FL                                    | OW) (DELIV!<br>               |   | ') CALCUL<br><sup>-</sup> 。 - 14.4) +               |                                 | <u>:</u>   | (P <sub>a</sub> )²<br>(P <sub>d</sub> )² | = 0.207<br>=                                       |
| $(P_e)^2 \cdot (P_n)^2$<br>or<br>$(P_e)^2 \cdot (P_d)^2$             | (P <sub>e</sub> ) <sup>2</sup> - (P <sub>u</sub> ) <sup>2</sup> | Choose formula 1 or 2  1. Pe <sup>2</sup> - Pe <sup>2</sup> 2. Pe <sup>2</sup> - Pe <sup>2</sup> divided by: Pe <sup>2</sup> - Pe <sup>3</sup> | LOG of<br>formuta<br>1, or 2,<br>and divide | p,2. p,2                      | Sio   | ssure Curve<br>pe = "n"<br>- orsigned<br>lard Slope | nxl                             | oc [   | Antilog                                  | Open Flow Deliverability Equals R x Antilog (Mcfd) |
|  |   |  |   |                               |   |   |                                 | -  |  |  |
|  |   |  |   |                               |   |   |                                 |  |  |  |
| Open Flow  |   | Mcfd @ 14.   | 65 psia                                     |                               | Deliverat   | oility  |                                 | <u> </u>   | Mcfd @ 14.65 psia                        | <u> </u>   |
| The undersi  | •   |  | • •   |                               | -   |   |                                 | e above repo   | rt and that he ha                        | knowledge of                                       |
|  |   |  |   |                               |   | B   | eth .                           | Blen   | F  | RECEIVED   |
|  | Witness (   |  |   |                               | -   |   |                                 |  | ·  | C 1 4 2011   |

KCC WICHITA

| exempt of and that correct t | clare under penalty of perjury under the laws of the state of Kansas that I am authorized to request status under Rule K.A.R. 82-3-304 on behalf of the operator BEREXCO LLC the foregoing pressure information and statements contained on this application form are true and o the best of my knowledge and belief based upon available production summaries and lease records ment installation and/or upon type of completion or upon use being made of the gas well herein named. |
|------------------------------|--|
| l hei                        | reby request a one-year exemption from open flow testing for the STUMP-SMITH F-1   |
|                              | on the grounds that said well:   |
|                              | is a coalbed methane producer is cycled on plunger lift due to water is a source of natural gas for injection into an oil reservoir undergoing ER is on vacuum at the present time; KCC approval Docket No is not capable of producing at a daily rate in excess of 250 mcf/D  ther agree to supply to the best of my ability any and all supporting documents deemed by Commission necessary to corroborate this claim for exemption from testing.                                    |
|                              | Signature:   |

Instructions:

If a gas well meets one of the eligibility criteria set out in KCC regulation K.A.R. 82-3-304, the operator may complete the statement provided above in order to claim exempt status for the gas well.

At some point during the current calendar year, wellhead shut-in pressure shall have been measured after a minimum of 24 hours shut-in/buildup time and shall be reported on the front side of this form under **OBSERVED SURFACE DATA**. Shut-in pressure shall thereafter be reported yearly in the same manner for so long as the gas well continues to meet the eligibility criterion or until the claim of eligibility for exemption **IS** denied.

The G-2 form conveying the newest shut-in pressure reading shall be filed with the Wichita office no RECENTED

December 31 of the year for which it's intended to acquire exempt status for the subject well. The form must be signed and dated on the front side as though it was a verified report of annual test results.

DEC 1 4 2011