15-169-19025-00-00

KANSAS

Rev. 6-26-62

STATE CORPORATION COMMISSION

CONSERVATION DIVISION AGENT'S REPORT STATE CORPORATION COMMISSION

J. P. Roberts Administrator 500 Insurance Building Wichita 2, Kansas

INV. NO.

JAN 17 1967 SONSERVATION DIVISION Wichita, Kansas.

Operator's 1	Full Name			• • • • • • • • • • • • • • • • • • • •					·
Complete Add	ress: 20	00 North Ma	in, Wich	ita, Kans	sas	·		····	•
Lease Name_	Caywood				N	Well No	1		
ocation_	C W/4 NE	:/4		, 8	3ec. 6	Twp. 15	Rge2	(E)_	(W) X
County	Saline					Depth_			
bandoned 01	.1 Well	Gas We	11	_Input V	Well	SWD W	ell_	D & A	
ther well a		•	•		4., T. F. F.				
lugging Con	tractor:	Knight Cas	ing Pull	Ling Co.					
ddress: Bo				· ·			Licens	e No.	+36
			· · · · · · · · · · · · · · · · · · ·						
he Above we	ll was pl		ollows:		•		ry Yea	r 1967	7
he Above we	ll was pl	ugged as fo	ollows:	nted with	n 3 sack	S.			
he Above we Hole filled Hole bailed	with sand to 200°.	to 3230° a	ollows: .nd cemer e set fr	nted with	1 3 sack to 190•	s. and hole	cemente	d with 2	20 sacks
he Above we dole filled dole bailed dole filled	with sand to 200°.	to 3230° a Rock bridg	ollows: .nd cemer e set fr	nted with	1 3 sack to 190•	s. and hole	cemente	d with 2	20 sacks
he Above we dole filled dole bailed dole filled	with sand to 200°.	to 3230° a Rock bridg	ollows: .nd cemer e set fr	nted with	1 3 sack to 190•	s. and hole	cemente	d with 2	20 sacks
he Above we dole filled dole bailed dole filled	with sand to 200°.	to 3230° a Rock bridg	ollows: .nd cemer e set fr	nted with	1 3 sack to 190•	s. and hole	cemente	d with 2	20 sacks
The Above we dole filled dole bailed dole filled	with sand to 200°.	to 3230° a Rock bridg	ollows: .nd cemer e set fr	nted with	1 3 sack to 190•	s. and hole	cemente	d with 2	20 sacks
he Above we Hole filled Hole bailed	with sand to 200°.	to 3230° a Rock bridg	ollows: .nd cemer e set fr	nted with	1 3 sack to 190•	s. and hole	cemente	d with 2	20 sacks
The Above we Hole filled Hole bailed Hole filled of cellar wi	vith sand to 200°. with mud th 10 sac	to 3230° a Rock bridg to 40°. Ro	ollows: Ind cemen e set fr ck bridg	nted with rom 200° ge set fr	to 190°	s. and hole to 30° an	cemented	d with 2	20 sacks