

1 060895

To: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API NUMBER 15-171-20,345-00-00
NW NW SE, SEC. 16, T 20 S, R 33 W/4
2310 feet from S section line
2310 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5399

Lease Name Flying M Ranch Well # B-1
County Scott 156.00

Operator: American Energies Corporation
Name & Address 575 Fourth Financial Center
Wichita, KS 67202

Well Total Depth 4800 feet
Conductor Pipe: Size _____ feet
Surface Casing: Size 8 5/8 feet 254

Abandoned Oil Well _____ Gas Well _____ Input Well _____ SWD Well _____ D&A X

Other well as hereinafter indicated _____

Plugging Contractor Beredco Inc. License Number 5147

Address 401 E. Douglas, #402, Wichita, KS 67202

Company to plug at: Hour: 1:30 p.m. Day: 2 Month: 11 Year: 19 86

Plugging proposal received from Howard Caine

(company name) Beredco (phone) 316-653-2463

were: to fill hole with heavy mud and spot cement through drill pipe Elevation 2960'
Anhydrite 2146'

1st plug at 2146' with 50 sx cement, 2nd plug at base Dakota with 75 sx cement,

3rd plug at 280' with 50 sx cement, 4th plug at 40' with 10 sx cement,

5th plug to circulate rathole with 15 sx cement,

6th plug to circulate mousehole with 10 sx cement.

Plugging Proposal Received by Paul Luthi
(TECHNICIAN)

Plugging Operations attended by Agent?: All _____ Part _____ None X

Operations Completed: Hour: 4:30 p.m. Day: 2 Month: 11 Year: 19 86

ACTUAL PLUGGING REPORT 1st plug at 2146' with 50 sx cement,

2nd plug at 1450' with 75 sx cement,

3rd plug at 280' with 50 sx cement,

4th plug at 40-0' with 10 sx cement,

5th plug to circulate rathole with 10 sx cement,

6th plug to circulate mousehole with 10 sx cement.

NOV 5 1986
11-05-86

Remarks: Used 60/40 Pozmix 6% gel by Halliburton.
(If additional description is necessary, use BACK of this form.)

(If data did not) observe this plugging.

INVOICED

Signed Paul A. Luthi
(TECHNICIAN)

DATE 11-5-86

INV. NO. 15304
11-2

CARD MUST BE TYPED

State of Kansas

CARD MUST BE SIGNED

NOTICE OF INTENTION TO DRILL

(see rules on reverse side)

Starting Date October 25, 1986

API Number 15-171-20,345-60-00

OPERATOR: License # 5399
Name American Energies Corporation
Address 575 Fourth Financial Center
City/State/Zip Wichita, KS 67202
Contact Person Alan L. DeGood
Phone 316-263-5785

NW. NW. SE. Sec. 16. Twp. 20. S. Rg. 33. East
2310. West
2310. Ft. from South Line of Section
Ft. from East Line of Section

(Note: Locate well on Section Plat on reverse side)

CONTRACTOR: License # 5369-5147
Name Beredco, Inc.
City/State Wichita, KS

Nearest lease or unit boundary line 330 feet

County Scott
Lease Name Flying M Ranch Well # B-1

Ground surface elevation N/A feet MSL

Well Drilled For: Well Class: Type Equipment:
X Oil SWD Infield X Mud Rotary
Gas Inj Pool Ext Air Rotary
OWWO Expl X Wildcat Cable

Domestic well within 330 feet: yes X no

Municipal well within one mile: yes X no

Surface pipe by Alternate: 1-2X

Depth to bottom of fresh water 220'

Depth to bottom of usable water 1350'

Surface pipe planned to be set 250'

Projected Total Depth 4750 feet

Formation Mississippian

If OWWO: old well info as follows:

Operator
Well Name
Comp Date Old Total Depth

I certify that well will comply with K.S.A. 55-101, et seq., plus eventually plugging hole to KCC specifications.

cementing will be done immediately upon setting production casing.

Date Oct 22, 1986 Signature of Operator or Agent Alan L. DeGood Title Vice-President

For KCC Use:

Conductor Pipe Required 250 feet; Minimum Surface Pipe Required 250 feet per Alt.

This Authorization Expires 9-21-87 Approved By 10-21-86

SPUD - 10-25-86

NO W.W.

PLUGGING PROPOSAL IF ABOVE IS D & A

This plugging proposal will be reviewed and approved or revised at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).

1st plug @ 2250' 2146 feet depth with 60
2nd plug @ 1450' 1450 feet depth with 75
3rd plug @ 250' 280 feet depth with 50
4th plug @ 40' 10 feet depth with 10
5th plug @ feet depth with
(2) Rathole with 15 sxs
(sxs of 60
sxs of 60-40 Poz 670 Gall
sxs of 60-40 Poz
sxs of 60-40 Poz
sxs of
(b) Mousehole with 10 sxs

PUSHER Howard Caine

TD 4800 FORMATION MISS.

SURFACE PIPE 8 5/8" @ 254'

ANHYDRITE 2146 BELEVATION

STARTING TIME & DATE 1:20 PM 10-25-86

COMPLETION TIME & DATE 4:30 PM 10-25-86

1st PLUG @ 2146 FT. W/ 50 SX

2nd PLUG @ 1450 FT. W/ 75 SX

3rd PLUG @ 280 FT. W/ 50 SX

4th PLUG @ 40 FT. W/ 10 SX

RAT HOLE CIRCULATED W/ 10 SX

MOUSE HOLE CIRCULATED W/ 10 SX

WATER WELL PLUGGED W/ SX

CEMENT COMPANY Halliburton

TECHNICIAN Paul Miller

6/4 6 0/0 - D.G.

NOV 5 1986