WELL HISTORY - DESCRIPTION OF WELL & LEASE

KANSAS CORPORATION COMMISSION
OIL & GAS CONSERVATION DIVISION
Form Must Be Typed
Form must be Signed
All blanks must be Filled

OPERATOR: License #5447	API No. 15
Name: OXY USA, INC.	Spot Description:
Address 1: P.O. BOX 2528	NE_NE_SE_Sec. 9 Twp. 28 S. R. 35 ☐ East West
Address 2:	2,554 Feet from North / South Line of Section
City: LIBERAL State: KS Zip: 67905 +	Feet from ☑ East / ☐ West Line of Section
Contact Person: LAURA BETH HICKERT	Footages Calculated from Nearest Outside Section Corner:
Phone: (620) 629-4253	□NE □NW □SE □SW
CONTRACTOR: License # 473	County: GRANT
Name: DESTAL TYLER WATER WELL SERVICE	Lease Name: ENGLISH STATION Well #: 1
Wellsite Geologist: N/A	Field Name:
	Producing Formation: Kelly Bushing:
Designate Type of Completion:	
New Well Re-Entry Workover	Total Depth: 300 Plug Back Total Depth: 120
Oil wsw swd slow	Amount of Surface Pipe Set and Cemented at: Feet
Gas D&A ENHR SIGW	Multiple Stage Cementing Collar Used?
☐ OG ☐ GSW ☐ Temp. Abd.	If yes, show depth set: Feet
CM (Coal Bed Methane)	If Alternate II completion, cement circulated from:
✓ Cathodic U Other (Core, Expl., etc.):	feet depth to:sx cmt.
If Workover/Re-entry: Old Well Info as follows:	
Operator:	Drilling Fluid Management Plan
Well Name:	(Data must be collected from the Reserve Pit)
Original Comp. Date: Original Total Depth:	Chloride content:ppm Fluid volume: 35 bbls
☐ Deepening ☐ Re-perf. ☐ Conv. to ENHR ☐ Conv. to SWD ☐ Conv. to GSW	Dewatering method used:EVAPORATION AND BACKFILL
Plug Back: Plug Back Total Depth	Location of fluid disposal if hauled offsite:
Commingled Permit #:	Operator Name:
Dual Completion Permit #:	Lease Name: License #:
SWD Permit #:	QuarterSecTwpS. R East West
ENHR Permit #:	_ County: Permit #:
Permit #	County.
12/29/2011 12/29/2011 12/29/2011 Spud Date or Date Reached TD Completion Date or	
Recompletion Date Recompletion Date	·
Kansas 67202, within 120 days of the spud date, recompletion, workover or c of side two of this form will be held confidential for a period of 12 months if rec	the Kansas Corporation Commission, 130 S. Market - Room 2078, Wichita, onversion of a well. Rule 82-3-130, 82-3-106 and 82-3-107 apply. Information quested in writing and submitted with the form (see rule 82-3-107 for confidencell report shall be attached with this form. ALL CEMENTING TICKETS MUST rm with all temporarily abandoned wells.
AFFIDAVIT	KCC Office Use ONLY FED 0.0 2040
I am the affiant and I hereby certify that all requirements of the statutes, rules and	regu-
lations promulgated to regulate the oil and gas industry have been fully complied	d with Letter of Confidentiality Received
and the statements herein are complete and correct to the best of my knowledge	ge. Confidential Release Date:
Laura WA. V. L.	Wireline Log Received
Signature: / WWW / / / / / / / / / / / / / / / /	Geologist Report Received
Title: Kywlutny Date: 2/7/12	UIC Distribution
	ALT I I II Approved by: Date: 2 10 1

Side Two

Operator Name: OXY	USA, INC.			Lease I	Name: _	ENGLISH S	TATION	_Well #:1_		
Sec. 9 Twp.28	s. r. <u>35</u>	Eas	t ✓ West	County	: <u>GR</u> /	NT				
INSTRUCTIONS: Show time tool open and close recovery, and flow rates line Logs surveyed. Atta	ed, flowing and sho if gas to surface to	ut-in press est, along	ures, whether s with final chart(hut-in press	sure rea	ched static leve	l, hydrostatic press	sures, bottom	hole tempera	ature, fluid
Drill Stem Tests Taken (Attach Additional Sh	eets)	Y	′es ✓ No			og Formati	on (Top), Depth ar	d Datum	☐ Sai	nple
Samples Sent to Geolog Cores Taken Electric Log Run Electric Log Submitted I (If no, Submit Copy)	gical Survey	_ _ _	es ☑ No		SEE /	ne ATTACHED		Тор	Daí	tum
List All E. Logs Run:		<u></u>		· ·		*****		n, •		- - "
		Pen		RECORD	√ N	ew Used	dian ata			
Purpose of String	Size Hole Drilled	Si	ze Casing t (In O.D.)	Weig Lbs. /	ht	Setting Depth	Type of Cement	# Sacks Used	Type and	
SURFACE	16	8.75		UNKNOV	٧N	20	CONCRETE	5	UNKNOWN	
		,								
		<u> </u>	ADDITIONAL	CEMENTIN	IG / SQI	JEEZE RECORE)		1	
Purpose: —— Perforate —— Protect Casing —— Plug Back TD —— Plug Off Zone	Depth Top Bottom	Туре	of Cement	# Sacks				ercent Additive	5	
Shots Per Foot	PERFORATI Specify	ON RECOF	RD - Bridge Plug Each Interval Per	s Set/Type forated			acture, Shot, Cement mount and Kind of Ma		rd	Depth
									·	1 7 - 2
TUBING RECORD:	Size:	Set At:		Packer At:		Liner Run:	Yes No		REC	
Date of First, Resumed Pro	oduction, SWD or EN	HR.	Producing Meth	od:	ı 🗆	Gas Lift (Other (Explain)		FEB (9 201 101 11-
Estimated Production Per 24 Hours	Oil	Bbls.	Gas	Mcf	Wat	er E	Bbls. G	as-Oil Ratio	(ravity
DISPOSITION Vented Sold (if vented, Submi	Used on Lease		_	ETHOD OF		Comp. Co	mmingled mit ACO-4)	PRODUCTI	ON INTERVAL	:



Tyler Water Well Inc. 305 Santa Fe Ave. Holcomb, KS 67851

KCC WICHITA

TEST HOLE REPORT

	Con	tact NameCorrpro Oxy 1_Engli Hole Number1_ GPS Hole Location	sh	·	Date_	12-27	-11		
	Test	Hole NumberI GPS	Ç.	tate	νς		Driller Clint		
	Test	Hole Location	3	iaic_			Dimeicarac		
	1030	Distance and	Direction fr	om Per	manent Lar	dmark or F	revious Test Hole		
				TES	ST LO	G			
		Approximate	e Static	Wa	ter Lev	el	Measured		
FROM 0	15	FORMATION Topsoil & Clay	FAIR	GOOI	FROM	то	FORMATION	FAIR	Good
15	30	Brown Sandy Clay Littl Cliche							
30	45	Same							<u> </u>
45	60	Brown Clay & Sandy Clay		<u> </u>					
60	75	Sand Little Clay		55.50	~ 2.		يقسانيو خبرات يشاريوا بمريديوا سو		_
75	90	Sand & Gravel							
90	105	Sand Little Clay							
105	120	Same							
120	135	Same							
135	140	Same							
140	150	Brown Clay							
150	165	Sand & Clay & Cliché					,		
165	170	Same							
170	180	Clay							
180	195	Sandy Clay Little Cliché							
195	210	Sand Little Clay							
210	214	Same							
214	225	Clay							
225	240	Sandy clay							
240	255	Sand Little Clay							
255	270	Same							
270	285	Clay Little Sand							
.285	.300	Sand Little Clay					and a second of the second of		
									<u> </u>
	ъ	CNA 1			р.)		
	Bag	gs of Mud			Bag	S OI b	Bran		-11 /
	D:+ Raf	gs of Hole Plug			Pag	IU FII	Il Cotton Seed	KEC	FIVED
	DI	140			Dag	3 OI (otton bood	FFR (า จ์ วกเ

corrpro^o

JOB NO.	340310223 INSTALLATION DATE 12/29/20									
JOB TITLE	INSTALLATION OF CATHODIC PROTECTION DEEP ANODE BED									
JOB SITE	English Station 8V						<u></u>			
COMPANY	OXY		1814		·			· · · · · · · · · · · · · · · · · · ·		
Rotary:	X Cable Tool:	_	Casing:			8" x 20' PVC				
	Depth: 300' Diameter: 8"	Cokebre	eze: Lores	SC#		10 EA MMC	1" X 39" TUBUL	AR ANODES		
Depth	· ·				Without		Depth Top			
Ft.	And	TO STRUCTURE			Coke	Coke	of Anode			
	Driller's Log.	E-	1 -				No	Ft.		
0	CASING	14.79].							
10	CASING		ļ <u></u>		0.8			<u>-</u>		
20	CASING				0.9					
30			ļ		0.7					
40					0.8					
50		ļ	ļ .	ļ	0.9					
60		· ·			0.8					
70		 	<u> </u>		0.2					
80		<u> </u>	<u></u>	ļ	0.2					
90		 		 	0.5					
100		<u> </u>		<u> </u>	0.3					
110		<u> </u>			0.3					
120		 	<u> </u>	-	0.3					
130		 	<u> </u>		0.2					
140		ļ			1.3					
150		<u> </u>	ļ	 	0.9					
160 170		 		 	1.7					
		<u> </u>	 	 	0.7	· · · · · · · · · · · · · · · · · · ·				
180 190		ł			1.8					
200		 	 	<u> </u>	0.4					
210		<u> </u>	1		0.4	4.5		210'		
220		†	<u> </u>		1.5	4.5		220'		
230	the state of the s	 	<u> </u>		1.1	4.6		230'		
240	هرا المارا المعالى المعالى المعالى المارات المعالى المارات المارات المعالى المارات الم				- 0.5 -	4.6		- 240'		
250					0.5	4.5		250'		
260					0.8	4.5		260'		
270					1.5	4.3		270'		
280					1.3	4.5		280'		
290					1.2	4.5		290'		
300		<u> </u>			1.3	4.6		300'		
310										
320										
330					$\sqcup \sqcup$					
340										
350		ļ		ļ	 					
360		 								
370		ļ	<u> </u>	ļ						
380		 			 					
390		-					ļ -			
400		<u>L</u>		L	ليصا		L			

RECEIVED FEB 0 9 2012

KCC WICHITA