

TO:
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGIN
130 SOUTH MARKET, SUITE 2078
WICHITA, KANSAS 67202

API Well Number: 15-003-20282-00-00
Spot: SWNENWSE Sec/Twnshp/Rge: 3-22S-19E
1998 feet from S Section Line, 1947 feet from E Section Line
Lease Name: UNIT 3 Well #: RW-10
County: ANDERSON Total Vertical Depth: 843 feet

Operator License No.: 33097
Op Name: SOUTHERN STAR CENTRAL GAS PIPE
Address: 4700 HWY 56
OWENSBORO, KY 42301

String	Size	Depth (ft)	Pulled (ft)	Comments
SURF	7	8		
PROD	2	843		137 SX

Well Type: OIL UIC Docket No: _____ Date/Time to Plug: 12/30/2011 12:00 PM
Plug Co. License No.: 6372 Plug Co. Name: SPLANE PULLING AND ROUSTABOUT SERVICE, INC.
Proposal Rcvd. from: STERLING BARKER Company: SOUTHERN STAR Phone: (785) 448-4816

Proposed Plugging Method: WELL HAS BROKE OUT AND IS RELEASING GAS. KILL WELL AND PULL 1" PIPE FROM HOLE. RUN A PACKER INSIDE 2" TO 750' AND SET IT. PUMP CEMENT THROUGH 1" DOWN PAST PACKER TO SEAL OFF BOTTOM OF HOLE. WAIT A COUPLE OF DAYS AND RELEASE PACKER. PULL PACKER AND 1" OUT AND RUN WORK STRING BACK IN AND TAG BOTTOM PLUG. CEMENT TO SURFACE, PULL WORK STRING OUT, AND TIE ONTO TUBING AND SQUEEZE CEMENT UNTIL GOOD RETURNS ARE APPARENT WHERE WELL IS BROKE OUT.

Plugging Proposal Received By: JOHN ALMOND WitnessType: NONE
Date/Time Plugging Completed: 12/31/2011 12:00 PM KCC Agent: JOHN ALMOND

Actual Plugging Report:

Contractor ran 1" pipe and packer down to 750', squeezed cement into well and shut in at 500 psi. they let the well set for a day and pulled the pipe and packer out, ran the 1" pipe back in to 800' and circulated portland cement to surface, hooked up to 2" and squeezed, shut in at 1000 psi. Contractor indicated he used 89 sacks cement to plug well.

Perfs:

Top	Bot	Thru	Comments
805	840		SQUIRREL

RECEIVED

FEB 13 2012 JA

KCC Chanute Dist. #3

RECEIVED

FEB 16 2012

KCC WICHITA

Remarks:

Plugged through: TBG

District: 03

Signed


(TECHNICIAN)

2/21/12