

TO: STATE CORPORATION COMMISSIO
CONSERVATION DIVISION - PLUGGIN
130 SOUTH MARKET, SUITE 2078
WICHITA, KANSAS 6720

API Well Number: 15-207-19864-00-00
Spot: NWSWNWSE Sec/Twnshp/Rge: 24-23S-16E
1834 feet from S Section Line, 2547 feet from E Section Line
Lease Name: REMLINGER/GLEUE Well #: 1
County: WOODSON Total Vertical Depth: 990 feet

Operator License No.: 34047
Op Name: RON-BOB OIL LLC
Address: PO BOX 41
NEOSHO FALLS, KS 66758

String	Size	Depth (ft)	Pulled (ft)	Comment
SURF	6.5	20		20 SX
PROD	2.375	965		20 SX

Well Type: OIL UIC Docket No: _____ Date/Time to Plug: 10/17/2011 12:00 AM
Plug Co. License No.: 33749 Plug Co. Name: KEPLEY WELL SERVICE, LLC
Proposal Rcvd. from: ROBERT CHRISTENSON Company: _____ Phone: (620) 365-0919

Proposed Plugging Method: RUN 1" INTO 2" TO BOTTOM AND RUN 1" BEHIND 2" TO BOTTOM, THEN CEMENT FROM BOTTOM TO SURFACE.

Plugging Proposal Received By: _____ WitnessType: NONE
Date/Time Plugging Completed 10/18/2011 8:00 AM KCC Agent: RYAN DULING

Actual Plugging Report:

Ran 1" pipe down the inside of the 2 3/8" casing to 675'. Got tight and could not wash down any farther. Ran 1" pipe down the backside of the 2 3/8" casing inside the 6.5" casing to 697'. Pumped cement through the 1" pipe inside the 2 3/8" casing from 675' to surface. Pulled 300' of 1" pipe out of the 2 3/8" casing. Pumped cement through the 1" pipe on the backside of the 2 3/8" casing from 697' to surface. Pulled 300' of 1" pipe from the backside. Pumped cement through the 1" pipe on the backside of the 2 3/8" casing from 397' to surface. Pulled the rest of the 1" pipe from the backside. Pumped cement through the 1" pipe inside the 2 3/8" casing from 375' to surface. Pulled the rest of the 1" pipe from the 2 3/8" casing. Topped well off with cement. A total of 95 sacks of portland cement was reported used to plug this well.

Perfs:

RECEIVED
FEB 16 2012
KCC Chanute Dist. #3 RMD

RECEIVED
FEB 23 2012

Remarks:

Plugged through: TBG

KCC WICHITA

District: 03

Signed _____

(TECHNICIAN)

2/28/12