

1 070270

15-101-0008000-00

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15- NA  
C NW NE, SEC. 30, T 16 S, R 27 W/E  
4620 feet from S section line  
1980 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # \_\_\_\_\_

Lease Name Gregor Well # 1

Operator: Kansas Corporation Commission  
Name &  
Address \_\_\_\_\_

County Lane

Well Total Depth 4636 feet

Conductor Pipe: Size \_\_\_\_\_ feet

Surface Casing: Size 8 5/8 feet 248

Abandoned Oil Well  Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A \_\_\_\_\_

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Kansas Corporation Commission License Number \_\_\_\_\_

Address \_\_\_\_\_

Company to plug at: Hour: 2:30 p.m. Day: 11 Month: 12 Year: 19 86

Plugging proposal received from Dan Goodrow

(company name) KCC (phone) 913-798-3873

were: 5 1/2" at 4620'

1st plug pump 350 lbs. hulls, 175 sx ATL cement, 50 sx ATL cement down annulus with  
50 lbs. hulls.

Note: Cement fell 570'.

Plugging Proposal Received by Dan Goodrow  
(TECHNICIAN)

Plugging Operations attended by Agent?: All  Part \_\_\_\_\_ None \_\_\_\_\_

Operations Completed: Hour: 3:30 p.m. Day: 11 Month: 12 Year: 19 86

ACTUAL PLUGGING REPORT 1st plug pumped 350 lbs. hulls, 175 sx ATL cement, 50 sx ATL cement  
down annulus with 50 lbs. hulls.

2nd plug filled hole to 0' with 3 yards ready mixed cement. (white concrete)

Maximum pressure 0 psi and shut in at vacuum. - 5 1/2"

Maximum pressure 500 psi and shut in 50 psi. - 8 5/8" annulus.

Remarks: Used ATL cement by Allied.  
(if additional description is necessary, use BACK of this form.)

I (did / ~~did not~~) observe this plugging \_\_\_\_\_  
STATE CORPORATION COMMISSION

Signed Dan Goodrow  
(TECHNICIAN)

FEB 5 1987  
02-05-1987  
CONSERVATION DIVISION  
Wichita, Kansas