TV	3040124 15-169-00609-007
To a series of the first of the series of th	API NUMBER 15- Suchef # C-6711
To: STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING SECTION 200 COLORADO DERBY BUILDING WICHITA, KANSAS 67202	NW SEC. 32, T/65, R 300/E
	appen Clawy FEET FROM N/S SECTION LINE
TECHNICIAN'S PLUGGING REPORT	FEET FROM W/F SECTION LINE
OPERATOR LICENSE #	LEASE NAME augusta Halon WELL # Q
OPERATOR: 7 alem Energy NAMES ADDRESS Lindsburg, KSV BOX 401- 67456	COUNTY Saline WELL TOTAL DEPTH46 235 35.00 CONDUCTOR PIPE: SIZE FEET
ABANDONED OIL WELL GAS WELL	SURFACE CASING: SIZE FEET Shallow INPUT WELL SWD WELL X D8.A
OTHER WELL AS HEREINAFTER INDICATED	
PLUGGING CONTRACTOR FILEM EN ADDRESS Lindshary 45.	reigy Cosp License Number 5732
COMPANY TO PLUG AT: HOUR: 934 M DAY:	3 NONTH: 10 YEAR: 1984
PLUGGING PROPOSAL RECIEVED FROM Cha	s. Casebeer 913-
(COMPANY NAME) - Falcon	Energy (PHONE) 227-2948
WERE: 25 Cf on batton.	- 25 y on tap -
PLUGGING PROF	OSAL RECEIVED BY Ralph Tille
PLUGGING OPERATIONS ATTENDED BY AGENT?: F	NONE
OPERATIONS COMPLETED: HOUR: 93711 DAY:	3 NONTH: 10 YEAR: 1984
ACTUAL DILICCIAG DEDIGOT	4-2 hull to batton-Let
C. I I have Property 25	4 into 43 + Shut in -
at 1900. Sungs of	of wine
Drugge	
Remarks:	RECEIVED
Now 10 - 8906/1	STATE CORPORATION COMMISSION
	OCT 1 5 1984
I (DID / DID NOT) OBSERVE THIS PLUGGING.	CONSERVATION DIVISION Wighting Kansac
	Signer (Salph (SAll))

INVOICED

FORM CP-2/3 Rev. 6-83

15-169-00609-00-01

THE KANSAS STATE BOARD OF HEALTH



TOPEKA KANSAS

Sanitation

September 11, 1958

Warner & Stevenson Saline County, Kansas NW/4 of 32-16-3W

6

Mr. Clyde Milligan, General Gounsel State Corporation Commission Fourth Floor State Office Building

Plugged 10-3-84

Dear Mr. Milligan:

Topeka, Kansas

Augusta Holm lease

This Section favors the issuance of a salt water disposal permit to Warner and Stevenson to use their Well No. 2 - located in the NW/4 of 32-16-3W, Saline County, Kansas.

The salt water is to be introduced into the Hutchinson member of Wellington shale formation with open hole from a depth of 300 feet to a bottom depth of 500 feet - maximum pressure at the well head not to exceed zero (0) pounds.

This well must be so cased and cemented as to allow none of the mineralised water to come up the hele to contact any of the upper water.

Sincerely,

OIL FIELD SECTION

Deland 6

Willard O. Hilton Chief Geologist & Director

WOH/e

CC: Jewel Ogden
N. Biegler

RECEIVED STATE CORPORATION COMMISSION

NOT 1 5 1984

CONSERVATION DIVISION Wichita, Kansas