1050327

IN

-		API NUMBER 15-135-22,644-00-00
TO: STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING SECTION 200 COLORADO DERBY BUILDING WICHITA, KANSAS 67202		C SE NW , SEC. 4 , T 16 S, R 25 W/R N SE Corner of SE Corner of NXX section line
TECHNICIA	N'S PLUGGING REPORT	3300 (EV SE Corner of WXX section line
Operator (License # 5123	Lease Name Carter Well # "G" 1
Operator:	Pickrell Drilling Company	CountyNess
	Litwin Building	Well Total Depth 4530 147.23 feet
	Wichita, KS 67202	Conductor Pipe: Sizefeet
		Surface Casing: Size 8 5/8 feet 305
Abandoned	Oll Well Gas Well	Input Well SWD Well D&A
	t as hereinafter indicated	
	· · · · · · · · · · · · · · · · · · ·	pany License Number 5123
Address	Litwin Building, Wichita, KS 672	.02
Company †	o plug at: Hour: 9:00 pm Day:	30 Month: August Year:19 84
Plugging	proposal received from	Herb French
(company	name) Pickrell	(phone) 316-262-8427
vere:	to fill hole with heavy mud an	nd spot cement through drill pipe
	at 1900' with 50 sx cement	
2nd plug	at 990' with 50 sx cement	
	at '330' with 40 sx cement	
	solid bridge hulls - plug at 40' cement to	surface with 10 sx cement
6th plug	to circulate rat hole with 15 sx	posal Received by Richard M. Jacky
	.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	(TECHNIC I ANT
Plugging	Operations attended by Agent?:	AllPartNoneX
Operation	ns Completed: Hour: $10:30~ ext{pmpay}$:	30 Month: August Year:19 84
ACTUAL PL	UGGING REPORT 1st plug at 1900'	with 50 sx cement, 2nd plug at 990' with 50 sx
cement, 3	3rd plug at 330' with 40 sx cemer	nt, 4th & 5th plugs - solid bridge - hulls - plug
		ement, 6th plug to circulate rat hole with 10
sx cement	·	
· .		
Remarks:	Used 60/40 Pozmix 2% gelp3%pccft (If additional_tdexcompation)	gy Allied. Dannier O'ssary, use BACK of this form.)
	did Dot) observe this plugging of	
9-17-	84 CONSERVATION CIN	VISION (TECHNICIAN)
3683	Wichita, Kansa	FORM CP-2/3

FORM CP-2/3 Rev.01-84