



CONFIDENTIAL

OIL & GAS CONSERVATION DIVISION

WELL COMPLETION FORM

WELL HISTORY - DESCRIPTION OF WELL & LEASE

Form Must Be Typed
Form must be Signed
All blanks must be Filled

OPERATOR: License # 34192
Name: SandRidge Exploration and Production LLC
Address 1: 123 ROBERT S. KERR AVE
Address 2:
City: OKLAHOMA CITY State: OK Zip: 73102 + 6406
Contact Person: Tiffany Golay
Phone: (405) 429-6543
CONTRACTOR: License # 34464
Name: Lariat Services, Inc.
Wellsite Geologist: Kathy Gentry
Purchaser:

Designate Type of Completion:
New Well Re-Entry Workover
Oil WSW SWD SIOW
Gas D&A ENHR SIGW
OG GSW Temp. Abd.
CM (Coal Bed Methane)
Cathodic Other (Core, Expl., etc.):

If Workover/Re-entry: Old Well Info as follows:
Operator:

Well Name:

Original Comp. Date: Original Total Depth:

Deepening Re-perf. Conv. to ENHR Conv. to SWD
Conv. to GSW
Plug Back: Plug Back Total Depth
Commingled Permit #:
Dual Completion Permit #:
SWD Permit #:
ENHR Permit #:
GSW Permit #:

11/18/2011 12/07/2011 12/10/2011
Spud Date or Date Reached TD Completion Date or
Recompletion Date Recompletion Date

API No. 15 - 15-033-21606-01-00

Spot Description:
N2_NE_NW_NW Sec. 19 Twp. 31 S. R. 19 East West
200 Feet from North / South Line of Section
990 Feet from East / West Line of Section

Footages Calculated from Nearest Outside Section Corner:
NE NW SE SW

County: Comanche

Lease Name: Sean Well #: 1-18H

Field Name:

Producing Formation: Mississippi

Elevation: Ground: 2087 Kelly Bushing: 2067

Total Depth: 9830 Plug Back Total Depth:

Amount of Surface Pipe Set and Cemented at: 920 Feet

Multiple Stage Cementing Collar Used? Yes No

If yes, show depth set: Feet

If Alternate II completion, cement circulated from:

feet depth to: w/ sx cmt.

Drilling Fluid Management Plan

(Data must be collected from the Reserve Pit)

Chloride content: 8891 ppm Fluid volume: 490 bbls

Dewatering method used: Haul Off Pit

Location of fluid disposal if hauled offsite:

Operator Name: Triple C Soil Farming

Lease Name: unknown License #: 99999

Quarter NW Sec. 27 Twp. 26 S. R. 18 East West

County: Woodward, OK Permit #: 18987

AFFIDAVIT

I am the affiant and I hereby certify that all requirements of the statutes, rules and regulations promulgated to regulate the oil and gas industry have been fully complied with and the statements herein are complete and correct to the best of my knowledge.

Submitted Electronically

KCC Office Use ONLY

Letter of Confidentiality Received
Date: 03/15/2012
Confidential Release Date:
Wireline Log Received
Geologist Report Received
UIC Distribution
ALT I II III Approved by: NAOMI JAMES Date: 03/19/2012

Sandridge Energy

Comanche (KS27S)

Sec 19-T31S-19W - GRID

Sean 1-18H

Wellbore #1

Survey: MWD Surveys

Standard Survey Report

07 December, 2011

Wolverine Directional, LLC

Survey Report

Company: Sandridge Energy	Local Co-ordinate Reference: Well Sean 1-18H	
Project: Comanche (KS27S)	TVD Reference: WELL @ 0.0ft (Original Well Elev)	
Site: Sec 19-T31S-19W - GRID	MD Reference: WELL @ 0.0ft (Original Well Elev)	
Well: Sean 1-18H	North Reference: Grid	
Wellbore: Wellbore #1	Survey Calculation Method: Minimum Curvature	
Design: Wellbore #1	Database: EDM 2003.21 Single User Db	

Design Wellbore #1				
Audit Notes:				
Version: 1.0	Phase: ACTUAL	Tie On Depth: 0.0		
Vertical Section:	Depth From (TVD) (ft)	+N/-S (ft)	+E/-W (ft)	Direction (°)
	0.0	0.0	0.0	1.44

Survey Program		Date 2011/12/07		
From (ft)	To (ft)	Survey (Wellbore)	Tool Name	Description
947.0	9,860.0	MWD Surveys (Wellbore #1)	MWD	MWD - Standard

Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)
0.0	0.00	0.00	0.0	0.0	0.0	0.0	0.00	0.00	0.00
947.0	0.30	237.30	947.0	-1.3	-2.1	-1.4	0.03	0.03	0.00
First MWD Survey									
1,135.0	0.70	236.10	1,135.0	-2.2	-3.5	-2.3	0.21	0.21	-0.64
1,419.0	1.30	174.50	1,419.0	-6.4	-4.6	-6.5	0.40	0.21	-21.69
1,705.0	0.30	209.10	1,704.9	-10.3	-4.6	-10.4	0.37	-0.35	12.10
1,991.0	0.40	300.30	1,990.9	-10.5	-5.9	-10.6	0.18	0.03	31.89
2,468.0	0.50	288.30	2,467.9	-9.0	-9.3	-9.2	0.03	0.02	-2.52
2,944.0	0.30	319.10	2,943.9	-7.4	-12.1	-7.7	0.06	-0.04	6.47
3,420.0	0.80	38.20	3,419.9	-3.8	-10.8	-4.1	0.17	0.11	16.62
3,895.0	1.00	30.20	3,894.8	2.4	-6.7	2.2	0.05	0.04	-1.68
3,927.0	0.80	29.80	3,926.8	2.8	-6.4	2.6	0.63	-0.63	-1.25
3,959.0	0.80	48.70	3,958.8	3.2	-6.2	3.0	0.82	0.00	59.06
3,990.0	0.90	25.60	3,989.8	3.5	-5.9	3.4	1.14	0.32	-74.52
4,022.0	0.90	30.60	4,021.8	4.0	-5.7	3.8	0.25	0.00	15.63
4,054.0	1.00	49.60	4,053.8	4.4	-5.3	4.2	1.03	0.31	59.38
4,086.0	0.70	49.40	4,085.8	4.7	-5.0	4.5	0.94	-0.94	-0.63
4,117.0	0.80	49.00	4,116.8	4.9	-4.6	4.8	0.32	0.32	-1.29
4,150.0	1.00	38.40	4,149.8	5.3	-4.3	5.2	0.79	0.61	-32.12
4,181.0	1.90	3.20	4,180.8	6.0	-4.1	5.9	3.96	2.90	-113.55
4,213.0	4.70	355.70	4,212.7	7.9	-4.2	7.8	8.83	8.75	-23.44
4,245.0	7.20	0.30	4,244.5	11.2	-4.3	11.1	7.95	7.81	14.38
4,277.0	9.10	5.50	4,276.2	15.7	-4.0	15.6	6.36	5.94	16.25
4,308.0	10.80	6.00	4,306.8	21.0	-3.5	20.9	5.49	5.48	1.61
4,340.0	12.70	6.40	4,338.1	27.5	-2.8	27.4	5.94	5.94	1.25
4,372.0	15.10	3.50	4,369.1	35.2	-2.1	35.1	7.81	7.50	-9.06
4,404.0	17.30	3.80	4,399.9	44.1	-1.5	44.0	6.88	6.88	0.94
4,435.0	19.30	5.00	4,429.3	53.8	-0.8	53.7	6.56	6.45	3.87
4,467.0	21.40	5.40	4,459.3	64.9	0.2	64.8	6.58	6.56	1.25
4,499.0	23.40	4.60	4,488.9	77.0	1.3	77.0	6.32	6.25	-2.50
4,531.0	25.70	4.90	4,518.0	90.3	2.4	90.3	7.20	7.19	0.94
4,563.0	27.70	5.40	4,546.6	104.6	3.7	104.6	6.29	6.25	1.56
4,594.0	29.00	5.50	4,573.9	119.2	5.1	119.3	4.20	4.19	0.32
4,626.0	30.20	5.00	4,601.7	135.0	6.5	135.1	3.83	3.75	-1.56
4,658.0	32.00	4.30	4,629.1	151.4	7.9	151.6	5.74	5.63	-2.19
4,690.0	34.40	3.30	4,655.9	168.9	9.0	169.1	7.69	7.50	-3.13
4,721.0	36.60	2.90	4,681.1	186.9	10.0	187.1	7.14	7.10	-1.29
4,753.0	38.20	2.90	4,706.5	206.3	11.0	206.5	5.00	5.00	0.00
4,785.0	40.30	2.70	4,731.3	226.5	12.0	226.8	6.57	6.56	-0.83

Wolverine Directional, LLC

Survey Report

Company: Sandridge Energy
Project: Comanche (KS27S)
Site: Sec 19-T31S-19W - GRID
Well: Sean 1-18H
Wellbore: Wellbore #1
Design: Wellbore #1

Local Co-ordinate Reference: Well Sean 1-18H
TVD Reference: WELL @ 0.0ft (Original Well Elev)
MD Reference: WELL @ 0.0ft (Original Well Elev)
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: EDM 2003.21 Single User Db

Survey

Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)
4,817.0	42.20	3.30	4,755.3	247.6	13.1	247.9	6.06	5.94	1.88
4,848.0	43.80	2.90	4,778.0	268.7	14.2	269.0	5.24	5.16	-1.29
4,880.0	45.50	3.20	4,800.8	291.2	15.4	291.5	5.35	5.31	0.94
4,912.0	47.70	3.10	4,822.8	314.4	16.7	314.7	6.88	6.88	-0.31
4,944.0	49.90	3.00	4,843.8	338.4	18.0	338.8	6.88	6.88	-0.31
4,975.0	50.40	2.80	4,863.7	362.2	19.2	362.6	1.69	1.61	-0.65
5,007.0	49.90	3.00	4,884.2	386.7	20.4	387.1	1.63	-1.56	0.63
5,039.0	49.90	2.30	4,904.8	411.2	21.5	411.6	1.67	0.00	-2.19
5,071.0	49.50	2.60	4,925.5	435.6	22.6	436.0	1.44	-1.25	0.94
5,102.0	49.60	2.80	4,945.6	459.1	23.7	459.6	0.59	0.32	0.65
5,134.0	51.30	3.20	4,966.0	483.8	25.0	484.2	5.40	5.31	1.25
5,166.0	53.60	4.00	4,985.5	509.1	26.6	509.6	7.46	7.19	2.50
5,197.0	56.10	4.10	5,003.4	534.4	28.4	534.9	8.07	8.06	0.32
5,229.0	59.10	3.90	5,020.5	561.3	30.3	561.9	9.39	9.38	-0.63
5,261.0	62.60	3.40	5,036.1	589.2	32.0	589.8	11.02	10.94	-1.56
5,293.0	66.20	2.30	5,049.9	618.0	33.5	618.7	11.67	11.25	-3.44
5,325.0	69.30	2.70	5,062.0	647.6	34.8	648.3	9.76	9.69	1.25
5,356.0	72.40	2.10	5,072.2	676.9	36.0	677.5	10.17	10.00	-1.94
5,388.0	75.50	1.90	5,081.0	707.6	37.1	708.3	9.71	9.69	-0.63
5,420.0	78.40	1.60	5,088.3	738.7	38.0	739.5	9.11	9.06	-0.94
5,452.0	81.60	0.90	5,093.8	770.2	38.7	771.0	10.23	10.00	-2.19
5,477.0	83.30	0.60	5,097.1	795.0	39.0	795.8	6.90	6.80	-1.20
5,541.0	86.20	1.30	5,103.0	858.7	40.1	859.5	4.66	4.53	1.09
5,573.0	86.60	1.10	5,105.0	890.7	40.7	891.4	1.40	1.25	-0.63
5,605.0	86.60	0.60	5,106.9	922.6	41.2	923.4	1.56	0.00	-1.56
5,636.0	86.90	0.90	5,108.6	953.6	41.6	954.3	1.37	0.97	0.97
5,668.0	87.10	0.50	5,110.3	985.5	42.0	986.3	1.40	0.63	-1.25
5,700.0	87.40	0.30	5,111.8	1,017.5	42.2	1,018.2	1.13	0.94	-0.63
5,732.0	86.90	0.30	5,113.4	1,049.4	42.4	1,050.2	1.56	-1.56	0.00
5,763.0	86.70	359.90	5,115.2	1,080.4	42.5	1,081.1	1.44	-0.65	-1.29
5,796.0	86.00	0.40	5,117.3	1,113.3	42.5	1,114.0	2.60	-2.12	1.52
5,828.0	86.30	0.80	5,119.4	1,145.2	42.9	1,146.0	1.56	0.94	1.25
5,860.0	87.70	0.20	5,121.1	1,177.2	43.2	1,177.9	4.76	4.38	-1.88
5,892.0	89.30	0.50	5,121.9	1,209.2	43.3	1,209.9	5.09	5.00	0.94
5,923.0	89.90	0.30	5,122.1	1,240.2	43.6	1,240.9	2.04	1.94	-0.65
5,955.0	90.20	359.90	5,122.1	1,272.2	43.6	1,272.9	1.56	0.94	-1.25
5,987.0	90.40	359.70	5,121.9	1,304.2	43.5	1,304.9	0.88	0.63	-0.63
6,019.0	91.00	359.80	5,121.6	1,336.2	43.4	1,336.9	1.90	1.88	0.31
6,051.0	91.20	359.80	5,120.9	1,368.2	43.3	1,368.8	0.63	0.63	0.00
6,083.0	91.60	359.50	5,120.2	1,400.2	43.1	1,400.8	1.56	1.25	-0.94
6,115.0	91.70	359.70	5,119.2	1,432.2	42.8	1,432.8	0.70	0.31	0.63
6,210.0	90.20	0.40	5,117.7	1,527.1	42.9	1,527.7	1.74	-1.58	0.74
6,306.0	90.50	0.40	5,117.1	1,623.1	43.6	1,623.7	0.31	0.31	0.00
6,401.0	91.60	359.90	5,115.3	1,718.1	43.8	1,718.7	1.27	1.16	-0.53
6,497.0	90.10	359.00	5,113.9	1,814.1	42.9	1,814.6	1.82	-1.56	-0.94
6,593.0	91.50	0.00	5,112.6	1,910.1	42.1	1,910.5	1.79	1.46	1.04
6,689.0	92.10	0.40	5,109.6	2,006.0	42.4	2,006.5	0.75	0.63	0.42
6,720.0	92.20	0.20	5,108.4	2,037.0	42.6	2,037.4	0.72	0.32	-0.65
6,784.0	87.90	359.70	5,108.3	2,101.0	42.5	2,101.4	6.76	-6.72	-0.78
6,816.0	86.80	359.30	5,109.8	2,133.0	42.2	2,133.3	3.66	-3.44	-1.25
6,848.0	86.60	358.00	5,111.7	2,164.9	41.5	2,165.3	4.10	-0.63	-4.06
6,880.0	87.10	358.20	5,113.4	2,196.8	40.4	2,197.1	1.68	1.56	0.63
6,912.0	88.10	358.30	5,114.8	2,228.8	39.5	2,229.1	3.14	3.13	0.31
6,944.0	89.10	359.50	5,115.5	2,260.8	38.8	2,261.0	4.88	3.13	3.75

Wolverine Directional, LLC

Survey Report

Company: Sandridge Energy
Project: Comanche (KS27S)
Site: Sec 19-T31S-19W - GRID
Well: Sean 1-18H
Wellbore: Wellbore #1
Design: Wellbore #1

Local Co-ordinate Reference: Well Sean 1-18H
TVD Reference: WELL @ 0.0ft (Original Well Elev)
MD Reference: WELL @ 0.0ft (Original Well Elev)
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: EDM 2003.21 Single User Db

Survey

Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N-S (ft)	+E-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)
6,975.0	90.40	359.50	5,115.7	2,291.8	38.6	2,292.0	4.19	4.19	0.00
7,007.0	90.70	0.60	5,115.4	2,323.8	38.6	2,324.0	3.56	0.94	3.44
7,039.0	90.60	0.40	5,115.0	2,355.8	38.9	2,356.0	0.70	-0.31	-0.63
7,071.0	90.40	359.90	5,114.7	2,387.8	39.0	2,388.0	1.68	-0.63	-1.56
7,103.0	90.00	0.00	5,114.6	2,419.8	38.9	2,420.0	1.29	-1.25	0.31
7,135.0	89.40	0.20	5,114.8	2,451.8	39.0	2,452.0	1.98	-1.88	0.63
7,167.0	89.10	359.80	5,115.2	2,483.8	39.0	2,484.0	1.56	-0.94	-1.25
7,199.0	89.20	0.20	5,115.7	2,515.8	39.0	2,515.9	1.29	0.31	1.25
7,230.0	89.20	0.50	5,116.1	2,546.7	39.2	2,546.9	0.97	0.00	0.97
7,262.0	89.40	1.80	5,116.5	2,578.7	39.8	2,578.9	4.11	0.63	4.06
7,294.0	90.90	1.80	5,116.4	2,610.7	40.8	2,610.9	4.69	4.89	0.00
7,326.0	92.80	2.40	5,115.4	2,642.7	42.0	2,642.9	6.23	5.94	1.88
7,358.0	93.50	2.90	5,113.6	2,674.6	43.5	2,674.8	2.69	2.19	1.56
7,390.0	93.10	2.80	5,111.8	2,706.5	45.1	2,706.8	1.29	-1.25	-0.31
7,422.0	90.90	2.40	5,110.7	2,738.5	46.5	2,738.8	6.99	-6.88	-1.25
7,453.0	91.20	2.90	5,110.1	2,769.4	47.9	2,769.7	1.88	0.97	1.61
7,485.0	90.20	2.30	5,109.7	2,801.4	49.4	2,801.7	3.64	-3.13	-1.88
7,517.0	89.10	2.30	5,109.9	2,833.4	50.7	2,833.7	3.44	-3.44	0.00
7,549.0	89.50	2.30	5,110.3	2,865.3	52.0	2,865.7	1.25	1.25	0.00
7,581.0	90.00	2.10	5,110.4	2,897.3	53.2	2,897.7	1.68	1.56	-0.63
7,613.0	90.40	1.90	5,110.3	2,929.3	54.3	2,929.7	1.40	1.25	-0.63
7,645.0	91.30	2.30	5,109.8	2,961.3	55.5	2,961.7	3.08	2.81	1.25
7,740.0	88.50	1.30	5,110.0	3,056.2	58.5	3,056.7	3.13	-2.95	-1.05
7,772.0	88.10	0.70	5,111.0	3,088.2	59.0	3,088.7	2.25	-1.25	-1.88
7,836.0	89.80	2.10	5,112.1	3,152.1	60.6	3,152.7	3.44	2.66	2.19
7,868.0	90.50	2.50	5,112.0	3,184.1	61.9	3,184.7	2.52	2.19	1.25
7,932.0	91.10	2.50	5,111.2	3,248.0	64.7	3,248.6	0.94	0.94	0.00
7,964.0	90.90	2.30	5,110.6	3,280.0	66.0	3,280.6	0.88	-0.63	-0.63
8,027.0	89.80	1.70	5,110.2	3,343.0	68.2	3,343.6	1.99	-1.75	-0.95
8,059.0	89.00	1.00	5,110.5	3,375.0	69.0	3,375.6	3.32	-2.50	-2.19
8,123.0	89.10	1.20	5,111.6	3,438.9	70.2	3,439.6	0.35	0.16	0.31
8,219.0	90.20	2.50	5,112.2	3,534.9	73.3	3,535.6	1.77	1.15	1.35
8,314.0	90.70	2.20	5,111.4	3,629.8	77.2	3,630.6	0.61	0.53	-0.32
8,410.0	91.80	2.10	5,109.4	3,725.7	80.8	3,726.6	1.15	1.15	-0.10
8,505.0	92.50	1.60	5,105.8	3,820.6	83.8	3,821.5	0.91	0.74	-0.53
8,537.0	92.60	1.40	5,104.4	3,852.6	84.7	3,853.5	0.70	0.31	-0.63
8,601.0	92.20	2.10	5,101.7	3,916.5	86.6	3,917.4	1.26	-0.63	1.09
8,696.0	91.30	3.20	5,098.8	4,011.3	91.0	4,012.3	1.50	-0.95	1.16
8,792.0	90.00	3.40	5,097.7	4,107.2	96.6	4,108.3	1.37	-1.35	0.21
8,824.0	90.30	3.80	5,097.6	4,139.1	98.6	4,140.3	1.56	0.94	1.25
8,887.0	89.80	2.60	5,097.6	4,202.0	102.1	4,203.2	2.06	-0.79	-1.90
8,983.0	88.00	1.20	5,099.4	4,297.9	105.3	4,299.2	2.38	-1.88	-1.46
9,015.0	88.80	1.60	5,100.3	4,329.9	106.0	4,331.2	2.79	2.50	1.25
9,079.0	88.60	1.40	5,101.7	4,393.8	107.7	4,395.2	0.44	-0.31	-0.31
9,174.0	90.50	1.50	5,102.5	4,488.8	110.1	4,490.2	2.00	2.00	0.11
9,270.0	90.50	1.60	5,101.7	4,584.8	112.7	4,586.2	0.10	0.00	0.10
9,365.0	91.40	1.80	5,100.1	4,679.7	115.5	4,681.1	0.97	0.95	0.21
9,461.0	93.90	2.90	5,095.6	4,775.5	119.5	4,777.0	2.84	2.60	1.15
9,524.0	93.50	2.30	5,091.6	4,838.3	122.3	4,839.9	1.14	-0.63	-0.95
9,556.0	92.90	3.00	5,089.8	4,870.2	123.8	4,871.8	2.88	-1.88	2.19
9,588.0	91.80	3.60	5,088.5	4,902.2	125.6	4,903.8	3.91	-3.44	1.88
9,620.0	90.70	3.20	5,087.8	4,934.1	127.5	4,935.7	3.66	-3.44	-1.25
9,652.0	90.60	3.30	5,087.4	4,966.0	129.3	4,967.7	0.44	-0.31	0.31
9,748.0	91.00	3.70	5,086.1	5,061.9	135.2	5,063.7	0.59	0.42	0.42

Wolverine Directional, LLC

Survey Report

Company: Sandridge Energy
Project: Comanche (KS27S)
Site: Sec 19-T31S-19W - GRID
Well: Sean 1-18H
Wellbore: Wellbore #1
Design: Wellbore #1

Local Co-ordinate Reference: Well Sean 1-18H
TVD Reference: WELL @ 0.0ft (Original Well Elev)
MD Reference: WELL @ 0.0ft (Original Well Elev)
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: EDM 2003.21 Single User Db

Survey

Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)	
9,810.0	91.20	3.70	5,084.9	5,123.7	139.2	5,125.6	0.32	0.32	0.00	
Last MWD Survey										
9,857.3	91.20	3.70	5,083.9	5,170.9	142.3	5,172.9	0.00	0.00	0.00	
Sean 1-18H PBHL										
9,860.0	91.20	3.70	5,083.8	5,173.6	142.4	5,175.5	0.00	0.00	0.00	
Proj to TD										

Survey Annotations

Measured Depth (ft)	Vertical Depth (ft)	Local Coordinates		Comment
		+N/-S (ft)	+E/-W (ft)	
947.0	947.0	-1.3	-2.1	First MWD Survey
9,810.0	5,084.9	5,123.7	139.2	Last MWD Survey
9,860.0	5,083.8	5,173.6	142.4	Proj to TD

Checked By: _____ **Approved By:** _____ **Date:** _____

Section 12
31S 20W

Section 7
31S 19W

371' FNL

BHL: 9830'

-99.431593 37.351505

1115' FWL

Bottom Perf: 9804'

-99.431598 37.351434

Section 13
31S 20W

Section 18
31S 19W

LOHRDING UNIT 1

ARLIE 18-1

ARLIE 18-2

Top Perf: 5390'
-99.431794 37.339324

Miss Entry: 5295'
-99.431804 37.339079

SEAN 1-18H

Section 24
31S 20W

Section 19
31S 19W



Actual Bottom-Hole Location of Sean 1-18H
Comanche County, Kansas
T&R: 31S 19W
Section: 18, 1115' FWL & 371' FNL
Long/Lat: -99.431593 37.351505


1 in = 667 ft



● Actual BH Location
* SandRidge Wells

Perf

Sections



Draftsman: Matt White
Draft Date: 3/15/2012

Drawing Name/Number:
Addendum_Seans_1-18H.mxd

Coordinate System:
NAD 1927 State Plane
Kansas South FIPS: 1502