

1 070363

To: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API NUMBER 15-101-21,395-00-00

NW NW SE, SEC. 24, T 18 S, R 28 W/E

2310 feet from S section line

2310 feet from E section line

Lease Name Parker Well # 1-24

County Lane Lane 151.78

Well Total Depth 4670 feet

Conductor Pipe: Size _____ feet

Surface Casing: Size 8 5/8 feet 253

TECHNICIAN'S PLUGGING REPORT

Operator License # 6113

Operator: Landmark Oil Exploration, Inc.

Name & Address 110 South Main, Suite 510

Wichita, KS 67202

Abandoned Oil Well _____ Gas Well _____ Input Well _____ SWD Well _____ D&A X

Other well as hereinafter indicated _____

Plugging Contractor Warrior Drilling Company License Number 5883

Address 151 North Main, Suite 700, Wichita, KS 67202

Company to plug at: Hour: 11:30 a.m. Day: 4 Month: 7 Year: 19 87

Plugging proposal received from Marion Burris

(company name) Warrior Drilling Company (phone) 316-653-7716

were: to fill hole with heavy mud and spot cement through drill pipe Elevation 2716 KB
Anhydrite 2077-2114'

1st plug at 2120' with 50 sx cement, 2nd plug at 1250' with 80 sx cement,

3rd plug at 280' with 50 sx cement, 4th plug at 40-0' with 10 sx cement,

5th plug to circulate rathole with 15 sx cement,

6th plug to circulate mousehole with 10 sx cement.

Plugging Proposal Received by Paul Luthi
(TECHNICIAN)

Plugging Operations attended by Agent?: All _____ Part _____ None X

Operations Completed: Hour: 2:45 p.m. Day: 4 Month: 7 Year: 19 87

ACTUAL PLUGGING REPORT 1st plug at 2120' with 50 sx cement,

2nd plug at 1250' with 80 sx cement,

3rd plug at 280' with 50 sx cement,

4th plug at 40-0' with 10 sx cement,

5th plug to circulate rathole with 15 sx cement,

6th plug to circulate mousehole with 10 sx cement.

RECEIVED
STATE CORPORATION COMMISSION

JUL 7 1987

CONSERVATION DIVISION
Wichita Kansas

Remarks: Used 60/40 Pozmix 6% gel by B.J. Titan.

(If additional description is necessary, use BACK of this form.)

INVOICED

(do not) observe this plugging.

DATE 7-7-87

Signed Dan Goodson
(TECHNICIAN)

INV. NO. 17437

CARD MUST BE TYPED

State of Kansas

CARD MUST BE SIGNED

NOTICE OF INTENTION TO DRILL

(see rules on reverse side)

Starting Date June 20 1987 month day year

API Number 15-101-21,395-00-00

OPERATOR: License # 06113 Name Landmark Oil Exploration, Inc. Address 110 S. Main, Suite 510 City/State/Zip Wichita, Kansas 67202 Contact Person Jeff Wood Phone (316) 265-8181

NW NW SE Sec 24 Twp 18 S, Rg 28 X West 2310 Ft. from South Line of Section 2310 Ft. from East Line of Section

(Note: Locate well on Section Plat on reverse side)

CONTRACTOR: License # 5883 Name Warrior Drilling Company City/State Wichita, Kansas

Nearest lease or unit boundary line 330 feet County Lane Lease Name Parker Well # 1-24

Well Drilled For: X Oil SWD Infield Mud Rotary Gas Inj Pool Ext Air Rotary OWWO Exp Wildcat Cable

Ground surface elevation feet MSL Domestic well within 330 feet: yes X no Municipal well within one mile: yes X no

If OWWO: old well info as follows: Operator Well Name Comp Date Old Total Depth

Depth to bottom of fresh water 75' Depth to bottom of usable water 1250' Surface pipe by Alternate: 1 X Surface pipe planned to be set 250 feet

I certify that well will comply with K.S.A. 55-101, et seq., plus eventually plugging hole to KCC specifications. Date 6-16-87 Signature of Operator or Agent Title Geologist

For KCC Use: Conductor Pipe Required feet; Minimum Surface Pipe Required 250 feet per Alt. 40 This Authorization Expires 12-16-87 Approved By 6-16-87

Set 290' of 8 5/8 on 6-26-87 RL will get plug proposal later

NW NW SE Sec 24 Twp 18 S, Rg 28 X East West

PLUGGING PROPOSAL IF ABOVE IS D & A

This plugging proposal will be reviewed and approved or revised at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).

1st plug @ Base Anhydrite feet depth with 50 sxs of 2nd plug @ Base Cheyenne feet depth with 80 sxs of 3rd plug @ 30' Below Surface feet depth with 40 sxs of 4th plug @ 40' To Surface feet depth with 10 sxs of 5th plug @ feet depth with sxs of (2) Rathole with 10 sxs (b) Mousehole with 10 sxs

PUSHER Marion Darris TD 4670' FORMATION MISS SURFACE PIPE 8 5/8 @ 253 ANHYDRITE 2077 ELEVATION 2716.88 STARTING TIME & DATE 11:30 AM 7-4-87 COMPLETION TIME & DATE 2:45 PM 7-4-87 1st PLUG @ 2120 FT. W/ 50 SX 2nd PLUG @ 1250 FT. W/ 80 SX 3rd PLUG @ 280 FT. W/ 50 SX 4th PLUG @ 40-0 FT. W/ 10 SX RAT HOLE CIRCULATED W/ 15 SX MOUSE HOLE CIRCULATED W/ 10 SX WATER WELL PLUGGED W/ CEMENT COMPANY B.J. Titon TECHNICIAN Dan Goodrow, Saw Aone R.F. 60/40 w/ 6% gel

RECEIVED STATE CORPORATION COMMISSION JUL 17 1987 CONSERVATION DIVISION Wichita, Kansas