

1 070965

6-26

API NUMBER 19- 101-21,339 -0000 7 179

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

NE NE NE, SEC. 1, T. 17 S, R. 30  
4950 feet from S section line  
330 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 6113

Lease Name Jennison "B" Well # 1

Operator: Landmark Oil Exploration

County Lane 149.63

Name & Address 250 N. Water, Suite 308

Well Total Depth 4604 feet

Wichita, KS 67202

Conductor Pipe: Size \_\_\_\_\_ feet

Surface Casing: Size 8 5/8 feet 268

Abandoned Oil Well  Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A \_\_\_\_\_

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Hembree Well Service License Number 6907

Address P.O. Box 458, Ness City, KS 67560

Company to plug at: Hour: 10:20 a.m. Day: 26 Month: 6 Year: 19 91

Plugging proposal received from George Harmison

(company name) Hembree Well Service (phone) 913-798-3408

were: 4 1/2" at 4589' w/175 sx cement, Perfs at 4377-83', PC @ 2236' w/330 sx cement to 0'  
1st plug pump 500 lbs. hulls and 300 lbs. hulls in first part of 150 sx Thrifty Mix cement  
down 4 1/2".

Check backside.

Plugging Proposal Received by Dan Goodrow (TECHNICIAN)

Plugging Operations attended by Agent?: All  Part \_\_\_\_\_ None \_\_\_\_\_

Operations Completed: Hour: 10:50 a.m. Day: 26 Month: 6 Year: 19 91

ACTUAL PLUGGING REPORT 1st plug pumped 500 lbs. hulls and 300 lbs. hulls in first part  
of 150 sx Thrifty Mix cement down 4 1/2". Maximum pressure 700 psi and shut in 0 psi.

Backside would not take.

RECEIVED STATE CORPORATION COMMISSION

JUL 01 1991

CONSERVATION DIVISION Wichita, Kansas

Remarks: Used Thrifty Mix by B.J. Services. No casing recovery.  
(if additional description is necessary, use BACK of this form.)

observe this plugging.

Signed Dan Goodrow (TECHNICIAN)

INVOICED

DATE JUL 22 1991

INV. NO. 32331

6-26